



ARMv8 Instruction Set Overview

Architecture Group

Document number: **PRD03-GENC-010197 24.0**
Date of Issue: 5 July 2012

© Copyright ARM Limited 2009-2012. All rights reserved.

Abstract

This document provides a high-level overview of the ARMv8 instructions sets, being mainly the new A64 instruction set used in AArch64 state but also those new instructions added to the A32 and T32 instruction sets since ARMv7-A for use in AArch32 state. For A64 this document specifies the preferred architectural assembly language notation to represent the new instruction set.

Keywords

AArch64, A64, AArch32, A32, T32, ARMv8

Proprietary Notice

This specification is protected by copyright and the practice or implementation of the information herein may be protected by one or more patents or pending applications. No part of this specification may be reproduced in any form by any means without the express prior written permission of ARM. **No license, express or implied, by estoppel or otherwise to any intellectual property rights is granted by this specification.**

Your access to the information in this specification is conditional upon your acceptance that you will not use or permit others to use the information for the purposes of determining whether implementations of the ARM architecture infringe any third party patents.

This specification is provided “as is”. ARM makes no representations or warranties, either express or implied, included but not limited to, warranties of merchantability, fitness for a particular purpose, or non-infringement, that the content of this specification is suitable for any particular purpose or that any practice or implementation of the contents of the specification will not infringe any third party patents, copyrights, trade secrets, or other rights.

This specification may include technical inaccuracies or typographical errors.

To the extent not prohibited by law, in no event will ARM be liable for any damages, including without limitation any direct loss, lost revenue, lost profits or data, special, indirect, consequential, incidental or punitive damages, however caused and regardless of the theory of liability, arising out of or related to any furnishing, practicing, modifying or any use of this specification, even if ARM has been advised of the possibility of such damages.

Words and logos marked with ® or TM are registered trademarks or trademarks of ARM Limited, except as otherwise stated below in this proprietary notice. Other brands and names mentioned herein may be the trademarks of their respective owners.

Copyright © 2009-2012 ARM Limited

110 Fulbourn Road, Cambridge, England CB1 9NJ

Restricted Rights Legend: Use, duplication or disclosure by the United States Government is subject to the restrictions set forth in DFARS 252.227-7013 (c)(1)(ii) and FAR 52.227-19.

This document is Non-Confidential but any disclosure by you is subject to you providing notice to and the acceptance by the recipient of, the conditions set out above.

In this document, where the term ARM is used to refer to the company it means “ARM or any of its subsidiaries as appropriate”.

Contents

| | | |
|----------|--|-----------|
| 1 | ABOUT THIS DOCUMENT | 7 |
| 1.1 | Change control | 7 |
| 1.1.1 | Current status and anticipated changes | 7 |
| 1.1.2 | Change history | 7 |
| 1.2 | References | 9 |
| 1.3 | Terms and abbreviations | 9 |
| 2 | INTRODUCTION | 10 |
| 3 | A64 OVERVIEW | 10 |
| 3.1 | Distinguishing 32-bit and 64-bit Instructions | 12 |
| 3.2 | Conditional Instructions | 12 |
| 3.3 | Addressing Features | 13 |
| 3.3.1 | Register Indexed Addressing | 13 |
| 3.3.2 | PC-relative Addressing | 13 |
| 3.4 | The Program Counter (PC) | 13 |
| 3.5 | Memory Load-Store | 13 |
| 3.5.1 | Bulk Transfers | 13 |
| 3.5.2 | Exclusive Accesses | 14 |
| 3.5.3 | Load-Acquire, Store-Release | 14 |
| 3.6 | Integer Multiply/Divide | 14 |
| 3.7 | Scalar Floating Point | 14 |
| 3.8 | Advanced SIMD | 15 |
| 4 | A64 ASSEMBLY LANGUAGE | 16 |
| 4.1 | Basic Structure | 16 |
| 4.2 | Instruction Mnemonics | 16 |
| 4.3 | Condition Codes | 17 |
| 4.4 | Register Names | 19 |
| 4.4.1 | General purpose (integer) registers | 19 |
| 4.4.2 | FP/SIMD registers | 20 |
| 4.5 | Load/Store Addressing Modes | 22 |
| 4.5.1 | Address Computation | 23 |

| | | |
|------------|--|-----------|
| 5 | A64 INSTRUCTION SET | 24 |
| 5.1 | Common Terms | 24 |
| 5.2 | Control Flow | 25 |
| 5.2.1 | Conditional Branch | 25 |
| 5.2.2 | Unconditional Branch (immediate) | 25 |
| 5.2.3 | Unconditional Branch (register) | 25 |
| 5.3 | Memory Access | 26 |
| 5.3.1 | Load-Store Single Register | 26 |
| 5.3.2 | Load-Store Single Register (unscaled offset) | 27 |
| 5.3.3 | Load-Store Pair | 28 |
| 5.3.4 | Load-Store Non-temporal Pair | 29 |
| 5.3.5 | Load-Store Unprivileged | 30 |
| 5.3.6 | Load-Store Exclusive | 31 |
| 5.3.7 | Load-Acquire / Store-Release | 32 |
| 5.3.8 | Prefetch Memory | 33 |
| 5.4 | Data Processing (immediate) | 34 |
| 5.4.1 | Arithmetic (immediate) | 34 |
| 5.4.2 | Logical (immediate) | 35 |
| 5.4.3 | Move (wide immediate) | 36 |
| 5.4.4 | PC-relative Address Calculation | 37 |
| 5.4.5 | Bitfield Operations | 37 |
| 5.4.6 | Extract (immediate) | 39 |
| 5.4.7 | Shift (immediate) | 39 |
| 5.4.8 | Sign/Zero Extend | 39 |
| 5.5 | Data Processing (register) | 40 |
| 5.5.1 | Arithmetic (shifted register) | 40 |
| 5.5.2 | Arithmetic (extending register) | 41 |
| 5.5.3 | Logical (shifted register) | 43 |
| 5.5.4 | Variable Shift | 44 |
| 5.5.5 | Bit Operations | 45 |
| 5.5.6 | Conditional Data Processing | 46 |
| 5.5.7 | Conditional Comparison | 48 |
| 5.6 | Integer Multiply / Divide | 48 |
| 5.6.1 | Multiply | 48 |
| 5.6.2 | Divide | 49 |
| 5.7 | Scalar Floating-point | 51 |
| 5.7.1 | Floating-point/SIMD Scalar Memory Access | 51 |
| 5.7.2 | Floating-point Move (register) | 54 |
| 5.7.3 | Floating-point Move (immediate) | 54 |
| 5.7.4 | Floating-point Convert | 55 |
| 5.7.5 | Floating-point Round to Integral | 57 |
| 5.7.6 | Floating-point Arithmetic (1 source) | 58 |
| 5.7.7 | Floating-point Arithmetic (2 source) | 58 |
| 5.7.8 | Floating-point Min/Max | 58 |
| 5.7.9 | Floating-point Multiply-Add | 59 |
| 5.7.10 | Floating-point Comparison | 59 |
| 5.7.11 | Floating-point Conditional Select | 60 |
| 5.8 | Advanced SIMD | 61 |

| | | |
|------------|--|------------|
| 5.8.1 | Overview | 61 |
| 5.8.2 | Advanced SIMD Mnemonics | 62 |
| 5.8.3 | Data Movement | 62 |
| 5.8.4 | Vector Arithmetic | 64 |
| 5.8.5 | Scalar Arithmetic | 68 |
| 5.8.6 | Vector Widening/Narrowing Arithmetic | 71 |
| 5.8.7 | Scalar Widening/Narrowing Arithmetic | 74 |
| 5.8.8 | Vector Unary Arithmetic | 74 |
| 5.8.9 | Scalar Unary Arithmetic | 76 |
| 5.8.10 | Vector-by-element Arithmetic | 77 |
| 5.8.11 | Scalar-by-element Arithmetic | 79 |
| 5.8.12 | Vector Permute | 80 |
| 5.8.13 | Vector Immediate | 80 |
| 5.8.14 | Vector Shift (immediate) | 81 |
| 5.8.15 | Scalar Shift (immediate) | 84 |
| 5.8.16 | Vector Floating Point / Integer Convert | 85 |
| 5.8.17 | Scalar Floating Point / Integer Convert | 86 |
| 5.8.18 | Vector Reduce (across lanes) | 86 |
| 5.8.19 | Vector Pairwise Arithmetic | 87 |
| 5.8.20 | Scalar Reduce (pairwise) | 88 |
| 5.8.21 | Vector Table Lookup | 88 |
| 5.8.22 | Vector Load-Store Structure | 89 |
| 5.8.23 | AArch32 Equivalent Advanced SIMD Mnemonics | 91 |
| 5.8.24 | Crypto Extension | 98 |
| 5.9 | System Instructions | 99 |
| 5.9.1 | Exception Generation and Return | 99 |
| 5.9.2 | System Register Access | 100 |
| 5.9.3 | System Management | 100 |
| 5.9.4 | Architectural Hints | 103 |
| 5.9.5 | Barriers and CLREX | 103 |
| 6 | A32 & T32 INSTRUCTION SETS | 105 |
| 6.1 | Partial Deprecation of IT | 106 |
| 6.2 | Load-Acquire / Store-Release | 106 |
| 6.2.1 | Non-Exclusive | 106 |
| 6.2.2 | Exclusive | 107 |
| 6.3 | VFP Scalar Floating-point | 108 |
| 6.3.1 | Floating-point Conditional Select | 108 |
| 6.3.2 | Floating-point minNum/maxNum | 108 |
| 6.3.3 | Floating-point Convert (floating-point to integer) | 108 |
| 6.3.4 | Floating-point Convert (half-precision to/from double-precision) | 109 |
| 6.3.5 | Floating-point Round to Integral | 109 |
| 6.4 | Advanced SIMD Floating-Point | 110 |
| 6.4.1 | Floating-point minNum/maxNum | 110 |
| 6.4.2 | Floating-point Convert | 110 |
| 6.4.3 | Floating-point Round to Integral | 110 |
| 6.5 | Crypto Extension | 111 |
| 6.6 | System Instructions | 112 |

| | | |
|-------|--------------------|-----|
| 6.6.1 | Halting Debug | 112 |
| 6.6.2 | Barriers and Hints | 112 |
| 6.6.3 | TLB Maintenance | 112 |

1 ABOUT THIS DOCUMENT

1.1 Change control

1.1.1 Current status and anticipated changes

This document is a released specification although further changes to correct defects and improve clarity should be expected.

1.1.2 Change history

| Issue | Date | By | Change |
|-------|---------------------------------|-----|--|
| | | NJS | Previous releases tracked in Domino |
| 7.0 | 17th December 2010 | NJS | Beta0 release |
| 8.0 | 25 th February 2011 | NJS | Beta0 update 1 |
| 9.0 | 20 th April 2011 | NJS | Beta1 release |
| 10.0 | 14 th July 2011 | NJS | Beta2 release |
| 11.0 | 9 th September 2011 | NJS | Beta2 update 1 |
| 12.0 | 28 th September 2011 | NJS | Beta3 release |
| 13.0 | 28 th October 2011 | NJS | Beta3 update 1 |
| 14.0 | 28 th October 2011 | NJS | Restructured and incorporated new AArch32 instructions. |
| 15.0 | 11 th November 2011 | NJS | First non-confidential release. Describe partial deprecation of the <code>IT</code> instruction. Rename <code>DRET</code> to <code>DRPS</code> and clarify its behavior. |
| 16.0 | 30 th November 2011 | NJS | Beta3 update 2. Minor typos and clarifications. |
| 19.0 | 28 th January 2012 | NJS | Improve description of addressing modes and use those terms consistently. Clarify recommendations for <code>FMOV</code> of constant <code>0.0</code> . Add AdvSIMD "MOV" alias for " <code>ORR Vd, Vn, Vn</code> ". Swap <code>UQADD</code> and <code>SQADD</code> in AArch32 AdvSIMD equivalents table. Use " <code>Rt.1</code> " consistently for first transfer register of load/store-pair instructions. Clarify rounding mode used by some floating-point converts. |
| 20.0 | 27 th March 2012 | NJS | Deleted alternating register forms of A64 AdvSIMD structure load-store instructions. Add AdvSIMD <code>SHLL{2}</code> instructions. Fix AdvSIMD scalar <code>[US] QSHL & SQSHLU</code> operand types. List included, deprecated and obsoleted ARMv7-A extensions and features. |
| 21.0 | 30 th March 2012 | NJS | Clarify compatibility of Debug, PMU and ETM extensions with ARMv7 software. Add new A32/T32 TLB maintenance operations. Remove dangling reference to AdvSIMD alternating registers. |
| 22.0 | 30th April 2012 | NJS | Permit <code>SP/WSP</code> as dest in <code>MOVI</code> and <code>MOV</code> (immediate) aliases. Remove " <code>UXT [BHW] Xd, Wn</code> " aliases and add " <code>UXTW Wd, Wn</code> ". AdvSIMD floating point "by element" allow <code>V0-31</code> for <code>Vm</code> . Add <code>MOV</code> aliases for AdvSIMD <code>UMOV</code> . Fix vector element index ranges. |

| | | | |
|------|---------------|-----|--|
| 23.0 | 1st June 2012 | NJS | Improve description of logical bitmask immediates. Delete the <code>MOVI</code> alias for <code>ORR</code> (immediate with zero register), the <code>MOV</code> alias is usually preferred. |
| 24.0 | 5th July 2012 | NJS | Use a legal implementation-defined register name in <code>MRS/MSR</code> example. Describe the <code>FCVTXN</code> semantics more clearly. Remove the <code>UXTW</code> architectural alias. Correct the maximum number of fractional bits Advanced SIMD fixed-point converts. Correct the supported data types for <code>SQDMLAL</code> (scalar). Correct the assembler syntax for <code>INS</code> (general register). |

1.2 References

This document refers to the following documents.

| Reference | Author | Document number | Title |
|-----------|------------------|-----------------|---|
| [v7A] | ARM | ARM DDI 0406C | ARM® Architecture Reference Manual, ARMv7-A and ARMv7-R edition |
| [AES] | NIST | FIPS 197 | Announcing the Advanced Encryption Standard (AES) |
| [SHA] | NIST | FIPS 180-2 | Announcing the Secure Hash Standard (SHA) |
| [GCM] | McGrew and Viega | n/a | The Galois/Counter Mode of Operation (GCM) |

1.3 Terms and abbreviations

This document uses the following terms and abbreviations.

| Term | Meaning |
|-------------|--|
| AArch64 | The 64-bit general purpose register width state of the ARMv8 architecture. |
| AArch32 | The 32-bit general purpose register width state of the ARMv8 architecture, broadly compatible with the ARMv7-A architecture. Note: The register width state can change only upon a change of exception level. |
| A64 | The new instruction set available when in AArch64 state, and described in this document. |
| A32 | The instruction set named ARM in the ARMv7 architecture, which uses 32-bit instructions. The new A32 instructions added by ARMv8 are described in §6. |
| T32 | The instruction set named Thumb in the ARMv7 architecture, which uses 16-bit and 32-bit instructions. The new T32 instructions added by ARMv8 are described in §6. |
| UNALLOCATED | Describes an opcode or combination of opcode fields which do not select a valid instruction at the current privilege level. Executing an UNALLOCATED encoding will usually result in taking an Undefined Instruction exception. |
| RESERVED | Describes an instruction field value within an otherwise allocated instruction which should not be used within this specific instruction context, for example a value which selects an unsupported data type or addressing mode. An instruction encoding which contains a RESERVED field value is an UNALLOCATED encoding. |

2 INTRODUCTION

This document provides an overview of the ARMv8 instruction sets. Most of the document forms a description of the new A64 instruction set used when the processor is operating in AArch64 register width state, and defines its preferred architectural assembly language.

Section 6 below lists the extensions introduced by ARMv8 to the A32 and T32 instruction sets – known in ARMv7 as the ARM and Thumb instruction sets respectively – which are available when the processor is operating in AArch32 register width state. The A32 and T32 assembly language syntax is unchanged from ARMv7.

In the syntax descriptions below the following conventions are used:

- UPPER UPPER-CASE text is fixed, while lower-case text is variable. So register name x_n indicates that the 'x' is required, followed by a variable register number, e.g. x_{29} .
- < > Any item bracketed by < and > is a short description of a type of value to be supplied by the user in that position. A longer description of the item is normally supplied by subsequent text.
- { } Any item bracketed by curly braces { and } is optional. A description of the item and of how its presence or absence affects the instruction is normally supplied by subsequent text. In some cases curly braces are actual symbols in the syntax, for example surrounding a register list, and such cases will be called out in the surrounding text.
- [] A list of alternative characters may be bracketed by [and]. A single one of the characters can be used in that position and the subsequent text will describe the meaning of the alternatives. In some cases the symbols [and] are part of the syntax itself, such as addressing modes and vector elements, and such cases will be called out in the surrounding text.
- a | b Alternative words are separated by a vertical bar | and may be surrounded by parentheses to delimit them, e.g. $U(ADD|SUB)W$ represents $UADDW$ or $USUBW$.
- +/- This indicates an optional + or - sign. If neither is coded, then + is assumed.

3 A64 OVERVIEW

The A64 instruction set provides similar functionality to the A32 and T32 instruction sets in AArch32 or ARMv7. However just as the addition of 32-bit instructions to the T32 instruction set rationalized some of the ARM ISA behaviors, the A64 instruction set includes further rationalizations. The highlights of the new instruction set are as follows:

- A clean, fixed length instruction set – instructions are 32 bits wide, register fields are contiguous bit fields at fixed positions, immediate values mostly occupy contiguous bit fields.
- Access to a larger general-purpose register file with 31 unbanked registers (0-30), with each register extended to 64 bits. General registers are encoded as 5-bit fields with register number 31 (0b11111) being a special case representing:
 - *Zero Register*: in most cases register number 31 reads as zero when used as a source register, and discards the result when used as a destination register.
 - *Stack Pointer*: when used as a load/store base register, and in a small selection of arithmetic instructions, register number 31 provides access to the *current stack pointer*.
- The PC is never accessible as a named register. Its use is implicit in certain instructions such as PC-relative load and address generation. The only instructions which cause a non-sequential change to the PC are the designated Control Flow instructions (see §5.2) and exceptions. The PC cannot be specified as the destination of a data processing instruction or load instruction.

-
- The procedure call link register (LR) is unbanked, general-purpose register 30; exceptions save the restart PC to the target exception level's ELR system register.
 - Scalar load/store addressing modes are uniform across all sizes and signedness of scalar integer, floating point and vector registers.
 - A load/store immediate offset may be scaled by the access size, increasing its effective offset range.
 - A load/store index register may contain a 64-bit or 32-bit signed/unsigned value, optionally scaled by the access size.
 - Arithmetic instructions for address generation which mirror the load/store addressing modes, see §3.3.
 - PC-relative load/store and address generation with a range of $\pm 4\text{GiB}$ is possible using just two instructions without the need to load an offset from a literal pool.
 - PC-relative offsets for literal pool access and most conditional branches are extended to $\pm 1\text{MiB}$, and for unconditional branches and calls to $\pm 128\text{MiB}$.
 - There are no multiple register LDM, STM, PUSH and POP instructions, but load-store of a non-contiguous pair of registers is available.
 - Unaligned addresses are permitted for most loads and stores, including paired register accesses, floating point and SIMD registers, with the exception of exclusive and ordered accesses (see §3.5.2).
 - Reduced conditionality. Fewer instructions can set the condition flags. Only conditional branches, and a handful of data processing instructions read the condition flags. Conditional or predicated execution is not provided, and there is no equivalent of T32's IT instruction (see §3.2).
 - A shift option for the final register operand of data processing instructions is available:
 - Immediate shifts only (as in T32).
 - No RRX shift, and no ROR shift for ADD/SUB.
 - The ADD/SUB/CMP instructions can first sign or zero-extend a byte, halfword or word in the final register operand, followed by an optional left shift of 1 to 4 bits.
 - Immediate generation replaces A32's rotated 8-bit immediate with operation-specific encodings:
 - Arithmetic instructions have a simple 12-bit immediate, with an optional left shift by 12.
 - Logical instructions provide sophisticated replicating bit mask generation.
 - Other immediates may be constructed inline in 16-bit "chunks", extending upon the MOVW and MOVW instructions of AArch32.
 - Floating point support is similar to AArch32 VFP but with some extensions, as described in §3.6.
 - Floating point and Advanced SIMD processing share a register file, in a similar manner to AArch32, but extended to thirty-two 128-bit registers. Smaller registers are no longer packed into larger registers, but are mapped one-to-one to the low-order bits of the 128-bit register, as described in §4.4.2.
 - There are no SIMD or saturating arithmetic instructions which operate on the general purpose registers, such operations being available only as part of the Advanced SIMD processing, described in §5.8.
 - There is no access to CPSR as a single register, but new system instructions provide the ability to atomically modify individual processor state fields, see §5.9.2.
 - The concept of a "coprocessor" is removed from the architecture. A set of system instructions described in §5.9 provides:
 - System register access
 - Cache/TLB management
 - VA \leftrightarrow PA translation
 - Barriers and CLREX
 - Architectural hints (WFI, etc)
 - Debug
-

3.1 Distinguishing 32-bit and 64-bit Instructions

Most integer instructions in the A64 instruction set have two forms, which operate on either 32-bit or 64-bit values within the 64-bit general-purpose register file. Where a 32-bit instruction form is selected, the following holds true:

- The upper 32 bits of the source registers are ignored;
- The upper 32 bits of the destination register are set to ZERO;
- Right shifts/rotates inject at bit 31, instead of bit 63;
- The condition flags, where set by the instruction, are computed from the lower 32 bits.

This distinction applies even when the result(s) of a 32-bit instruction form would be indistinguishable from the lower 32 bits computed by the equivalent 64-bit instruction form. For example a 32-bit bitwise `ORR` could be performed using a 64-bit `ORR`, and simply ignoring the top 32 bits of the result. But the A64 instruction set includes separate 32 and 64-bit forms of the `ORR` instruction.

Rationale: The C/C++ LP64 and LLP64 data models – expected to be the most commonly used on AArch64 – both define the frequently used `int`, `short` and `char` types to be 32 bits or less. By maintaining this semantic information in the instruction set, implementations can exploit this information to avoid expending energy or cycles to compute, forward and store the unused upper 32 bits of such data types. Implementations are free to exploit this freedom in whatever way they choose to save energy.

As well as distinct sign/zero-extend instructions, the A64 instruction set also provides the ability to extend and shift the final source register of an `ADD`, `SUB` or `CMP` instruction and the index register of a load/store instruction. This allows for an efficient implementation of array index calculations involving a 64-bit array pointer and 32-bit array index.

The assembly language notation is designed to allow the identification of registers holding 32-bit values as distinct from those holding 64-bit values. As well as aiding readability, tools may be able to use this to perform limited type checking, to identify programming errors resulting from the change in register size.

3.2 Conditional Instructions

The A64 instruction set does not include the concept of predicated or conditional execution. Benchmarking shows that modern branch predictors work well enough that predicated execution of instructions does not offer sufficient benefit to justify its significant use of opcode space, and its implementation cost in advanced implementations.

A very small set of “conditional data processing” instructions are provided. These instructions are unconditionally executed but use the condition flags as an extra input to the instruction. This set has been shown to be beneficial in situations where conditional branches predict poorly, or are otherwise inefficient.

The conditional instruction types are:

- Conditional branch: the traditional ARM conditional branch, together with compare and branch if register zero/non-zero, and test single bit in register and branch if zero/non-zero – all with increased displacement.
- Add/subtract with carry: the traditional ARM instructions, for multi-precision arithmetic, checksums, etc.
- Conditional select with increment, negate or invert: conditionally select between one source register and a second incremented/negated/inverted/unmodified source register. Benchmarking reveals these to be the highest frequency uses of single conditional instructions, e.g. for counting, absolute value, etc. These instructions also implement:
 - Conditional select (move): sets the destination to one of two source registers, selected by the condition flags. Short conditional sequences can be replaced by unconditional instructions followed by a conditional select.
 - Conditional set: conditionally select between 0 and 1 or -1, for example to materialize the condition flags as a Boolean value or mask in a general register.
- Conditional compare: sets the condition flags to the result of a comparison if the original condition was true, else to an immediate value. Permits the flattening of nested conditional expressions without using conditional branches or performing Boolean arithmetic within general registers.

3.3 Addressing Features

The prime motivation for a 64-bit architecture is access to a larger virtual address space. The AArch64 memory translation system supports a 49-bit virtual address (48 bits per translation table). Virtual addresses are sign-extended from 49 bits, and stored within a 64-bit pointer. Optionally, under control of a system register, the most significant 8 bits of a 64-bit pointer may hold a “tag” which will be ignored when used as a load/store address or the target of an indirect branch.

3.3.1 Register Indexed Addressing

The A64 instruction set extends on 32-bit T32 addressing modes, allowing a 64-bit index register to be added to the 64-bit base register, with optional scaling of the index by the access size. Additionally it provides for sign or zero-extension of a 32-bit value within an index register, again with optional scaling.

These register index addressing modes provide a useful performance gain if they can be performed within a single cycle, and it is believed that at least some implementations will be able to do this. However, based on implementation experience with AArch32, it is expected that other implementations will need an additional cycle to execute such addressing modes.

Rationale: The architects intend that implementations should be free to fine-tune the performance trade-offs within each implementation, and note that providing an instruction which in some implementations takes two cycles, is preferable to requiring the dynamic grouping of two independent instructions in an implementation that can perform this address arithmetic in a single cycle.

3.3.2 PC-relative Addressing

There is improved support for position-independent code and data addressing:

- PC-relative literal loads have an offset range of $\pm 1\text{MiB}$. This permits fewer literal pools, and more sharing of literal data between functions – reducing I-cache and TLB pollution.
- Most conditional branches have a range of $\pm 1\text{MiB}$, expected to be sufficient for the majority of conditional branches which take place within a single function.
- Unconditional branches, including branch and link, have a range of $\pm 128\text{MiB}$. Expected to be sufficient to span the static code segment of most executable load modules and shared objects, without needing linker-inserted trampolines or “veneers”.
- PC-relative load/store and address generation with a range of $\pm 4\text{GiB}$ may be performed inline using only two instructions, i.e. without the need to load an offset from a literal pool.

3.4 The Program Counter (PC)

The current Program Counter (PC) cannot be referred to by number as if part of the general register file and therefore cannot be used as the source or destination of arithmetic instructions, or as the base, index or transfer register of load/store instructions. The only instructions which read the PC are those whose function is to compute a PC-relative address (*ADR*, *ADRP*, literal load, and direct branches), and the branch-and-link instructions which store it in the link register (*BL* and *BLR*). The only way to modify the Program Counter is using explicit control flow instructions: conditional branch, unconditional branch, exception generation and exception return instructions.

Where the PC is read by an instruction to compute a PC-relative address, then its value is the address of the instruction, i.e. unlike A32 and T32 there is no implied offset of 4 or 8 bytes.

3.5 Memory Load-Store

3.5.1 Bulk Transfers

The *LDM*, *STM*, *PUSH* and *POP* instructions do not exist in A64, however bulk transfers can be constructed using the *LDP* and *STP* instructions which load and store a pair of independent registers from consecutive memory locations, and which support unaligned addresses when accessing normal memory. The *LDNP* and

STNP instructions additionally provide a “streaming” or “non-temporal” hint that the data does not need to be retained in caches. The PRFM (prefetch memory) instructions also include hints for “streaming” or “non-temporal” accesses, and allow targeting of a prefetch to a specific cache level.

3.5.2 Exclusive Accesses

Exclusive load-store of a byte, halfword, word and doubleword. Exclusive access to a pair of doublewords permit atomic updates of a pair of pointers, for example circular list inserts. All exclusive accesses must be naturally aligned, and exclusive pair access must be aligned to twice the data size (i.e. 16 bytes for a 64-bit pair).

3.5.3 Load-Acquire, Store-Release

Explicitly synchronising load and store instructions implement the release-consistency (RCsc) memory model, reducing the need for explicit memory barriers, and providing a good match to emerging language standards for shared memory. The instructions exist in both exclusive and non-exclusive forms, and require natural address alignment. See §5.3.7 for more details.

3.6 Integer Multiply/Divide

Including 32 and 64-bit multiply, with accumulation:

- $32 \pm (32 \times 32) \rightarrow 32$
- $64 \pm (64 \times 64) \rightarrow 64$
- $\pm (32 \times 32) \rightarrow 32$
- $\pm (64 \times 64) \rightarrow 64$

Widening multiply (signed and unsigned), with accumulation:

- $64 \pm (32 \times 32) \rightarrow 64$
- $\pm (32 \times 32) \rightarrow 64$
- $(64 \times 64) \rightarrow \text{hi64} \langle 127:64 \rangle$

Multiply instructions write a single register. A 64×64 to 128-bit multiply requires a sequence of two instructions to generate a pair of 64-bit result registers:

- $+ (64 \times 64) \rightarrow \langle 63:0 \rangle$
- $(64 \times 64) \rightarrow \langle 127:64 \rangle$

Signed and unsigned 32- and 64-bit divide are also provided. A remainder instruction is not provided, but a remainder may be computed easily from the dividend, divisor and quotient using an MSUB instruction. There is no hardware check for “divide by zero”, but this check can be performed in the shadow of a long latency division. A divide by zero writes zero to the destination register.

3.7 Scalar Floating Point

AArch64 mandates hardware floating point wherever floating point arithmetic is required – there is no “soft-float” variant of the AArch64 Procedure Calling Standard (PCS).

Scalar floating point functionality is similar to AArch32 VFP, with the following changes:

- The deprecated “small vector” feature of VFP is removed.
- There are 32 S registers and 32 D registers. The S registers are not packed into D registers, but occupy the low 32 bits of the corresponding D register. For example $S_{31}=D_{31}\langle 31:0 \rangle$, not $D_{15}\langle 63:32 \rangle$.
- Load/store addressing modes identical to integer load/stores.
- Load/store of a pair of floating point registers.
- Floating point FCSEL and FCCMP equivalent to the integer CSEL and CCMP.

- Floating point `FCMP` and `FCCMP` instructions set the integer condition flags directly, and do not modify the condition flags in the FPSR.
- All floating-point multiply-add and multiply-subtract instructions are “fused”.
- Convert between 64-bit integer and floating point.
- Convert FP to integer with explicit rounding direction: towards zero, towards +Inf, towards -Inf, to nearest with ties to even, and to nearest with ties away from zero.
- Round FP to nearest integral FP with explicit rounding direction (as above).
- Direct conversion between half-precision and double-precision.
- `FMINNM` & `FMAXNM` implementing the IEEE754-2008 `minNum()` and `maxNum()` operations, returning the numerical value if one of the operands is a quiet NaN.

3.8 Advanced SIMD

See §5.8 below for a detailed description.

4 A64 ASSEMBLY LANGUAGE

4.1 Basic Structure

The letter **w** is shorthand for a 32-bit *word*, and **x** for a 64-bit *extended word*. The letter **x** (*extended*) is used rather than **D** (*double*), since **D** conflicts with its use for floating point and SIMD “double-precision” registers and the T32 load/store “double-register” instructions (e.g. `LDRD`).

An A64 assembler will recognise both upper and lower-case variants of instruction mnemonics and register names, but not mixed case. An A64 disassembler may output either upper or lower-case mnemonics and register names. The case of program and data labels **is** significant.

The fundamental statement format and operand order follows that used by AArch32 UAL assemblers and disassemblers, i.e. a single statement per source line, consisting of one or more optional program labels, followed by an instruction mnemonic, then a *destination* register and one or more *source* operands separated by commas.

```
{label:*} {opcode {dest{, source1{, source2{, source3}}}}}
```

This dest/source ordering is reversed for store instructions, in common with AArch32 UAL.

The A64 assembly language does not require the ‘#’ symbol to introduce immediate values, though an assembler must allow it. An A64 disassembler shall always output a ‘#’ before an immediate value for readability.

Where a user-defined symbol or label is identical to a pre-defined register name (e.g. “x0”) then if it is used in a context where its interpretation is ambiguous – for example in an operand position that would accept either a register name or an immediate expression – then an assembler must interpret it as the register name. A symbol may be disambiguated by using it within an expression context, i.e. by placing it within parentheses and/or prefixing it with an explicit ‘#’ symbol.

In the examples below the sequence “//” is used as a comment leader and ARMv8 assemblers are encouraged to accept this syntax, though they may also support their legacy A32 and T32 comment syntax.

4.2 Instruction Mnemonics

An A64 instruction form can be identified by the following combination of attributes:

- The operation *name* (e.g. `ADD`) which indicates the instruction semantics.
- The operand *container*, usually the register type. An instruction writes to the whole container, but if it is not the largest in its class, then the remainder of the largest container in the class is set to ZERO.
- The operand data *subtype*, where some operand(s) are a different size from the primary *container*.
- The final source operand type, which may be a register or an immediate value.

The *container* is one of:

| Integer Class | |
|------------------------------------|--|
| W | 32-bit integer |
| X | 64-bit integer |
| SIMD Scalar & Floating Point Class | |
| B | 8-bit scalar |
| H | 16-bit scalar & half-precision float |
| S | 32-bit scalar & single-precision float |
| D | 64-bit scalar & double-precision float |
| Q | 128-bit scalar |

The *subtype* is one of:

| Load-Store / Sign-Zero Extend | |
|-------------------------------|---------------------------------|
| B | byte |
| SB | signed byte |
| H | halfword |
| SH | signed halfword |
| W | word |
| SW | signed word |
| Register Width Changes | |
| H | High (dst gets top half) |
| N | Narrow (dst < src) |
| L | Long (dst > src) |
| W | Wide (dst == src1, src1 > src2) |
| <i>etc</i> | |

These attributes are combined in the assembly language notation to identify the specific instruction form. In order to retain a close look and feel to the existing ARM assembly language, the following format has been adopted:

```
<name>{<subtype>} <container>
```

In other words the operation *name* and *subtype* are described by the instruction mnemonic, and the *container* size by the operand name(s). Where *subtype* is omitted, it is inherited from *container*.

In this way an assembler programmer can write an instruction without having to remember a multitude of new mnemonics; and the reader of a disassembly listing can straightforwardly read an instruction and see at a glance the type and size of each operand.

The implication of this is that the A64 assembly language *overloads* instruction mnemonics, and distinguishes between the different forms of an instruction based on the operand register names. For example the ADD instructions below all have different opcodes, but the programmer only has to remember one mnemonic and the assembler automatically chooses the correct opcode based on the operands – with the disassembler doing the reverse.

```
ADD    W0, W1, W2           // add 32-bit register
ADD    X0, X1, X2           // add 64-bit register
ADD    X0, X1, W2, SXTW    // add 64-bit extending register
ADD    X0, X1, #42         // add 64-bit immediate
```

4.3 Condition Codes

In AArch32 assembly language conditionally executed instructions are represented by directly appending the condition to the mnemonic, without a delimiter. This leads to some ambiguity which can make assembler code difficult to parse: for example ADCS, BICS, LSLs and TEQ look at first glance like conditional instructions.

The A64 ISA has far fewer instructions which set or test condition codes. Those that do will be identified as follows:

1. Instructions which set the condition flags are notionally different instructions, and will continue to be identified by appending an 's' to the base mnemonic, e.g. ADDS.

2. Instructions which are truly conditionally executed (i.e. when the condition is false they have no effect on the architectural state, aside from advancing the program counter) have the condition appended to the instruction with a '.' delimiter. For example `B.EQ`.
3. If there is more than one instruction extension, then the conditional extension is always last.
4. Instructions which are unconditionally executed, but use the condition flags as a source operand, will specify the condition to test in their final operand position, e.g. `CSEL Wd, Wm, Wn, NE`

To aid portability an A64 assembler may also provide the old UAL conditional mnemonics, so long as they have direct equivalents in the A64 ISA. However, the UAL mnemonics will not be generated by an A64 disassembler – their use is deprecated in 64-bit assembler code, and may cause a warning or error if backward compatibility is not explicitly requested by the programmer.

The full list of condition codes is as follows:

| Encoding | Name (& alias) | Meaning (integer) | Meaning (floating point) | Flags |
|----------|-----------------|--|-----------------------------------|-----------------|
| 0000 | EQ | Equal | Equal | Z==1 |
| 0001 | NE | Not equal | Not equal, or unordered | Z==0 |
| 0010 | HS (CS) | Unsigned higher or same (Carry set) | Greater than, equal, or unordered | C==1 |
| 0011 | LO (CC) | Unsigned lower (Carry clear) | Less than | C==0 |
| 0100 | MI | Minus (negative) | Less than | N==1 |
| 0101 | PL | Plus (positive or zero) | Greater than, equal, or unordered | N==0 |
| 0110 | VS | Overflow set | Unordered | V==1 |
| 0111 | VC | Overflow clear | Ordered | V==0 |
| 1000 | HI | Unsigned higher | Greater than, or unordered | C==1 && Z==0 |
| 1001 | LS | Unsigned lower or same | Less than or equal | !(C==1 && Z==0) |
| 1010 | GE | Signed greater than or equal | Greater than or equal | N==V |
| 1011 | LT | Signed less than | Less than or unordered | N!=V |
| 1100 | GT | Signed greater than | Greater than | Z==0 && N==V |
| 1101 | LE | Signed less than or equal | Less than, equal, or unordered | !(Z==0 && N==V) |
| 1110 | AL | Always | Always | Any |
| 1111 | NV [†] | Always | Always | Any |

[†]The condition code `NV` exists only to provide a valid disassembly of the '1111b' encoding, and otherwise behaves identically to `AL`.

4.4 Register Names

4.4.1 General purpose (integer) registers

The thirty one general purpose registers in the main integer register bank are named R_0 to R_{30} , with special register number 31 having different names, depending on the context in which it is used. However, when the registers are used in a specific instruction form, they must be further qualified to indicate the operand data size (32 or 64 bits) – and hence the instruction’s data size.

The qualified names for the general purpose registers are as follows, where ‘n’ is the register number 0 to 30:

| | | |
|--------------------|-------|-------|
| Size (bits) | 32b | 64b |
| Name | W_n | X_n |

Where register number 31 represents *read zero* or *discard result* (aka the “zero register”):

| | | |
|--------------------|-----|-----|
| Size (bits) | 32b | 64b |
| Name | WZR | XZR |

Where register number 31 represents the *stack pointer*:

| | | |
|--------------------|-----|-----|
| Size (bits) | 32b | 64b |
| Name | WSP | SP |

In more detail:

- The names X_n and W_n refer to the same architectural register.
- There is no register named W_{31} or X_{31} .
- For instruction operands where register 31 is interpreted as the 64-bit *stack pointer*, it is represented by the name SP . For operands which do not interpret register 31 as the 64-bit stack pointer this name shall cause an assembler error.
- The name WSP represents register 31 as the *stack pointer* in a 32-bit context. It is provided only to allow a valid disassembly, and should not be seen in correctly behaving 64-bit code.
- For instruction operands which interpret register 31 as the *zero register*, it is represented by the name XZR in 64-bit contexts, and WZR in 32-bit contexts. In operand positions which do not interpret register 31 as the zero register these names shall cause an assembler error.
- Where a mnemonic is overloaded (i.e. can generate different instruction encodings depending on the data size), then an assembler shall determine the precise form of the instruction from the size of the *first* register operand. Usually the other operand registers should match the size of the first operand, but in some cases a register may have a different size (e.g. an address base register is always 64 bits), and a source register may be smaller than the destination if it contains a word, halfword or byte that is being widened by the instruction to 64 bits.
- The architecture does not define a special name for register 30 that reflects its special role as the link register on procedure calls. Such software names may be defined as part of the Procedure Calling Standard.

4.4.2 FP/SIMD registers

The thirty two registers in the FP/SIMD register bank named V_0 to V_{31} are used to hold floating point operands for the scalar floating point instructions, and both scalar and vector operands for the Advanced SIMD instructions. As with the general purpose integer registers, when they are used in a specific instruction form the names must be further qualified to indicate the data *shape* (i.e. the data element size and number of elements or lanes) held within them.

Note however that the data *type*, i.e. the interpretation of the bits within each register or vector element – integer (signed, unsigned or irrelevant), floating point, polynomial or cryptographic hash – is not described by the register name, but by the instruction mnemonics which operate on them. For more details see the Advanced SIMD description in §5.8.

4.4.2.1 SIMD scalar register

In Advanced SIMD and floating point instructions which operate on scalar data the FP/SIMD registers behave similarly to the main general-purpose integer registers, i.e. only the lower bits are accessed, with the unused high bits ignored on a read and set to zero on a write. The qualified names for scalar FP/SIMD names indicate the number of significant bits as follows, where ‘n’ is a register number 0 to 31:

| Size (bits) | 8b | 16b | 32b | 64b | 128b |
|-------------|----|-----|-----|-----|------|
| Name | Bn | Hn | Sn | Dn | Qn |

4.4.2.2 SIMD vector register

When a register holds multiple data elements on which arithmetic will be performed in a parallel, SIMD fashion, then a qualifier describes the vector shape: i.e. the element size, and the number of elements or “lanes”. Where “bits×lanes” does not equal 128, the upper 64 bits of the register are ignored when read and set to zero on a write.

The fully qualified SIMD vector register names are as follows, where ‘n’ is the register number 0 to 31:

| Shape (bits×lanes) | 8b×8 | 8b×16 | 16b×4 | 16b×8 | 32b×2 | 32b×4 | 64b×1 | 64b×2 |
|--------------------|-------|--------|-------|-------|-------|-------|-------|-------|
| Name | Vn.8B | Vn.16B | Vn.4H | Vn.8H | Vn.2S | Vn.4S | Vn.1D | Vn.2D |

4.4.2.3 SIMD vector element

Where a single element from a SIMD vector register is used as a scalar operand, this is indicated by appending a constant, zero-based “element index” to the vector register name, inside square brackets. The number of lanes is not represented, since it is not encoded, and may only be inferred from the index value.

| Size (bits) | 8b | 16b | 32b | 64b |
|-------------|---------|---------|---------|---------|
| Name | Vn.B[i] | Vn.H[i] | Vn.S[i] | Vn.D[i] |

However an assembler shall accept a fully qualified SIMD vector register name as in §4.4.2.2, so long as the number of lanes is greater than the index value. For example the following forms will both be accepted by an assembler as the name for the 32-bit element in bits <63:32> of SIMD register 9:

| | |
|----------|---------------------------------|
| V9.S[1] | <i>standard disassembly</i> |
| V9.2S[1] | <i>optional number of lanes</i> |
| V9.4S[1] | <i>optional number of lanes</i> |

Note that the vector register element name $V_{n.S}[0]$ is not equivalent to the scalar register name S_n . Although they represent the same bits in the register, they select different instruction encoding forms, i.e. vector element vs scalar form.

4.4.2.4 SIMD vector register list

Where an instruction operates on a “list” of vector registers – for example vector load-store and table lookup – the registers are specified as a list within curly braces. This list consists of either a sequence of registers separated by commas, or a register range separated by a hyphen. The registers must be numbered in increasing order (modulo 32), in increments of one or two. The hyphenated form is preferred for disassembly if there are more than two registers in the list, and the register numbers are monotonically increasing in increments of one. The following are equivalent representations of a set of four registers V_4 to V_7 , each holding four lanes of 32-bit elements:

| | |
|----------------------------------|-----------------------------------|
| $\{V4.4S - V7.4S\}$ | <i>standard disassembly</i> |
| $\{V4.4S, V5.4S, V6.4S, V7.4S\}$ | <i>alternative representation</i> |

4.4.2.5 SIMD vector element list

It is also possible for registers in a list to have a vector element form, for example $LD4$ loading one element into each of four registers, in which case the index is appended to the list, as follows:

| | |
|-------------------------------------|--|
| $\{V4.S - V7.S\}[3]$ | <i>standard disassembly</i> |
| $\{V4.4S, V5.4S, V6.4S, V7.4S\}[3]$ | <i>alternative with optional number of lanes</i> |

4.5 Load/Store Addressing Modes

Load/store addressing modes in the A64 instruction set broadly follow T32, using a 64-bit *base* address from a general register X_n ($n=0-30$) or the current stack pointer SP , with an immediate or register *offset*. The complete set of addressing modes is as follows. Some types of load or store instruction may support only a subset of these, and the supported modes are listed in the detailed instruction descriptions below.

| Addressing Form | Offset | | |
|---------------------------|---------------|------------------------|---------------------------|
| | immediate | register | extended register |
| Base register (no offset) | [base{,#0}] | - | - |
| Base plus offset | [base{,#imm}] | [base,Xm{,LSL #imm}] | [base,Wm,(S U)XTW {#imm}] |
| Pre-indexed | [base,#imm]! | - | - |
| Post-indexed | [base],#imm | [base],Xm [‡] | - |
| Literal (pc-relative) | label | - | - |

- *Base plus offset* addressing means that the address is the value in the 64-bit register *base* plus an *offset*.
- *Pre-indexed* addressing means that the address is the value in the 64-bit register *base* plus *offset*, then the address is written back to *base*.
- *Post-indexed* addressing means that the address is the value in the 64-bit register *base*, then address plus *offset* is written back to *base*.
- *Literal* addressing means that the address is the value in the 64-bit program counter PC plus a 19-bit signed word offset, i.e. a word-aligned address within $\pm 1\text{MiB}$ of PC . Only available for loads of 32 bits or larger and prefetch instructions: PC is not usable in other addressing modes. The syntax for *label* is described in section 5 below.
- An *immediate offset* may be unsigned or signed (two's complement), and unscaled or scaled, depending on the type of load/store instruction. When scaled it is encoded as a multiple of the transfer size, but the assembly language always uses a **byte** offset with the assembler/disassembler converting as necessary. The usable byte offsets therefore depend on the type of load/store instruction and the transfer size.

| Bits | Sign | Scaling | Write-back? | Load/Store Type |
|------|----------|----------|-------------|-------------------------------|
| 0 | - | - | - | exclusive / acquire / release |
| 7 | signed | scaled | option | register pair |
| 9 | signed | unscaled | option | single register |
| 12 | unsigned | scaled | no | single register |

- A *register offset* means that *offset* is the value in 64-bit general register X_m , optionally scaled by the transfer size (in bytes) if so indicated by “,LSL #imm”, where $\text{imm}=\log_2(\text{size})$.
- An *extended register offset* means that *offset* is the value in 32-bit general register W_m , sign or zero extended to 64 bits, then scaled by the transfer size if so indicated by “#imm”, where $\text{imm}=\log_2(\text{size})$. An assembler must accept W_m or X_m as an *extended register offset*, but W_m is preferred for disassembly.
- The *pre/post-indexed by register offset* modes are not generally available, except that post-indexed mode[‡] may be used with the Advanced SIMD load/store structure instructions in section 5.8.22.
- There is no subtract or “down” option, so generating an address lower than the value in the *base* register requires a negative signed *immediate offset* or a *register offset* holding a negative value.
- When *base* is SP the current stack pointer must initially be quadword (16 byte) aligned – with misalignment causing a stack alignment fault. The offset does not have to be a multiple of 16 bytes unless so required by the specific load/store instruction. SP may never be used as a *register offset*.

4.5.1 Address Computation

Apart from pre/post-indexed forms, any addressing mode may be computed and written to a general register or (in most cases) to the current stack pointer using general-purpose arithmetic instructions, as follows:

| Addressing Form | Offset | | |
|---------------------------|--|-------------------------------------|---|
| | immediate | register | extended register |
| Base register (no offset) | ADD Xd SP, base, #0 | - | - |
| Base plus offset | ADD Xd SP, base, #imm or SUB Xd SP, base, #imm | ADD Xd SP, base, Xm {, LSL #imm} | ADD Xd SP, base, Wm, (S U)XT(W H B) {#imm} |
| Pre-indexed | n/a | - | - |
| Post-indexed | n/a | n/a | - |
| Literal (pc-relative) | ADR Xd, label | - | - |

Notes:

- To calculate a *base plus immediate offset* the ADD (immediate) instructions defined in §5.4.1 accept an unsigned 12-bit immediate, with optional left shift by 12. This means that a single ADD instruction cannot support the full range of byte offsets available to a single register load/store with scaled 12-bit immediate offset. For example a quadword LDR effectively has a 16-bit byte offset. To calculate an address where the byte offset requires more than 12 bits it will be necessary to use two ADD instructions, for example:

```
ADD    Xd, base, #(imm & 0xfff)
ADD    Xd, Xd, #(imm >> 12), LSL #12
```

- To calculate a *base plus extended register offset* the ADD (extending register) instructions defined in §5.5.2 provide a superset of the load/store addressing mode, since they also support sign or zero-extension of a byte or halfword value, with any shift amount between 0 and 4, for example:

```
ADD    Xd, base, Wm, SXTW #3    // Xd = base+(SignExtend(Wm) LSL 3)
ADD    Xd, base, Wm, UXTH #4    // Xd = base+(ZeroExtend(Wm<15:0>) LSL 4)
```

- If the same *extended register* offset is used by more than one load/store instruction then it may – depending on the processor implementation – be more efficient to calculate the zero/sign-extended and scaled intermediate result just once and then reuse it as a simple *register* offset. The “extend-and-scale” calculation may be performed using the SBFIZ and UBFIZ bitfield instructions defined in §5.4.5, for example:

```
SBFIZ  Xd, Xm, #3, #32          // Xd = "Wm, SXTW #3"
UBFIZ  Xd, Xm, #4, #16          // Xd = "Wm, UXTH #4"
```

5 A64 INSTRUCTION SET

5.1 Common Terms

The following syntax terms are used frequently throughout the A64 instruction set description. See also the syntax notation described in section 2 above.

| | |
|---------------------------|---|
| <code>Xn</code> | Unless otherwise indicated a general register operand <code>Xn</code> or <code>Wn</code> interprets register 31 as the <i>zero register</i> , represented by the names <code>XZR</code> or <code>WZR</code> respectively. |
| <code>Xn SP</code> | A general register operand of the form <code>Xn SP</code> or <code>Wn WSP</code> interprets register 31 as the <i>stack pointer</i> , represented by the names <code>SP</code> or <code>WSP</code> respectively. |
| <code>cond</code> | A standard ARM condition <code>EQ</code> , <code>NE</code> , <code>CS HS</code> , <code>CC LO</code> , <code>MI</code> , <code>PL</code> , <code>VS</code> , <code>VC</code> , <code>HI</code> , <code>LS</code> , <code>GE</code> , <code>LT</code> , <code>GT</code> , <code>LE</code> , <code>AL</code> or <code>NV</code> with the same meanings as in AArch32. Note that although <code>AL</code> and <code>NV</code> represent different encodings, as in AArch32 they are both interpreted as the “always true” condition. Unless stated AArch64 instructions do not set or use the condition flags, but those that do set all of the condition flags. If used in a pseudo-code expression this symbol represents a Boolean whose value is the truth of the specified condition test. |
| <code>invert(cond)</code> | The inverse of <code>cond</code> , for example the inverse of <code>GT</code> is <code>LE</code> . |
| <code>uimmn</code> | An n -bit unsigned (positive) immediate value. |
| <code>simmn</code> | An n -bit two's complement signed immediate value (where n includes the sign bit). |
| <code>label</code> | Represents a pc-relative reference from an instruction to a target code or data location. The precise syntax is likely to be specific to individual toolchains, but the preferred form is “ <i>pcsym</i> ” or “ <i>pcsym±delta</i> ”, where <i>pcsym</i> is: <ol style="list-style-type: none"> The preferred architectural notation which is (at the choice of the disassembler) the character ‘.’ or string “{<code>pc</code>}” representing the referencing instruction’s absolute address or its offset within a relocatable image. For a programmers’ view where the instruction’s address in memory or offset is known and a list of symbols is available, then the symbol name whose value is nearest to, and preferably less than or equal to the target location’s address or offset. For a programmers’ view where the instruction’s address or section offset is known but a list of symbols is not available, then the target address or section offset as a hexadecimal constant. And where in all cases “ <i>±delta</i> ” gives the byte offset from <i>pcsym</i> to the target location’s address or offset, which may be omitted if the offset is zero. As a convenience assemblers may permit the notation “= <i>value</i> ” in conjunction with pc-relative literal load instructions to place a large immediate value or symbolic address in a literal pool and generate a hidden label reference to that value. Such notation is non-architectural and is unlikely to appear in a disassembly listing. Furthermore A64 has instructions to construct immediate values (section 5.4.3) and addresses (section 5.4.4) in a register which may be preferable to loading from a literal pool. |
| <code>addr</code> | Represents an addressing mode that is some subset (documented for each class of instruction) of the addressing modes defined in section 4.5 above. |
| <code>lshift</code> | Represents an optional shift operator performed on the final source operand of a logical instruction, taking chosen from <code>LSL</code> , <code>LSR</code> , <code>ASR</code> , or <code>ROR</code> , followed by a constant shift amount <code>#imm</code> in the range 0 to <i>regwidth</i> -1. If omitted the default is “ <code>LSL #0</code> ”. |
| <code>ashift</code> | Represents an optional shift operator to be performed on the final source operand of an arithmetic instruction chosen from <code>LSL</code> , <code>LSR</code> , or <code>ASR</code> , followed by a constant shift amount <code>#imm</code> in the range 0 to <i>regwidth</i> -1. If omitted the default is “ <code>LSL #0</code> ”. |

5.2 Control Flow

5.2.1 Conditional Branch

Unless stated, conditional branches have a branch offset range of $\pm 1\text{MiB}$ from the program counter.

`B cond label`

Branch: conditionally jumps to program-relative label if cond is true.

`CBNZ Wn, label`

Compare and Branch Not Zero: conditionally jumps to program-relative label if Wn is not equal to zero.

`CBNZ Xn, label`

Compare and Branch Not Zero (extended): conditionally jumps to label if Xn is not equal to zero.

`CBZ Wn, label`

Compare and Branch Zero: conditionally jumps to label if Wn is equal to zero.

`CBZ Xn, label`

Compare and Branch Zero (extended): conditionally jumps to label if Xn is equal to zero.

`TBNZ Xn|Wn, #uimm6, label`

Test and Branch Not Zero: conditionally jumps to label if bit number uimm6 in register Xn is not zero. The bit number implies the width of the register, which may be written and should be disassembled as Wn if uimm6 is less than 32. Limited to a branch offset range of $\pm 32\text{KiB}$.

`TBZ Xn|Wn, #uimm6, label`

Test and Branch Zero: conditionally jumps to label if bit number uimm6 in register Xn is zero. The bit number implies the width of the register, which may be written and should be disassembled as Wn if uimm6 is less than 32. Limited to a branch offset range of $\pm 32\text{KiB}$.

5.2.2 Unconditional Branch (immediate)

Unconditional branches support an immediate branch offset range of $\pm 128\text{MiB}$.

`B label`

Branch: unconditionally jumps to pc-relative label.

`BL label`

Branch and Link: unconditionally jumps to pc-relative label, writing the address of the next sequential instruction to register X30.

5.2.3 Unconditional Branch (register)

`BLR Xm`

Branch and Link Register: unconditionally jumps to address in Xm, writing the address of the next sequential instruction to register X30.

`BR Xm`

Branch Register: jumps to address in Xm, with a hint to the CPU that this is not a subroutine return.

`RET {Xm}`

Return: jumps to register Xm, with a hint to the CPU that this is a subroutine return. An assembler shall default to register X30 if Xm is omitted.

5.3 Memory Access

Aside from exclusive and explicitly ordered loads and stores, addresses may have arbitrary alignment unless strict alignment checking is enabled (`SCTLR.A==1`). However if SP is used as the base register then the value of the stack pointer prior to adding any offset must be quadword (16 byte) aligned, or else a stack alignment exception will be generated.

A memory read or write generated by the load or store of a single general-purpose register aligned to the size of the transfer is atomic. Memory reads or writes generated by the non-exclusive load or store of a pair of general-purpose registers aligned to the size of the register are treated as two atomic accesses, one for each register. In all other cases, unless otherwise stated, there are no atomicity guarantees.

5.3.1 Load-Store Single Register

Addressing modes supported by `addr` (referring to §4.5):

- Base plus immediate offset (scaled 12-bit unsigned, unscaled 9-bit signed);
- Base plus 64-bit register offset (optionally scaled);
- Base plus 32-bit extended register offset (optionally scaled);
- Pre-indexed by immediate offset (unscaled 9-bit signed);
- Post-indexed by immediate offset (unscaled 9-bit signed);
- Literal (pc-relative), for loads of 32-bits or larger.

If a Load instruction specifies writeback and the register being loaded is also the base register, then one of the following behaviours can occur:

- The instruction is UNALLOCATED
- The instruction is treated as a NOP
- The instruction performs the load using the specified addressing mode and the base register becomes UNKNOWN. In addition, if an exception occurs during such an instruction, the base address might be corrupted such that the instruction cannot be repeated.

If a Store instruction performs a writeback and the register being stored is also the base register, then one of the following behaviours can occur:

- The instruction is UNALLOCATED
- The instruction is treated as a NOP
- The instruction performs the stores of the register specified using the specified addressing mode but the value stored is UNKNOWN

`LDR Wt, addr`

Load Register: loads a word from memory addressed by `addr` to `Wt`.

`LDR Xt, addr`

Load Register (extended): loads a doubleword from memory addressed by `addr` to `Xt`.

`LDRB Wt, addr`

Load Byte: loads a byte from memory addressed by `addr`, then zero-extends it to `Wt`.

`LDRSB Wt, addr`

Load Signed Byte: loads a byte from memory addressed by `addr`, then sign-extends it into `Wt`.

`LDRSB Xt, addr`

Load Signed Byte (extended): loads a byte from memory addressed by `addr`, then sign-extends it into `Xt`.

`LDRH Wt, addr`

Load Halfword: loads a halfword from memory addressed by `addr`, then zero-extends it into `Wt`.

LDRSH *Wt*, *addr*

Load Signed Halfword: loads a halfword from memory addressed by *addr*, then sign-extends it into *Wt*.

LDRSH *Xt*, *addr*

Load Signed Halfword (extended): loads a halfword from memory addressed by *addr*, then sign-extends it into *Xt*.

LDRSW *Xt*, *addr*

Load Signed Word (extended): loads a word from memory addressed by *addr*, then sign-extends it into *Xt*.

STR *Wt*, *addr*

Store Register: stores word from *Wt* to memory addressed by *addr*.

STR *Xt*, *addr*

Store Register (extended): stores doubleword from *Xt* to memory addressed by *addr*.

STRB *Wt*, *addr*

Store Byte: stores byte from *Wt* to memory addressed by *addr*.

STRH *Wt*, *addr*

Store Halfword: stores halfword from *Wt* to memory addressed by *addr*.

5.3.2 Load-Store Single Register (unscaled offset)

Addressing modes supported (referring to §4.5):

- Base plus immediate offset (unscaled 9-bit signed).

These mnemonics distinguish instructions which use this form of offset when the byte offset value could also be represented by instructions which use the scaled 12-bit unsigned immediate offset form, i.e. when its value is positive and naturally aligned to the transfer size.

A programmer-friendly assembler should also generate these instructions in response to the standard LDR/STR mnemonics when the immediate offset is unambiguous, i.e. negative or unaligned. A disassembler could also display these instructions using the standard LDR/STR mnemonics when the encoded immediate is unambiguous, however that is not required by the architectural assembly language.

LDUR *Wt*, [*base*,#*simm9*]

Load (Unscaled) Register: loads a word from memory addressed by *base+simm9* to *Wt*.

LDUR *Xt*, [*base*,#*simm9*]

Load (Unscaled) Register (extended): loads a doubleword from memory addressed by *base+simm9* to *Xt*.

LDURB *Wt*, [*base*,#*simm9*]

Load (Unscaled) Byte: loads a byte from memory addressed by *base+simm9*, then zero-extends it into *Wt*.

LDURSB *Wt*, [*base*,#*simm9*]

Load (Unscaled) Signed Byte: loads a byte from memory addressed by *base+simm9*, then sign-extends it into *Wt*.

LDURSB *Xt*, [*base*,#*simm9*]

Load (Unscaled) Signed Byte (extended): loads a byte from memory addressed by *base+simm9*, then sign-extends it into *Xt*.

LDURH Wt , [$base, \#simm9$]

Load (Unscaled) Halfword: loads a halfword from memory addressed by $base+simm9$, then zero-extends it into Wt .

LDURSH Wt , [$base, \#simm9$]

Load (Unscaled) Signed Halfword: loads a halfword from memory addressed by $base+simm9$, then sign-extends it into Wt .

LDURSH Xt , [$base, \#simm9$]

Load (Unscaled) Signed Halfword (extended): loads a halfword from memory addressed by $base+simm9$, then sign-extends it into Xt .

LDURSW Xt , [$base, \#simm9$]

Load (Unscaled) Signed Word (extended): loads a word from memory addressed by $base+simm9$, then sign-extends it into Xt .

STUR Wt , [$base, \#simm9$]

Store (Unscaled) Register: stores word from Wt to memory addressed by $base+simm9$.

STUR Xt , [$base, \#simm9$]

Store (Unscaled) Register (extended): stores doubleword from Xt to memory addressed by $base+simm9$.

STURB Wt , [$base, \#simm9$]

Store (Unscaled) Byte: stores byte from Wt to memory addressed by $base+simm9$.

STURH Wt , [$base, \#simm9$]

Store (Unscaled) Halfword: stores halfword from Wt to memory addressed by $base+simm9$.

5.3.3 Load-Store Pair

Addressing modes supported by `addr` (referring to §4.5):

- Base plus immediate offset (scaled 7-bit signed);
- Pre-indexed by immediate offset (scaled 7-bit signed);
- Post-indexed by immediate offset (scaled 7-bit signed).

If a Load Pair instruction specifies the same register for the two registers that are being loaded, then one of the following behaviours can occur:

- The instruction is UNALLOCATED
- The instruction is treated as a NOP
- The instruction performs all of the loads using the specified addressing mode and the register being loaded takes an UNKNOWN value

If a Load Pair instruction specifies writeback and one of the registers being loaded is also the base register, then one of the following behaviours can occur:

- The instruction is UNALLOCATED
- The instruction is treated as a NOP
- The instruction performs all of the loads using the specified addressing mode and the base register becomes UNKNOWN. In addition, if an exception occurs during such an instruction, the base address might be corrupted such that the instruction cannot be repeated.

If a Store Pair instruction performs a writeback and one of the registers being stored is also the base register, then one of the following behaviours can occur:

- The instruction is UNALLOCATED
- The instruction is treated as a NOP

- The instruction performs all of the stores of the registers specified using the specified addressing mode but the value stored for the base register is UNKNOWN

LDP *Wt1*, *Wt2*, *addr*

Load Pair Registers: loads two words from memory addressed by *addr* to *Wt1* and *Wt2*.

LDP *Xt1*, *Xt2*, *addr*

Load Pair Registers (extended): loads two doublewords from memory addressed by *addr* to *Xt1* and *Xt2*.

LDPSW *Xt1*, *Xt2*, *addr*

Load Pair Signed Words (extended) loads two words from memory addressed by *addr*, then sign-extends them into *Xt1* and *Xt2*.

STP *Wt1*, *Wt2*, *addr*

Store Pair Registers: stores two words from *Wt1* and *Wt2* to memory addressed by *addr*.

STP *Xt1*, *Xt2*, *addr*

Store Pair Registers (extended): stores two doublewords from *Xt1* and *Xt2* to memory addressed by *addr*.

5.3.4 Load-Store Non-temporal Pair

Addressing modes supported (referring to §4.5):

- Base plus immediate offset (scaled 7-bit signed);

The load-store non-temporal pair instructions provide a hint to the memory system that an access is “non-temporal” or “streaming” and unlikely to be accessed again in the near future so need not be retained in data caches. However depending on the memory type they may permit memory reads to be preloaded and memory writes to be gathered, in order to accelerate bulk memory transfers.

Furthermore, as a special exception to the normal memory ordering rules, where an address dependency exists between two memory reads and the second read was generated by a Load Non-temporal Pair instruction then, in the absence of any other barrier mechanism to achieve order, those memory accesses can be observed in any order by other observers within the shareability domain of the memory addresses being accessed.

If a Load Non-temporal Pair instruction specifies the same register for the two registers that are being loaded, then one of the following behaviours can occur:

- The instruction is UNALLOCATED
- The instruction is treated as a NOP
- The instruction performs all of the loads using the specified addressing mode and the register being loaded takes an UNKNOWN value

LDNP *Wt1*, *Wt2*, [*base*,#*imm*]

Load Non-temporal Pair: loads two words from memory addressed by *base+imm* to *Wt1* and *Wt2*, with a non-temporal hint.

LDNP *Xt1*, *Xt2*, [*base*,#*imm*]

Load Non-temporal Pair (extended): loads two doublewords from memory addressed by *base+imm* to *Xt1* and *Xt2*, with a non-temporal hint.

STNP *Wt1*, *Wt2*, [*base*,#*imm*]

Store Non-temporal Pair: stores two words from *Wt1* and *Wt2* to memory addressed by *base+imm*, with a non-temporal hint.

STNP Xt1, Xt2, [base,#imm]

Store Non-temporal Pair (extended): stores two doublewords from Xt1 and Xt2 to memory addressed by base+imm, with a non-temporal hint.

5.3.5 Load-Store Unprivileged

Addressing modes supported (referring to §4.5):

- Base plus immediate offset (unscaled 9-bit signed).

The load-store unprivileged instructions may be used when the processor is at the EL1 exception level to perform a memory access as if it were at the EL0 (unprivileged) exception level. If the processor is at any other exception level, then a normal memory access for that level is performed. (The letter 'T' in these mnemonics is based on an historical ARM convention which described an access to an unprivileged virtual address as being "translated").

LDTR Wt, [base,#simm9]

Load Unprivileged Register: loads word from memory addressed by base+simm9 to Wt, using EL0 privileges when at EL1.

LDTR Xt, [base,#simm9]

Load Unprivileged Register (extended): loads doubleword from memory addressed by base+simm9 to Xt, using EL0 privileges when at EL1.

LDTRB Wt, [base,#simm9]

Load Unprivileged Byte: loads a byte from memory addressed by base+simm9, then zero-extends it into Wt, using EL0 privileges when at EL1.

LDTRSB Wt, [base,#simm9]

Load Unprivileged Signed Byte: loads a byte from memory addressed by base+simm9, then sign-extends it into Wt, using EL0 privileges when at EL1.

LDTRSB Xt, [base,#simm9]

Load Unprivileged Signed Byte (extended): loads a byte from memory addressed by base+simm9, then sign-extends it into Xt, using EL0 privileges when at EL1.

LDTRH Wt, [base,#simm9]

Load Unprivileged Halfword: loads a halfword from memory addressed by base+simm9, then zero-extends it into Wt, using EL0 privileges when at EL1.

LDTRSH Wt, [base,#simm9]

Load Unprivileged Signed Halfword: loads a halfword from memory addressed by base+simm9, then sign-extends it into Wt, using EL0 privileges when at EL1.

LDTRSH Xt, [base,#simm9]

Load Unprivileged Signed Halfword (extended): loads a halfword from memory addressed by base+simm9, then sign-extends it into Xt, using EL0 privileges when at EL1.

LDTRSW Xt, [base,#simm9]

Load Unprivileged Signed Word (extended): loads a word from memory addressed by base+simm9, then sign-extends it into Xt, using EL0 privileges when at EL1.

STTR Wt, [base,#simm9]

Store Unprivileged Register: stores a word from Wt to memory addressed by base+simm9, using EL0 privileges when at EL1.

STTR Xt, [base,#simm9]

Store Unprivileged Register (extended): stores a doubleword from Xt to memory addressed by base+simm9, using EL0 privileges when at EL1.

STTRB Wt , $[base, \#simm9]$

Store Unprivileged Byte: stores a byte from Wt to memory addressed by $base+simm9$, using EL0 privileges when at EL1.

STTRH Wt , $[base, \#simm9]$

Store Unprivileged Halfword: stores a halfword from Wt to memory addressed by $base+simm9$, using EL0 privileges when at EL1.

5.3.6 Load-Store Exclusive

Addressing modes supported (referring to §4.5):

- Base register (no offset).

The load exclusive instructions mark the accessed physical address being accessed as an exclusive access, which is checked by the store exclusive, permitting the construction of “atomic” read-modify-write operations on shared memory variables, semaphores, mutexes, spinlocks, etc.

Natural alignment is required: an unaligned address will cause an alignment fault. A memory access generated by a load exclusive pair or store exclusive pair must be aligned to the size of the pair, and when a store exclusive pair succeeds it will cause a single-copy atomic update of the entire memory location.

LDXR Wt , $[base\{, \#0\}]$

Load Exclusive Register: loads a word from memory addressed by $base$ to Wt . Records the physical address as an exclusive access.

LDXR Xt , $[base\{, \#0\}]$

Load Exclusive Register (extended): loads a doubleword from memory addressed by $base$ to Xt . Records the physical address as an exclusive access.

LDXRB Wt , $[base\{, \#0\}]$

Load Exclusive Byte: loads a byte from memory addressed by $base$, then zero-extends it into Wt . Records the physical address as an exclusive access.

LDXRH Wt , $[base\{, \#0\}]$

Load Exclusive Halfword: loads a halfword from memory addressed by $base$, then zero-extends it into Wt . Records the physical address as an exclusive access.

LDXP $Wt1$, $Wt2$, $[base\{, \#0\}]$

Load Exclusive Pair Registers: loads two words from memory addressed by $base$, and to $Wt1$ and $Wt2$. Records the physical address as an exclusive access.

LDXP $Xt1$, $Xt2$, $[base\{, \#0\}]$

Load Exclusive Pair Registers (extended): loads two doublewords from memory addressed by $base$ to $Xt1$ and $Xt2$. Records the physical address as an exclusive access.

STXR Ws , Wt , $[base\{, \#0\}]$

Store Exclusive Register: stores word from Wt to memory addressed by $base$, and sets Ws to the returned exclusive access status.

STXR Ws , Xt , $[base\{, \#0\}]$

Store Exclusive Register (extended): stores doubleword from Xt to memory addressed by $base$, and sets Ws to the returned exclusive access status.

STXRB Ws , Wt , $[base\{, \#0\}]$

Store Exclusive Byte: stores byte from Wt to memory addressed by $base$, and sets Ws to the returned exclusive access status.

STXRH *Ws*, *Wt*, [*base*{, #0}]

Store Exclusive Halfword: stores halfword from *Xt* to memory addressed by *base*, and sets *Ws* to the returned exclusive access status.

STXP *Ws*, *Wt1*, *Wt2*, [*base*{, #0}]

Store Exclusive Pair: stores two words from *Wt1* and *Wt2* to memory addressed by *base*, and sets *Ws* to the returned exclusive access status.

STXP *Ws*, *Xt1*, *Xt2*, [*base*{, #0}]

Store Exclusive Pair (extended): stores two doublewords from *Xt1* and *Xt2* to memory addressed by *base*, and sets *Ws* to the returned exclusive access status.

5.3.7 Load-Acquire / Store-Release

Addressing modes supported (referring to §4.5):

- Base register (no offset).

A load-acquire is a load where it is guaranteed that all loads and stores appearing in program order after the load-acquire will be observed by each observer after that observer observes the load-acquire, but says nothing about loads and stores appearing before the load-acquire.

A store-release will be observed by each observer after that observer observes any loads or stores that appear in program order before the store-release, but says nothing about loads and stores appearing after the store-release.

In addition, a store-release followed by a load-acquire will be observed by each observer in program order.

A further consideration is that all store-release operations must be multi-copy atomic: that is, if one agent has seen a store-release, then all agents have seen the store-release. There are no requirements for ordinary stores to be multi-copy atomic.

Natural alignment is required: an unaligned address will cause an alignment fault.

5.3.7.1 Non-exclusive

LDAR *Wt*, [*base*{, #0}]

Load-Acquire Register: loads a word from memory addressed by *base* to *Wt*.

LDAR *Xt*, [*base*{, #0}]

Load-Acquire Register (extended): loads a doubleword from memory addressed by *base* to *Xt*.

LDARB *Wt*, [*base*{, #0}]

Load-Acquire Byte: loads a byte from memory addressed by *base*, then zero-extends it into *Wt*.

LDARH *Wt*, [*base*{, #0}]

Load-Acquire Halfword: loads a halfword from memory addressed by *base*, then zero-extends it into *Wt*.

STLR *Wt*, [*base*{, #0}]

Store-Release Register: stores a word from *Wt* to memory addressed by *base*.

STLR *Xt*, [*base*{, #0}]

Store-Release Register (extended): stores a doubleword from *Xt* to memory addressed by *base*.

STLRB *Wt*, [*base*{, #0}]

Store-Release Byte: stores a byte from *Wt* to memory addressed by *base*.

STLRH *Wt*, [*base*{, #0}]

Store-Release Halfword: stores a halfword from *Wt* to memory addressed by *base*.

5.3.7.2 Exclusive

LDAXR *Wt*, [*base*{, #0}]

Load-Acquire Exclusive Register: loads word from memory addressed by *base* to *Wt*. Records the physical address as an exclusive access.

LDAXR *Xt*, [*base*{, #0}]

Load-Acquire Exclusive Register (extended): loads doubleword from memory addressed by *base* to *Xt*. Records the physical address as an exclusive access.

LDAXRB *Wt*, [*base*{, #0}]

Load-Acquire Exclusive Byte: loads byte from memory addressed by *base*, then zero-extends it into *Wt*. Records the physical address as an exclusive access.

LDAXRH *Wt*, [*base*{, #0}]

Load-Acquire Exclusive Halfword: loads halfword from memory addressed by *base*, then zero-extends it into *Wt*. Records the physical address as an exclusive access.

LDAXP *Wt1*, *Wt2*, [*base*{, #0}]

Load-Acquire Exclusive Pair Registers: loads two words from memory addressed by *base* to *Wt1* and *Wt2*. Records the physical address as an exclusive access.

LDAXP *Xt1*, *Xt2*, [*base*{, #0}]

Load-Acquire Exclusive Pair Registers (extended): loads two doublewords from memory addressed by *base* to *Xt1* and *Xt2*. Records the physical address as an exclusive access.

STLXR *Ws*, *Wt*, [*base*{, #0}]

Store-Release Exclusive Register: stores word from *Wt* to memory addressed by *base*, and sets *Ws* to the returned exclusive access status.

STLXR *Ws*, *Xt*, [*base*{, #0}]

Store-Release Exclusive Register (extended): stores doubleword from *Xt* to memory addressed by *base*, and sets *Ws* to the returned exclusive access status.

STLXRB *Ws*, *Wt*, [*base*{, #0}]

Store-Release Exclusive Byte: stores byte from *Wt* to memory addressed by *base*, and sets *Ws* to the returned exclusive access status.

STLXRH *Ws*, *Xt*|*Wt*, [*base*{, #0}]

Store-Release Exclusive Halfword: stores the halfword from *Wt* to memory addressed by *base*, and sets *Ws* to the returned exclusive access status.

STLXP *Ws*, *Wt1*, *Wt2*, [*base*{, #0}]

Store-Release Exclusive Pair: stores two words from *Wt1* and *Wt2* to memory addressed by *base*, and sets *Ws* to the returned exclusive access status.

STLXP *Ws*, *Xt1*, *Xt2*, [*base*{, #0}]

Store-Release Exclusive Pair (extended): stores two doublewords from *Xt1* and *Xt2* to memory addressed by *base*, and sets *Ws* to the returned exclusive access status.

5.3.8 Prefetch Memory

Addressing modes supported by *addr* (referring to §4.5):

- Base plus immediate offset (scaled 12-bit unsigned, unscaled 9-bit signed);
- Base plus 64-bit register offset (optionally scaled by 8, i.e. `LSL #3`);
- Base plus 32-bit extended register offset (optionally scaled by 8);
- Literal (pc-relative).

The prefetch memory instructions signal the memory system that memory accesses from a specified address are likely in the near future. The memory system can respond by taking actions that are expected to speed up the memory accesses when they do occur, such as pre-loading the specified address into one or more caches. Since these are only hints, it is valid for the CPU to treat any or all prefetch instructions as a no-op.

PRFM <prfop>, addr

Prefetch Memory, using the <prfop> hint, where <prfop> is one of:

PLDL1KEEP, PLDL1STRM, PLDL2KEEP, PLDL2STRM, PLDL3KEEP, PLDL3STRM
 PSTL1KEEP, PSTL1STRM, PSTL2KEEP, PSTL2STRM, PSTL3KEEP, PSTL3STRM

<prfop> ::= <type><target><policy> | #uimm5
 <type> ::= "PLD" (prefetch for load) | "PST" (prefetch for store)
 <target> ::= "L1" (L1 cache) | "L2" (L2 cache) | "L3" (L3 cache)
 <policy> ::= "KEEP" (retained or temporal prefetch, i.e. allocate in cache normally)
 | "STRM" (streaming or non-temporal prefetch, i.e. memory used only once)
 #uimm5 ::= represents the unallocated hint encodings as a 5-bit immediate

PRFUM <prfop>, [base, #simm9]

Prefetch Memory (unscaled offset), explicitly uses the unscaled 9-bit signed immediate offset addressing mode, as described in section 5.3.2

5.4 Data Processing (immediate)

The following instruction groups are supported:

- Arithmetic (immediate)
- Logical (immediate)
- Move (immediate)
- Bitfield (operations)
- Shift (immediate)
- Sign/zero extend

5.4.1 Arithmetic (immediate)

These instructions accept an *arithmetic immediate* shown as `aimm`, which is encoded as a 12-bit unsigned immediate shifted left by 0 or 12 bits. In the assembly language this may be written as:

#uimm12, LSL #sh

A 12-bit unsigned immediate, explicitly shifted left by 0 or 12.

#uimm24

A 24-bit unsigned immediate. An assembler shall determine the appropriate value of `uimm12` with lowest possible shift of 0 or 12 which generates the requested value; if the value contains non-zero bits in bits<23:12> and in bits<11:0> then an error shall result.

#nimm25

A "programmer-friendly" assembler may accept a negative immediate between $-(2^{24}-1)$ and -1 inclusive, causing it to convert a requested ADD operation to a SUB, or *vice versa*, and then encode the absolute value of the immediate as for `uimm24`. However this behaviour is not required by the architectural assembly language.

A disassembler should normally output the arithmetic immediate using the `uimm24` form, unless the encoded shift amount is not the lowest possible shift that could have been used (for example `#0, LSL #12` could not be output using the `uimm24` form).

The arithmetic instructions which do not set condition flags may read and/or write the current stack pointer, for example to adjust the stack pointer in a function prologue or epilogue; the flag setting instructions can read the stack pointer, but not write it.

`ADD Wd|WSP, Wn|WSP, #aimm`

Add (immediate): $Wd|WSP = Wn|WSP + aimm$.

`ADD Xd|SP, Xn|SP, #aimm`

Add (extended immediate): $Xd|SP = Xn|SP + aimm$.

`ADDS Wd, Wn|WSP, #aimm`

Add and set flags (immediate): $Wd = Wn|WSP + aimm$, setting the condition flags.

`ADDS Xd, Xn|SP, #aimm`

Add and set flags (extended immediate): $Xd = Xn|SP + aimm$, setting the condition flags.

`SUB Wd|WSP, Wn|WSP, #aimm`

Subtract (immediate): $Wd|WSP = Wn|WSP - aimm$.

`SUB Xd|SP, Xn|SP, #aimm`

Subtract (extended immediate): $Xd|SP = Xn|SP - aimm$.

`SUBS Wd, Wn|WSP, #aimm`

Subtract and set flags (immediate): $Wd = Wn|WSP - aimm$, setting the condition flags.

`SUBS Xd, Xn|SP, #aimm`

Subtract and set flags (extended immediate): $Xd = Xn|SP - aimm$, setting the condition flags.

`CMP Wn|WSP, #aimm`

Compare (immediate): alias for `SUBS WZR, Wn|WSP, #aimm`.

`CMP Xn|SP, #aimm`

Compare (extended immediate): alias for `SUBS XZR, Xn|SP, #aimm`.

`CMN Wn|WSP, #aimm`

Compare negative (immediate): alias for `ADDS WZR, Wn|WSP, #aimm`.

`CMN Xn|SP, #aimm`

Compare negative (extended immediate): alias for `ADDS XZR, Xn|SP, #aimm`.

`MOV Wd|WSP, Wn|WSP`

Move (register): alias for `ADD Wd|WSP, Wn|WSP, #0`, but only when one or other of the registers is `WSP`. In other cases the `ORR Wd, WZR, Wn` instruction is used.

`MOV Xd|SP, Xn|SP`

Move (extended register): alias for `ADD Xd|SP, Xn|SP, #0`, but only when one or other of the registers is `SP`. In other cases the `ORR Xd, XZR, Xn` instruction is used.

5.4.2 Logical (immediate)

The logical immediate instructions accept a *bitmask immediate* value named `bimm32` or `bimm64`. Such an immediate is a 32 or 64 bit pattern viewed as a vector of identical elements of size $e = 2, 4, 8, 16, 32$ or (in the case of `bimm64`) 64 bits. Each element contains the same sub-pattern: a single run of 1 to $e-1$ non-zero bits,

rotated by 0 to $e-1$ bits. This mechanism can generate 5,334 unique 64-bit patterns (as 2,667 pairs of pattern and their bitwise inverse). Since the all-zeros and all-ones values cannot be described in this way, an assembler must either report an error for a logical instruction with such an immediate, or a programmer-friendly assembler may generate some other instruction which achieves the programmer's intended result. Using any other immediate value which cannot be represented in this way is an assembler error.

The logical (immediate) instructions may write to the current stack pointer, for example to align the stack pointer in a function prologue.

Note: Apart from `ANDS`, logical immediate instructions do not set the condition flags, but “interesting” results can usually directly control a `CBZ`, `CBNZ`, `TBZ` or `TBNZ` conditional branch.

`AND Wd|WSP, Wn, #bimm32`

Bitwise AND (immediate): $Wd|WSP = Wn \text{ AND } bimm32$.

`AND Xd|SP, Xn, #bimm64`

Bitwise AND (extended immediate): $Xd|SP = Xn \text{ AND } bimm64$.

`ANDS Wd, Wn, #bimm32`

Bitwise AND and Set Flags (immediate): $Wd = Wn \text{ AND } bimm32$, setting N & Z condition flags based on the result and clearing the C & V flags.

`ANDS Xd, Xn, #bimm64`

Bitwise AND and Set Flags (extended immediate): $Xd = Xn \text{ AND } bimm64$, setting N & Z condition flags based on the result and clearing the C & V flags.

`EOR Wd|WSP, Wn, #bimm32`

Bitwise exclusive OR (immediate): $Wd|WSP = Wn \text{ EOR } bimm32$.

`EOR Xd|SP, Xn, #bimm64`

Bitwise exclusive OR (extended immediate): $Xd|SP = Xn \text{ EOR } bimm64$.

`ORR Wd|WSP, Wn, #bimm32`

Bitwise inclusive OR (immediate): $Wd|WSP = Wn \text{ OR } bimm32$.

`ORR Xd|SP, Xn, #bimm64`

Bitwise inclusive OR (extended immediate): $Xd|SP = Xn \text{ OR } bimm64$.

`TST Wn, #bimm32`

Bitwise test (immediate): alias for `ANDS WZR, Wn, #bimm32`.

`TST Xn, #bimm64`

Bitwise test (extended immediate): alias for `ANDS XZR, Xn, #bimm64`

5.4.3 Move (wide immediate)

These instructions insert a 16-bit immediate (or inverted immediate) into a 16-bit aligned position in the destination register, with the value of the other destination register bits depending on the variant used. The shift amount `pos` may be any multiple of 16 less than the register size. Omitting “`LSL #pos`” implies a shift of 0.

`MOVZ Wt, #uimm16{, LSL #pos}`

Move with Zero (immediate): $Wt = \text{LSL}(uimm16, pos)$.

Usually disassembled as `MOV`, see below.

`MOVZ Xt, #uimm16{, LSL #pos}`

Move with Zero (extended immediate): $Xt = \text{LSL}(uimm16, pos)$.

Usually disassembled as `MOV`, see below.

```
MOVN Wt, #uimm16{, LSL #pos}
```

Move with NOT (immediate): $Wt = \text{NOT}(\text{LSL}(uimm16, pos))$.
Usually disassembled as MOV, see below.

```
MOVN Xt, #uimm16{, LSL #pos}
```

Move with NOT (extended immediate): $Xt = \text{NOT}(\text{LSL}(uimm16, pos))$.
Usually disassembled as MOV, see below.

```
MOVK Wt, #uimm16{, LSL #pos}
```

Move with Keep (immediate): $Wt_{\langle pos+15:pos \rangle} = uimm16$.

```
MOVK Xt, #uimm16{, LSL #pos}
```

Move with Keep (extended immediate): $Xt_{\langle pos+15:pos \rangle} = uimm16$.

5.4.3.1 Move (immediate)

```
MOV Wd|WZR|WSP, #simm32
```

A complex alias for a single MOVZ, or MOVN, or ORR (immediate with zero register) instruction to load a 32-bit immediate value into register *Wd*. An assembler error shall result if the immediate cannot be created by a single one of these instructions. If there is a choice, then to ensure reversability an assembler must prefer a MOVZ to MOVN, and MOVZ or MOVN to ORR. A disassembler should output ORR (immediate with zero), MOVZ and MOVN as a MOV mnemonic, except when ORR has an immediate that could be generated by a MOVZ or MOVN instruction, or where a MOVN has an immediate that could be encoded by MOVZ, or where MOVZ/MOVN #0 have a shift amount other than LSL #0, in which case the machine-instruction mnemonic must be used. Register 31 is named WZR when the alias represents a MOVZ or MOVN instruction, but WSP when the alias represents an ORR (immediate) instruction.

```
MOV Xd|XZR|SP, #simm64
```

As MOV but for loading a 64-bit immediate into register *Xd*. Register 31 is named XZR when the alias represents a MOVZ or MOVN instruction, but SP when the alias represents an ORR (immediate) instruction.

5.4.4 PC-relative Address Calculation

```
ADRP Xd, label
```

Address of Page: sign extends a 21-bit offset, shifts it left by 12 and adds it to the value of the PC with its bottom 12 bits cleared, writing the result to register *Xd*. This computes the base address of the 4KiB aligned memory region containing label, and is designed to be used in conjunction with a load, store or ADD instruction which supplies the bottom 12 bits of the label's address. This permits position-independent addressing of any location within $\pm 4\text{GiB}$ of the PC using two instructions, providing that dynamic relocation is done with a minimum granularity of 4KiB (i.e. the bottom 12 bits of the label's address are unaffected by the relocation). The term "page" is short-hand for the 4KiB relocation granule, and is not necessarily related to the virtual memory page size.

```
ADR Xd, label
```

Address: adds a 21-bit signed byte offset to the program counter, writing the result to register *Xd*. Used to compute the effective address of any location within $\pm 1\text{MiB}$ of the PC.

5.4.5 Bitfield Operations

In the machine instructions immediate operand #*r* is the right rotation required to move the source bitfield to its new position in the destination register, while #*s* is the leftmost (or sign) bit of the bitfield within the source register. Both values must be in the range 0 to reg.size - 1.

```
BFM Wd, Wn, #r, #s
```

Bitfield Move: if $s \geq r$ then $Wd_{\langle s-r:0 \rangle} = Wn_{\langle s:r \rangle}$, else $Wd_{\langle 32+s-r, 32-r \rangle} = Wn_{\langle s:0 \rangle}$.
Leaves other bits in *Wd* unchanged.

BFM $Xd, Xn, \#r, \#s$

Bitfield Move: if $s \geq r$ then $Xd\langle s-r:0 \rangle = Xn\langle s:r \rangle$, else $Xd\langle 64+s-r, 64-r \rangle = Xn\langle s:0 \rangle$.
Leaves other bits in Xd unchanged.

SBFM $Wd, Wn, \#r, \#s$

Signed Bitfield Move: if $s \geq r$ then $Wd\langle s-r:0 \rangle = Wn\langle s:r \rangle$, else $Wd\langle 32+s-r, 32-r \rangle = Wn\langle s:0 \rangle$.
Sets bits to the left of the destination bitfield to copies of its leftmost bit, and bits to the right to zero.

SBFM $Xd, Xn, \#r, \#s$

Signed Bitfield Move: if $s \geq r$ then $Xd\langle s-r:0 \rangle = Xn\langle s:r \rangle$, else $Xd\langle 64+s-r, 64-r \rangle = Xn\langle s:0 \rangle$.
Sets bits to the left of the destination bitfield to copies of its leftmost bit, and bits to the right to zero.

UBFM $Wd, Wn, \#r, \#s$

Unsigned Bitfield Move: if $s \geq r$ then $Wd\langle s-r:0 \rangle = Wn\langle s:r \rangle$, else $Wd\langle 32+s-r, 32-r \rangle = Wn\langle s:0 \rangle$.
Sets bits to the left and right of the destination bitfield to zero.

UBFM $Xd, Xn, \#r, \#s$

Unsigned Bitfield Move: if $s \geq r$ then $Xd\langle s-r:0 \rangle = Xn\langle s:r \rangle$, else $Xd\langle 32+s-r, 32-r \rangle = Xn\langle s:0 \rangle$.
Sets bits to the left and right of the destination bitfield to zero.

The following aliases provide more familiar bitfield insert and extract mnemonics, with conventional bitfield `lsb` and `width` operands, which must satisfy the constraints `lsb >= 0 && width >= 1 && lsb+width <= reg.size`

BFI $Wd, Wn, \#lsb, \#width$

Bitfield Insert: alias for BFM $Wd, Wn, \#((32-lsb) \& 31), \#(width-1)$.
Preferred for disassembly when $s < r$.

BFI $Xd, Xn, \#lsb, \#width$

Bitfield Insert (extended): alias for BFM $Xd, Xn, \#((64-lsb) \& 63), \#(width-1)$.
Preferred for disassembly when $s < r$.

BFXIL $Wd, Wn, \#lsb, \#width$

Bitfield Extract and Insert Low: alias for BFM $Wd, Wn, \#lsb, \#(lsb+width-1)$.
Preferred for disassembly when $s \geq r$.

BFXIL $Xd, Xn, \#lsb, \#width$

Bitfield Extract and Insert Low (extended): alias for BFM $Xd, Xn, \#lsb, \#(lsb+width-1)$.
Preferred for disassembly when $s \geq r$.

SBFIZ $Wd, Wn, \#lsb, \#width$

Signed Bitfield Insert in Zero: alias for SBFM $Wd, Wn, \#((32-lsb) \& 31), \#(width-1)$.
Preferred for disassembly when $s < r$.

SBFIZ $Xd, Xn, \#lsb, \#width$

Signed Bitfield Insert in Zero (extended): alias for SBFM $Xd, Xn, \#((64-lsb) \& 63), \#(width-1)$.
Preferred for disassembly when $s < r$.

SBFX $Wd, Wn, \#lsb, \#width$

Signed Bitfield Extract: alias for SBFM $Wd, Wn, \#lsb, \#(lsb+width-1)$.
Preferred for disassembly when $s \geq r$.

SBFX $Xd, Xn, \#lsb, \#width$

Signed Bitfield Extract (extended): alias for SBFM $Xd, Xn, \#lsb, \#(lsb+width-1)$.
Preferred for disassembly when $s \geq r$.

UBFIZ Wd, Wn, #lsb, #width

Unsigned Bitfield Insert in Zero: alias for UBFM Wd,Wn,#((32-lsb)&31),#(width-1).
Preferred for disassembly when $s < r$.

UBFIZ Xd, Xn, #lsb, #width

Unsigned Bitfield Insert in Zero (extended): alias for UBFM Xd,Xn,#((64-lsb)&63),#(width-1).
Preferred for disassembly when $s < r$.

UBFX Wd, Wn, #lsb, #width

Unsigned Bitfield Extract: alias for UBFM Wd,Wn,#lsb,#(lsb+width-1).
Preferred for disassembly when $s \geq r$.

UBFX Xd, Xn, #lsb, #width

Unsigned Bitfield Extract (extended): alias for UBFM Xd,Xn,#lsb,#(lsb+width-1).
Preferred for disassembly when $s \geq r$.

5.4.6 Extract (immediate)

EXTR Wd, Wn, Wm, #lsb

Extract: $Wd = Wn:Wm<lsb+31,lsb>$. The bit position *lsb* must be in the range 0 to 31.

EXTR Xd, Xn, Xm, #lsb

Extract (extended): $Xd = Xn:Xm<lsb+63,lsb>$. The bit position *lsb* must be in the range 0 to 63.

5.4.7 Shift (immediate)

All immediate shifts and rotates are aliases, implemented using the Bitfield or Extract instructions. In all cases the immediate shift amount *uimm* must be in the range 0 to (*reg.size* - 1).

ASR Wd, Wn, #uimm

Arithmetic Shift Right (immediate): alias for SBFM Wd,Wn,#uimm,#31.

ASR Xd, Xn, #uimm

Arithmetic Shift Right (extended immediate): alias for SBFM Xd,Xn,#uimm,#63.

LSL Wd, Wn, #uimm

Logical Shift Left (immediate): alias for UBFM Wd,Wn,#((32-uimm)&31),#(31-uimm).

LSL Xd, Xn, #uimm

Logical Shift Left (extended immediate): alias for UBFM Xd,Xn,#((64-uimm)&63),#(63-uimm)

LSR Wd, Wn, #uimm

Logical Shift Right (immediate): alias for UBFM Wd,Wn,#uimm,#31.

LSR Xd, Xn, #uimm

Logical Shift Right (extended immediate): alias for UBFM Xd,Xn,#uimm,#31.

ROR Wd, Wm, #uimm

Rotate Right (immediate): alias for EXTR Wd,Wm,Wm,#uimm.

ROR Xd, Xm, #uimm

Rotate Right (extended immediate): alias for EXTR Xd,Xm,Xm,#uimm.

5.4.8 Sign/Zero Extend

SXT[BH] Wd, Wn

Signed Extend Byte|Halfword: alias for SBFM Wd,Wn,#0,#7|15.

SXT [BHW] X_d, W_n

Signed Extend Byte|Halfword|Word (extended): alias for SBFM $X_d, X_n, \#0, \#7 | 15 | 31$.

UXT [BH] W_d, W_n

Unsigned Extend Byte|Halfword|Word: alias for UBFM $W_d, W_n, \#0, \#7 | 15$. A programmer-friendly assembler should accept a destination X_d in place of W_d , however that is not the preferred form for disassembly.

5.5 Data Processing (register)

The following instruction groups are supported:

- Arithmetic (shifted register)
- Arithmetic (extending register)
- Logical (shifted register)
- Arithmetic (unshifted register)
- Shift (register)
- Bitwise operations

5.5.1 Arithmetic (shifted register)

The shifted register instructions apply an optional shift to the final source operand value before performing the arithmetic operation. The register size of the instruction controls where new bits are fed in to the intermediate result on a right shift or rotate (i.e. bit 63 or 31).

The shift operators LSL, ASR and LSR accept an immediate shift amount in the range 0 to reg.size - 1.

Omitting the shift operator implies “LSL #0” (i.e. no shift), and “LSL #0” should not be output by a disassembler; all other shifts by zero must be output.

The register names SP and WSP may not be used with this class of instructions, instead see section 5.5.2.

ADD $W_d, W_n, W_m\{, \text{ashift } \#imm\}$

Add (register): $W_d = W_n + \text{ashift}(W_m, imm)$.

ADD $X_d, X_n, X_m\{, \text{ashift } \#imm\}$

Add (extended register): $X_d = X_n + \text{ashift}(X_m, imm)$.

ADDS $W_d, W_n, W_m\{, \text{ashift } \#imm\}$

Add and Set Flags (register): $W_d = W_n + \text{ashift}(W_m, imm)$, setting condition flags.

ADDS $X_d, X_n, X_m\{, \text{ashift } \#imm\}$

Add and Set Flags (extended register): $X_d = X_n + \text{ashift}(X_m, imm)$, setting condition flags.

SUB $W_d, W_n, W_m\{, \text{ashift } \#imm\}$

Subtract (register): $W_d = W_n - \text{ashift}(W_m, imm)$.

SUB $X_d, X_n, X_m\{, \text{ashift } \#imm\}$

Subtract (extended register): $X_d = X_n - \text{ashift}(X_m, imm)$.

SUBS $W_d, W_n, W_m\{, \text{ashift } \#imm\}$

Subtract and Set Flags (register): $W_d = W_n - \text{ashift}(W_m, imm)$, setting condition flags.

SUBS Xd, Xn, Xm{, ashift #imm}

Subtract and Set Flags (extended register): $Xd = Xn - \text{ashift}(Xm, \text{imm})$, setting condition flags.

CMN Wn, Wm{, ashift #imm}

Compare Negative (register): alias for ADDS WZR, Wn, Wm{, ashift #imm}.

CMN Xn, Xm{, ashift #imm}

Compare Negative (extended register): alias for ADDS XZR, Xn, Xm{, ashift #imm}.

CMP Wn, Wm{, ashift #imm}

Compare (register): alias for SUBS WZR, Wn, Wm{, ashift #imm}.

CMP Xn, Xm{, ashift #imm}

Compare (extended register): alias for SUBS XZR, Xn, Xm{, ashift #imm}.

NEG Wd, Wm{, ashift #imm}

Negate: alias for SUB Wd, WZR, Wm{, ashift #imm}.

NEG Xd, Xm{, ashift #imm}

Negate (extended): alias for SUB Xd, XZR, Xm{, ashift #imm}.

NEGS Wd, Wm{, ashift #imm}

Negate and Set Flags: alias for SUBS Wd, WZR, Wm{, ashift #imm}.

NEGS Xd, Xm{, ashift #imm}

Negate and Set Flags (extended): alias for SUBS Xd, XZR, Xm{, ashift #imm}.

5.5.2 Arithmetic (extending register)

The extending register instructions differ from the shifted register forms in that:

1. Non-flag setting variants permit use of the stack pointer as either or both of the destination and first source register. The flag setting variants only permit the stack pointer as the first source register.
2. They provide an optional sign or zero-extension of a portion of the second source register value, followed by an optional immediate left shift between 1 and 4 inclusive.

The "extending shift" is described by the mandatory `extend` operator `SXTB`, `SXTH`, `SXTW`, `SXTX`, `UXTB`, `UXTH`, `UXTW` or `UXTX`, which is followed by an optional left shift amount. If the shift amount is omitted then it defaults to zero, and a zero shift amount should not be output by a disassembler.

For 64-bit instruction forms the operators `UXTX` and `SXTX` (`UXTX` preferred) both perform a "no-op" extension of the second source register, followed by optional shift. If and only if `UXTX` used in combination with the register name `SP` in at least one operand, then the alias `LSL` is preferred, and in this case both the operator and shift amount may be omitted, implying "`LSL #0`".

Similarly for 32-bit instruction forms the operators `UXTW` and `SXTW` (`UXTW` preferred) both perform a "no-op" extension of the second source register, followed by optional shift. If and only if `UXTW` is used in combination with the register name `WSP` in at least one operand, then the alias `LSL` is preferred. In the 64-bit form of these instructions the final register operand is written as `Wm` for all but the (possibly omitted) `UXTX/LSL` and `SXTX` operators. For example:

```
CMP    X4, W5, SXTW
ADD    X1, X2, W3, UXTB #2
SUB    SP, SP, X1           // SUB SP, SP, X1, UXTX #0
```

ADD Wd|WSP, Wn|WSP, Wm, extend {#imm}

Add (register, extending): $Wd|WSP = Wn|WSP + LSL(\text{extend}(Wm), \text{imm})$.

ADD Xd|SP, Xn|SP, Wm, extend {#imm}

Add (extended register, extending): $Xd|SP = Xn|SP + LSL(\text{extend}(Wm), \text{imm})$.

ADD Xd|SP, Xn|SP, Xm{, UXTX|LSL #imm}

Add (extended register, extending): $Xd|SP = Xn|SP + LSL(Xm, \text{imm})$.

ADDS Wd, Wn|WSP, Wm, extend {#imm}

Add and Set Flags (register, extending): $Wd = Wn|WSP + LSL(\text{extend}(Wm), \text{imm})$, setting the condition flags.

ADDS Xd, Xn|SP, Wm, extend {#imm}

Add and Set Flags (extended register, extending): $Xd = Xn|SP + LSL(\text{extend}(Wm), \text{imm})$, setting the condition flags.

ADDS Xd, Xn|SP, Xm{, UXTX|LSL #imm}

Add and Set Flags (extended register, extending): $Xd = Xn|SP + LSL(Xm, \text{imm})$, setting the condition flags.

SUB Wd|WSP, Wn|WSP, Wm, extend {#imm}

Subtract (register, extending): $Wd|WSP = Wn|WSP - LSL(\text{extend}(Wm), \text{imm})$.

SUB Xd|SP, Xn|SP, Wm, extend {#imm}

Subtract (extended register, extending): $Xd|SP = Xn|SP - LSL(\text{extend}(Wm), \text{imm})$.

SUB Xd|SP, Xn|SP, Xm{, UXTX|LSL #imm}

Subtract (extended register, extending): $Xd|SP = Xn|SP - LSL(Xm, \text{imm})$.

SUBS Wd, Wn|WSP, Wm, extend {#imm}

Subtract and Set Flags (register, extending): $Wd = Wn|WSP - LSL(\text{extend}(Wm), \text{imm})$, setting the condition flags.

SUBS Xd, Xn|SP, Wm, extend {#imm}

Subtract and Set Flags (extended register, extending): $Xd = Xn|SP - LSL(\text{extend}(Wm), \text{imm})$, setting the condition flags.

SUBS Xd, Xn|SP, Xm{, UXTX|LSL #imm}

Subtract and Set Flags (extended register, extending): $Xd = Xn|SP - LSL(Xm, \text{imm})$, setting the condition flags.

CMN Wn|WSP, Wm, extend {#imm}

Compare Negative (register, extending): alias for ADDS WZR, Wn, Wm, extend {#imm}.

CMN Xn|SP, Wm, extend {#imm}

Compare Negative (extended register, extending): alias for ADDS XZR, Xn, Wm, extend {#imm}.

CMN Xn|SP, Xm{, UXTX|LSL #imm}

Compare Negative (extended register, extending): alias for ADDS XZR, Xn, Xm{, UXTX|LSL #imm}.

CMP Wn|WSP, Wm, extend {#imm}

Compare (register, extending): alias for SUBS WZR, Wn, Wm, extend {#imm}.

CMP Xn|SP, Wm, extend {#imm}

Compare (extended register, extending): alias for SUBS XZR, Xn, Wm, extend {#imm}.

CMP Xn|SP, Xm{, UXTX|LSL #imm}

Compare (extended register, extending): alias for SUBS XZR, Xn, Xm{, UXTX|LSL #imm}.

5.5.3 Logical (shifted register)

The logical (shifted register) instructions apply an optional shift operator to their final source operand before performing the main operation. The register size of the instruction controls where new bits are fed in to the intermediate result on a right shift or rotate (i.e. bit 63 or 31).

The shift operators `LSL`, `ASR`, `LSR` and `ROR` accept an immediate shift amount in the range 0 to `reg.size - 1`.

Omitting the shift operator implies “`LSL #0`” (i.e. no shift), and an “`LSL #0`” should not be output by a disassembler – however all other shifts by zero must be output.

Note: Apart from `ANDS` and `BICS` the logical instructions do not set the condition flags, but “interesting” results can usually directly control a `CBZ`, `CBNZ`, `TBZ` or `TBNZ` conditional branch.

```
AND Wd, Wn, Wm{, lshift #imm}
```

Bitwise AND (register): $Wd = Wn \text{ AND } \text{lshift}(Wm, \text{imm})$.

```
AND Xd, Xn, Xm{, lshift #imm}
```

Bitwise AND (extended register): $Xd = Xn \text{ AND } \text{lshift}(Xm, \text{imm})$.

```
ANDS Wd, Wn, Wm{, lshift #imm}
```

Bitwise AND and Set Flags (register): $Wd = Wn \text{ AND } \text{lshift}(Wm, \text{imm})$, setting N & Z condition flags based on the result and clearing the C & V flags.

```
ANDS Xd, Xn, Xm{, lshift #imm}
```

Bitwise AND and Set Flags (extended register): $Xd = Xn \text{ AND } \text{lshift}(Xm, \text{imm})$, setting N & Z condition flags based on the result and clearing the C & V flags.

```
BIC Wd, Wn, Wm{, lshift #imm}
```

Bit Clear (register): $Wd = Wn \text{ AND } \text{NOT}(\text{lshift}(Wm, \text{imm}))$.

```
BIC Xd, Xn, Xm{, lshift #imm}
```

Bit Clear (extended register): $Xd = Xn \text{ AND } \text{NOT}(\text{lshift}(Xm, \text{imm}))$.

```
BICS Wd, Wn, Wm{, lshift #imm}
```

Bit Clear and Set Flags (register): $Wd = Wn \text{ AND } \text{NOT}(\text{lshift}(Wm, \text{imm}))$, setting N & Z condition flags based on the result and clearing the C & V flags.

```
BICS Xd, Xn, Xm{, lshift #imm}
```

Bit Clear and Set Flags (extended register): $Xd = Xn \text{ AND } \text{NOT}(\text{lshift}(Xm, \text{imm}))$, setting N & Z condition flags based on the result and clearing the C & V flags.

```
EON Wd, Wn, Wm{, lshift #imm}
```

Bitwise exclusive OR NOT (register): $Wd = Wn \text{ EOR } \text{NOT}(\text{lshift}(Wm, \text{imm}))$.

```
EON Xd, Xn, Xm{, lshift #imm}
```

Bitwise exclusive OR NOT (extended register): $Xd = Xn \text{ EOR } \text{NOT}(\text{lshift}(Xm, \text{imm}))$.

```
EOR Wd, Wn, Wm{, lshift #imm}
```

Bitwise exclusive OR (register): $Wd = Wn \text{ EOR } \text{lshift}(Wm, \text{imm})$.

```
EOR Xd, Xn, Xm{, lshift #imm}
```

Bitwise exclusive OR (extended register): $Xd = Xn \text{ EOR } \text{lshift}(Xm, \text{imm})$.

```
ORR Wd, Wn, Wm{, lshift #imm}
```

Bitwise inclusive OR (register): $Wd = Wn \text{ OR } \text{lshift}(Wm, \text{imm})$.

```
ORR Xd, Xn, Xm{, lshift #imm}
```

Bitwise inclusive OR (extended register): $Xd = Xn \text{ OR } \text{lshift}(Xm, \text{imm})$.

```
ORN Wd, Wn, Wm{, lshift #imm}
```

Bitwise inclusive OR NOT (register): $Wd = Wn \text{ OR } \text{NOT}(\text{lshift}(Wm, \text{imm}))$.

```
ORN Xd, Xn, Xm{, lshift #imm}
```

Bitwise inclusive OR NOT (extended register): $Xd = Xn \text{ OR } \text{NOT}(\text{lshift}(Xm, \text{imm}))$.

```
MOV Wd, Wm
```

Move (register): alias for ORR Wd, WZR, Wm.

```
MOV Xd, Xm
```

Move (extended register): alias for ORR Xd, XZR, Xm.

```
MVN Wd, Wm{, lshift #imm}
```

Move NOT (register): alias for ORN Wd, WZR, Wm{, lshift #imm}.

```
MVN Xd, Xm{, lshift #imm}
```

Move NOT (extended register): alias for ORN Xd, XZR, Xm{, lshift #imm}.

```
TST Wn, Wm{, lshift #imm}
```

Bitwise Test (register): alias for ANDS WZR, Wn, Wm{, lshift #imm}.

```
TST Xn, Xm{, lshift #imm}
```

Bitwise Test (extended register): alias for ANDS XZR, Xn, Xm{, lshift #imm}.

5.5.4 Variable Shift

The variable shift amount in Wm or Xm is positive, and modulo the register size. For example an extended 64-bit shift with Xm containing the value 65 will result in a shift by $(65 \text{ MOD } 64) = 1$ bit. The machine instructions are as follows:

```
ASRV Wd, Wn, Wm
```

Arithmetic Shift Right Variable: $Wd = \text{ASR}(Wn, Wm \ \& \ 0x1f)$.

```
ASRV Xd, Xn, Xm
```

Arithmetic Shift Right Variable (extended): $Xd = \text{ASR}(Xn, Xm \ \& \ 0x3f)$.

```
LSLV Wd, Wn, Wm
```

Logical Shift Left Variable: $Wd = \text{LSL}(Wn, Wm \ \& \ 0x1f)$.

```
LSLV Xd, Xn, Xm
```

Logical Shift Left Variable (extended register): $Xd = \text{LSL}(Xn, Xm \ \& \ 0x3f)$.

```
LSRV Wd, Wn, Wm
```

Logical Shift Right Variable: $Wd = \text{LSR}(Wn, Wm \ \& \ 0x1f)$.

```
LSRV Xd, Xn, Xm
```

Logical Shift Right Variable (extended): $Xd = \text{LSR}(Xn, Xm \ \& \ 0x3f)$.

```
RORV Wd, Wn, Wm
```

Rotate Right Variable: $Wd = \text{ROR}(Wn, Wm \ \& \ 0x1f)$.

```
RORV Xd, Xn, Xm
```

Rotate Right Variable (extended): $Xd = \text{ROR}(Xn, Xm \ \& \ 0x3f)$.

However the “Variable Shift” machine instructions have a preferred set of “Shift (register)” aliases which match the Shift (immediate) aliases described elsewhere:

ASR Wd, Wn, Wm

Arithmetic Shift Right (register): preferred alias for ASRV Wd, Wn, Wm .

ASR Xd, Xn, Xm

Arithmetic Shift Right (extended register): preferred alias for ASRV Xd, Xn, Xm .

LSL Wd, Wn, Wm

Logical Shift Left (register): preferred alias for LSLV Wd, Wn, Wm .

LSL Xd, Xn, Xm

Logical Shift Left (extended register): preferred alias for LSLV Xd, Xn, Xm .

LSR Wd, Wn, Wm

Logical Shift Right (register): preferred alias for LSRV Wd, Wn, Wm .

LSR Xd, Xn, Xm

Logical Shift Right (extended register): preferred alias for LSRV Xd, Xn, Xm .

ROR Wd, Wn, Wm

Rotate Right (register): preferred alias for RORV Wd, Wn, Wm .

ROR Xd, Xn, Xm

Rotate Right (extended register): preferred alias for RORV Xd, Xn, Xm .

5.5.5 Bit Operations

CLS Wd, Wm

Count Leading Sign Bits: sets wd to the number of consecutive bits following the topmost bit in Wm , that are the same as the topmost bit. The count does not include the topmost bit itself, so the result will be in the range 0 to 31 inclusive.

CLS Xd, Xm

Count Leading Sign Bits (extended): sets xd to the number of consecutive bits following the topmost bit in Xm , that are the same as the topmost bit. The count does not include the topmost bit itself, so the result will be in the range 0 to 63 inclusive.

CLZ Wd, Wm

Count Leading Zeros: sets wd to the number of binary zeros at the most significant end of Wm . The result will be in the range 0 to 32 inclusive.

CLZ Xd, Xm

Count Leading Zeros: (extended) sets xd to the number of binary zeros at the most significant end of Xm . The result will be in the range 0 to 64 inclusive.

RBIT Wd, Wm

Reverse Bits: reverses the 32 bits from Wm , writing to wd .

RBIT Xd, Xm

Reverse Bits (extended): reverses the 64 bits from Xm , writing to Xd .

REV Wd, Wm

Reverse Bytes: reverses the 4 bytes in Wm , writing to wd .

REV Xd, Xm

Reverse Bytes (extended): reverses 8 bytes in Xm , writing to Xd .

REV16 Wd, Wm

Reverse Bytes in Halfwords: reverses the 2 bytes in each 16-bit element of Wm , writing to wd .

REV16 Xd, X_m

Reverse Bytes in Halfwords (extended): reverses the 2 bytes in each 16-bit element of X_m , writing to Xd .

REV32 Xd, X_m

Reverse Bytes in Words (extended): reverses the 4 bytes in each 32-bit element of X_m , writing to Xd .

5.5.6 Conditional Data Processing

These instructions support two unshifted source registers, with the condition flags as a third source. Note that the instructions are not conditionally executed: the destination register is always written.

ADC Wd, Wn, Wm

Add with Carry: $Wd = Wn + Wm + C$.

ADC Xd, Xn, X_m

Add with Carry (extended): $Xd = Xn + X_m + C$.

ADCS Wd, Wn, Wm

Add with Carry and Set Flags: $Wd = Wn + Wm + C$, setting the condition flags.

ADCS Xd, Xn, X_m

Add with Carry and Set Flags (extended): $Xd = Xn + X_m + C$, setting the condition flags.

CSEL $Wd, Wn, Wm, cond$

Conditional Select: $Wd = \text{if } cond \text{ then } Wn \text{ else } Wm$.

CSEL $Xd, Xn, X_m, cond$

Conditional Select (extended): $Xd = \text{if } cond \text{ then } Xn \text{ else } X_m$.

CSINC $Wd, Wn, Wm, cond$

Conditional Select Increment: $Wd = \text{if } cond \text{ then } Wn \text{ else } Wm+1$.

CSINC $Xd, Xn, X_m, cond$

Conditional Select Increment (extended): $Xd = \text{if } cond \text{ then } Xn \text{ else } X_m+1$.

CSINV $Wd, Wn, Wm, cond$

Conditional Select Invert: $Wd = \text{if } cond \text{ then } Wn \text{ else } \text{NOT}(Wm)$.

CSINV $Xd, Xn, X_m, cond$

Conditional Select Invert (extended): $Xd = \text{if } cond \text{ then } Xn \text{ else } \text{NOT}(X_m)$.

CSNEG $Wd, Wn, Wm, cond$

Conditional Select Negate: $Wd = \text{if } cond \text{ then } Wn \text{ else } -Wm$.

CSNEG $Xd, Xn, X_m, cond$

Conditional Select Negate (extended): $Xd = \text{if } cond \text{ then } Xn \text{ else } -X_m$.

CSET $Wd, cond$

Conditional Set: $Wd = \text{if } cond \text{ then } 1 \text{ else } 0$.

Alias for CSINC $Wd, WZR, WZR, \text{invert}(cond)$.

CSET $Xd, cond$

Conditional Set (extended): $Xd = \text{if } cond \text{ then } 1 \text{ else } 0$.

Alias for CSINC $Xd, XZR, XZR, \text{invert}(cond)$

CSETM $Wd, cond$

Conditional Set Mask: $Wd = \text{if } cond \text{ then } -1 \text{ else } 0$.

Alias for CSINV $Wd, WZR, WZR, \text{invert}(cond)$.

CSETM X_d , $cond$

Conditional Set Mask (extended): $X_d = \text{if } cond \text{ then } -1 \text{ else } 0.$
 Alias for CSINV $X_d, WZR, WZR, \text{invert}(cond).$

CINC $W_d, W_n, cond$

Conditional Increment: $W_d = \text{if } cond \text{ then } W_{n+1} \text{ else } W_n.$
 Alias for CSINC $W_d, W_n, W_n, \text{invert}(cond).$

CINC $X_d, X_n, cond$

Conditional Increment (extended): $X_d = \text{if } cond \text{ then } X_{n+1} \text{ else } X_n.$
 Alias for CSINC $X_d, X_n, X_n, \text{invert}(cond).$

CINV $W_d, W_n, cond$

Conditional Invert: $W_d = \text{if } cond \text{ then } \text{NOT}(W_n) \text{ else } W_n.$
 Alias for CSINV $W_d, W_n, W_n, \text{invert}(cond).$

CINV $X_d, X_n, cond$

Conditional Invert (extended): $X_d = \text{if } cond \text{ then } \text{NOT}(X_n) \text{ else } X_n.$
 Alias for CSINV $X_d, X_n, X_n, \text{invert}(cond).$

CNEG $W_d, W_n, cond$

Conditional Negate: $W_d = \text{if } cond \text{ then } -W_n \text{ else } W_n.$
 Alias for CSNEG $W_d, W_n, W_n, \text{invert}(cond).$

CNEG $X_d, X_n, cond$

Conditional Negate (extended): $X_d = \text{if } cond \text{ then } -X_n \text{ else } X_n.$
 Alias for CSNEG $X_d, X_n, X_n, \text{invert}(cond).$

SBC W_d, W_n, W_m

Subtract with Carry: $W_d = W_n - W_m - 1 + C.$

SBC X_d, X_n, X_m

Subtract with Carry (extended): $X_d = X_n - X_m - 1 + C.$

SBCS W_d, W_n, W_m

Subtract with Carry and Set Flags: $W_d = W_n - W_m - 1 + C$, setting the condition flags.

SBCS X_d, X_n, X_m

Subtract with Carry and Set Flags (extended): $X_d = X_n - X_m - 1 + C$, setting the condition flags.

NGC W_d, W_m

Negate with Carry: $W_d = -W_m - 1 + C.$
 Alias for SBC $W_d, WZR, W_m.$

NGC X_d, X_m

Negate with Carry (extended): $X_d = -X_m - 1 + C.$
 Alias for SBC $X_d, XZR, X_m.$

NGCS W_d, W_m

Negate with Carry and Set Flags: $W_d = -W_m - 1 + C$, setting the condition flags.
 Alias for SBCS $W_d, WZR, W_m.$

NGCS X_d, X_m

Negate with Carry and Set Flags (extended): $X_d = -X_m - 1 + C$, setting the condition flags.
 Alias for SBCS $X_d, XZR, X_m.$

5.5.7 Conditional Comparison

Conditional comparison provides a “conditional select” for the NZCV condition flags, setting the flags to the result of a comparison if the input condition is true, or to an immediate value if the input condition is false. There are register and immediate forms, with the immediate form accepting a small 5-bit unsigned value.

The #uimm4 operand is the bitmask used to set the NZCV flags when the input condition is false, with bit 3 the new value of the N flag, bit 2 the Z flag, bit 1 the C flag, and bit 0 the V flag.

CCMN Wn, Wm, #uimm4, cond

Conditional Compare Negative (register):

NZCV = if cond then CMP(Wn,-Wm) else uimm4.

CCMN Xn, Xm, #uimm4, cond

Conditional Compare Negative (extended register):

NZCV = if cond then CMP(Xn,-Xm) else uimm4.

CCMN Wn, #uimm5, #uimm4, cond

Conditional Compare Negative (immediate):

NZCV = if cond then CMP(Wn,-uimm5) else uimm4.

CCMN Xn, #uimm5, #uimm4, cond

Conditional Compare Negative (extended immediate):

NZCV = if cond then CMP(Xn,-uimm5) else uimm4.

CCMP Wn, Wm, #uimm4, cond

Conditional Compare (register):

NZCV = if cond then CMP(Wn,Wm) else uimm4.

CCMP Xn, Xm, #uimm4, cond

Conditional Compare (extended register):

NZCV = if cond then CMP(Xn,Xm) else uimm4.

CCMP Wn, #uimm5, #uimm4, cond

Conditional Compare (immediate):

NZCV = if cond then CMP(Wn,uimm5) else uimm4.

CCMP Xn, #uimm5, #uimm4, cond

Conditional Compare (extended immediate):

NZCV = if cond then CMP(Xn,uimm5) else uimm4.

5.6 Integer Multiply / Divide

5.6.1 Multiply

MADD Wd, Wn, Wm, Wa

Multiply-Add: $Wd = Wa + (Wn \times Wm)$.

MADD Xd, Xn, Xm, Xa

Multiply-Add (extended): $Xd = Xa + (Xn \times Xm)$.

MSUB Wd, Wn, Wm, Wa

Multiply-Subtract: $Wd = Wa - (Wn \times Wm)$.

MSUB Xd, Xn, Xm, Xa

Multiply-Subtract (extended): $Xd = Xa - (Xn \times Xm)$.

MNEG Wd, Wn, Wm

Multiply-Negate: $Wd = -(Wn \times Wm)$.

Alias for MSUB Wd, Wn, Wm, WZR .

MNEG Xd, Xn, Xm

Multiply-Negate (extended): $Xd = -(Xn \times Xm)$.

Alias for MSUB Xd, Xn, Xm, XZR .

MUL Wd, Wn, Wm

Multiply: $Wd = Wn \times Wm$.

Alias for MADD Wd, Wn, Wm, WZR .

MUL Xd, Xn, Xm

Multiply (extended): $Xd = Xn \times Xm$.

Alias for MADD Xd, Xn, Xm, XZR .

SMADDL Xd, Wn, Wm, Xa

Signed Multiply-Add Long: $Xd = Xa + (Wn \times Wm)$, treating source operands as signed.

SMSUBL Xd, Wn, Wm, Xa

Signed Multiply-Subtract Long: $Xd = Xa - (Wn \times Wm)$, treating source operands as signed.

SMNEGL Xd, Wn, Wm

Signed Multiply-Negate Long: $Xd = -(Wn \times Wm)$, treating source operands as signed.

Alias for SMSUBL Xd, Wn, Wm, XZR .

SMULL Xd, Wn, Wm

Signed Multiply Long: $Xd = Wn \times Wm$, treating source operands as signed.

Alias for SMADDL Xd, Wn, Wm, XZR .

SMULH Xd, Xn, Xm

Signed Multiply High: $Xd = (Xn \times Xm) \langle 127:64 \rangle$, treating source operands as signed.

UMADDL Xd, Wn, Wm, Xa

Unsigned Multiply-Add Long: $Xd = Xa + (Wn \times Wm)$, treating source operands as unsigned.

UMSUBL Xd, Wn, Wm, Xa

Unsigned Multiply-Subtract Long: $Xd = Xa - (Wn \times Wm)$, treating source operands as unsigned.

UMNEGL Xd, Wn, Wm

Unsigned Multiply-Negate Long: $Xd = -(Wn \times Wm)$, treating source operands as unsigned.

Alias for UMSUBL Xd, Wn, Wm, XZR .

UMULL Xd, Wn, Wm

Unsigned Multiply Long: $Xd = Wn \times Wm$, treating source operands as unsigned.

Alias for UMADDL Xd, Wn, Wm, XZR .

UMULH Xd, Xn, Xm

Unsigned Multiply High: $Xd = (Xn \times Xm) \langle 127:64 \rangle$, treating source operands as unsigned.

5.6.2 Divide

The integer divide instructions compute (numerator÷denominator) and deliver the quotient, which is rounded towards zero. The remainder may then be computed as numerator−(quotient×denominator) using the MSUB instruction.

If a signed integer division ($\text{INT_MIN} \div -1$) is performed, where INT_MIN is the most negative integer value representable in the selected register size, then the result will overflow the signed integer range. No indication of this overflow is produced and the result written to the destination register will be INT_MIN .

NOTE: The divide instructions do not generate a trap upon division by zero, but write zero to the destination register.

SDIV Wd, Wn, Wm

Signed Divide: $Wd = Wn \div Wm$, treating source operands as signed.

SDIV Xd, Xn, Xm

Signed Divide (extended): $Xd = Xn \div Xm$, treating source operands as signed.

UDIV Wd, Wn, Wm

Unsigned Divide: $Wd = Wn \div Wm$, treating source operands as unsigned.

UDIV Xd, Xn, Xm

Unsigned Divide (extended): $Xd = Xn \div Xm$, treating source operands as unsigned.

5.7 Scalar Floating-point

The A64 scalar floating point instruction set is based closely on ARM VFPv4, and unless explicitly mentioned in individual instruction descriptions the handling and generation of denormals, infinities, non-numeric, and floating point exceptions, replicates the behaviour of the equivalent VFPv4 instructions. Full details may be found in the floating point pseudocode.

5.7.1 Floating-point/SIMD Scalar Memory Access

The FP/SIMD scalar load-store instructions operate on the scalar form of the FP/SIMD registers as described in §4.4.2.1. The available memory addressing modes (see §4.5) are identical to the general-purpose register load-store instructions, and like those instructions permit arbitrary address alignment unless strict alignment checking is enabled. However, unlike the general-purpose load-store instructions, the FP/SIMD load-store instructions make no guarantee of atomicity, even when the address is naturally aligned to the size of data.

5.7.1.1 Load-Store Single FP/SIMD Register

Addressing modes supported by `addr` (referring to §4.5):

- Base plus immediate offset (scaled 12-bit unsigned or unscaled 9-bit signed);
- Base plus 64-bit register offset (optionally scaled);
- Base plus 32-bit extended register offset (optionally scaled);
- Pre-indexed by immediate offset (unscaled 9-bit signed);
- Post-indexed by immediate offset (unscaled 9-bit signed);
- Literal (pc-relative), for loads of 32-bits or larger.

`LDR Bt, addr`

Load Register (byte): load a byte from memory addressed by `addr` to 8-bit `Bt`.

`LDR Ht, addr`

Load Register (half): load a halfword from memory addressed by `addr` to 16-bit `Ht`.

`LDR St, addr`

Load Register (single): load a word from memory addressed by `addr` to 32-bit `St`.

`LDR Dt, addr`

Load Register (double): load a doubleword from memory addressed by `addr` to 64-bit `Dt`.

`LDR Qt, addr`

Load Register (quad): load a quadword from memory addressed by `addr` to 128-bit `Qt`.

`STR Bt, addr`

Store Register (byte): store byte from 8-bit `Bt` to memory addressed by `addr`.

`STR Ht, addr`

Store Register (half): store halfword from 16-bit `Ht` to memory addressed by `addr`.

`STR St, addr`

Store Register (single): store word from 32-bit `St` to memory addressed by `addr`.

`STR Dt, addr`

Store Register (double): store doubleword from 64-bit `Dt` to memory addressed by `addr`.

`STR Qt, addr`

Store Register (quad): store quadword from 128-bit `Qt` to memory addressed by `addr`.

5.7.1.2 Load-Store Single FP/SIMD Register (unscaled offset)

Addressing modes supported (referring to §4.5):

- Base plus immediate offset (unscaled 9-bit signed).

These mnemonics distinguish instructions which use this form of offset when the byte offset value could also be represented by instructions which use the scaled 12-bit unsigned immediate offset form, i.e. when its value is positive and naturally aligned to the transfer size.

A programmer-friendly assembler should also generate these instructions in response to the standard `LDR/STR` mnemonics when the immediate offset is unambiguous, i.e. negative or unaligned. A disassembler could also display these instructions using the standard `LDR/STR` mnemonics when the encoded immediate is unambiguous, however that is not required by the architectural assembly language.

`LDUR Bt, [base,#simm9]`

Load (Unscaled) Register (byte): load a byte from memory addressed by `base+simm9` to 8-bit `Bt`.

`LDUR Ht, [base,#simm9]`

Load (Unscaled) Register (half): load a halfword from memory addressed by `base+simm9` to 16-bit `Ht`.

`LDUR St, [base,#simm9]`

Load (Unscaled) Register (single): load a word from memory addressed by `base+simm9` to 32-bit `St`.

`LDUR Dt, [base,#simm9]`

Load (Unscaled) Register (double): load a doubleword from memory addressed by `base+simm9` to 64-bit `Dt`.

`LDUR Qt, [base,#simm9]`

Load (Unscaled) Register (quad): load a quadword from memory addressed by `base+simm9` to 128-bit `Qt`.

`STUR Bt, [base,#simm9]`

Store (Unscaled) Register (byte): store byte from 8-bit `Bt` to memory addressed by `base+simm9`.

`STUR Ht, [base,#simm9]`

Store (Unscaled) Register (half): store halfword from 16-bit `Ht` to memory addressed by `base+simm9`.

`STUR St, [base,#simm9]`

Store (Unscaled) Register (single): store word from 32-bit `St` to memory addressed by `base+simm9`.

`STUR Dt, [base,#simm9]`

Store (Unscaled) Register (double): store doubleword from 64-bit `Dt` to memory addressed by `base+simm9`.

`STUR Qt, [base,#simm9]`

Store (Unscaled) Register (quad): store quadword from 128-bit `Qt` to memory addressed by `base+simm9`.

5.7.1.3 Load-Store FP/SIMD Pair

Addressing modes supported by `addr` (referring to §4.5):

- Base plus immediate offset (scaled 7-bit signed);
- Pre-indexed by immediate offset (scaled 7-bit signed);
- Post-indexed by immediate offset (scaled 7-bit signed).

If a Load Pair instruction specifies the same register for the two registers that are being loaded, then one of the following behaviours can occur:

- The instruction is UNALLOCATED
- The instruction is treated as a NOP
- The instruction performs all of the loads using the specified addressing mode and the register being loaded takes an UNKNOWN value

LDP St1, St2, addr

Load Pair (single): load two consecutive words from memory addressed by `addr` to 32-bit St1 and St2.

LDP Dt1, Dt2, addr

Load Pair (double): load two consecutive doublewords from memory addressed by `addr` to 64-bit Dt1 and Dt2.

LDP Qt1, Qt2, addr

Load Pair (quad): load two consecutive quadwords from memory addressed by `addr` to 128-bit Qt1 and Qt2.

STP St1, St2, addr

Store Pair (single): store two consecutive words from 32-bit St1 and St2 to memory addressed by `addr`.

STP Dt1, Dt2, addr

Store Pair (double): store two consecutive doublewords from 64-bit Dt1 and Dt2 to memory addressed by `addr`.

STP Qt1, Qt2, addr

Store Pair (quad): store two consecutive quadwords from 128-bit Qt1 and Qt2 to memory addressed by `addr`.

5.7.1.4 Load-Store FP/SIMD Non-Temporal Pair

Addressing modes supported (referring to §4.5):

- Base plus immediate offset (scaled 7-bit signed).

The load-store non-temporal pair instructions provide a hint to the memory system that the data being accessed is “non-temporal”, i.e. it is a “streaming” access to memory which is unlikely to be referenced again in the near future, and need not be retained in data caches. However depending on the memory type they may permit memory reads to be preloaded and memory writes to be gathered, in order to accelerate bulk memory transfers.

As a special exception to the normal memory ordering rules, where an address dependency exists between two memory reads and the second read was generated by a Load Non-temporal Pair instruction then, in the absence of any other barrier mechanism to achieve order, those memory accesses can be observed in any order by other observers within the shareability domain of the memory addresses being accessed.

If a Load Non-temporal Pair instruction specifies the same register for the two registers that are being loaded, then one of the following behaviours can occur:

- The instruction is UNALLOCATED
- The instruction is treated as a NOP
- The instruction performs all of the loads using the specified addressing mode and the register being loaded takes an UNKNOWN value

LDNP St1, St2, [base,#imm]

Load Non-temporal Pair (single): load two consecutive words from memory addressed by `base+imm` to 32-bit St1 and St2, with a non-temporal hint.

LDNP Dt1, Dt2, [base,#imm]

Load Non-temporal Pair (double): load two consecutive doublewords from memory addressed by base+imm to 64-bit Dt1 and Dt2, with a non-temporal hint.

LDNP Qt1, Qt2, [base,#imm]

Load Non-temporal Pair (quad): load two consecutive quadwords from memory addressed by base+imm to 128-bit Qt1 and Qt2, with a non-temporal hint.

STNP St1, St2, [base,#imm]

Store Non-temporal Pair (single): store two consecutive words from 32-bit St1 and St2 to memory addressed by base+imm, with a non-temporal hint.

STNP Dt1, Dt2, [base,#imm]

Store Non-temporal Pair (double): store two consecutive doublewords from 64-bit Dt1 and Dt2 to memory addressed by base+imm, with a non-temporal hint.

STNP Qt1, Qt2, [base,#imm]

Store Non-temporal Pair (quad): store two consecutive quadwords from 128-bit Qt1 and Qt2 to memory addressed by base+imm, with a non-temporal hint.

5.7.2 Floating-point Move (register)

Note that some of these instructions overlap functionality provided by Advanced SIMD instructions (DUP, INS, and UMOV) but these FMOV instructions should be preferred when operating on scalar floating-point data, so as to avoid the creation of scalar code that depends upon the availability of the Advanced SIMD instruction set.

FMOV Sd, Sn

Move 32 bits unchanged from Sn to Sd.

FMOV Dd, Dn

Move 64 bits unchanged from Dn to Dd.

FMOV Wd, Sn

Move 32 bits unchanged from Sn to Wd.

FMOV Sd, Wn

Move 32 bits unchanged from Wn to Sd.

FMOV Xd, Dn

Move 64 bits unchanged from Dn to Xd.

FMOV Dd, Xn

Move 64 bits unchanged from Xn to Dd.

FMOV Xd, Vn.D[1]

Move 64 bits unchanged from Vn<127:64> to Xd.

FMOV Vd.D[1], Xn

Move 64 bits unchanged from Xn to Vd<127:64>, leaving other bits in Vd unmodified.

5.7.3 Floating-point Move (immediate)

The floating point constant fp_{imm} may be specified either in decimal notation (e.g. “12.0” or “-1.2e1”), or as a string beginning “0x” followed by the hexadecimal representation of its IEEE754 encoding. A disassembler should prefer the decimal notation, so long as the value can be displayed precisely.

The floating point value must be expressible as $\pm n \cdot 16 \times 2^r$, where n and r are integers such that $16 \leq n \leq 31$ and $-3 \leq r \leq 4$, i.e. a normalized binary floating point encoding with 1 sign bit, 4 bits of fraction and a 3-bit exponent.

Note that this encoding does not include the constant 0.0. There are several instructions which could be used to store zero into an FP/SIMD register, however to provide consistency across a range of microarchitectures it is recommended that software use `FMOV Sd, WZR` or `FMOV Dd, XZR`. CPUs are encouraged to implement an `FMOV` from general register 31 with similar performance to a floating-point move (immediate) instruction.

`FMOV Sd, #fpimm`

Single-precision floating-point move immediate $Sd = fpimm$.

`FMOV Dd, #fpimm`

Double-precision floating-point move immediate $Dd = fpimm$.

5.7.4 Floating-point Convert

5.7.4.1 Convert Floating-point Precision

These instructions convert a floating-point scalar from one precision to a floating-point scalar with a different precision, using the FPCR rounding mode. Handling of non-finites and exceptional conditions is as VFPv4.

`FCVT Sd, Hn`

Convert from half-precision scalar in Hn to single-precision in Sd .

`FCVT Hd, Sn`

Convert from single-precision scalar in Sn to half-precision in Hd .

`FCVT Dd, Hn`

Convert from half-precision scalar in Hn to double-precision in Dd .

`FCVT Hd, Dn`

Convert from double-precision scalar in Dn to half-precision in Hd .

`FCVT Dd, Sn`

Convert from single-precision scalar in Sn to double-precision in Dd .

`FCVT Sd, Dn`

Convert from double-precision scalar in Dn to single-precision in Sd .

5.7.4.2 Convert to/from Integer

These instructions convert a floating-point scalar to or from a signed or unsigned integer in a general-purpose register. They will raise the Invalid Operation exception (`FPSR.IOC`) in response to a floating point input of NaN, Infinity, or a numerical value that cannot be represented within the destination register. An out of range integer result will also be saturated to the destination size. A numeric result which differs from the input will raise the Inexact exception (`FPSR.IXC`). When flush-to-zero mode is enabled a denormal input will be replaced by a zero and will raise the Input Denormal exception (`FPSR.IDC`).

The letter 'r' in these mnemonics selects the rounding mode as follows: N (to nearest, ties to even); A (to nearest, ties away from zero), P (towards +Inf); M (towards -Inf), Z (towards zero).

`FCVTrS Wd, Sn`

Convert single-precision scalar in Sn to signed 32-bit integer in Wd .

`FCVTrS Xd, Sn`

Convert single-precision scalar in Sn to signed 64-bit integer in Xd .

`FCVTrS Wd, Dn`

Convert double-precision scalar in Dn to signed 32-bit integer in Wd .

`FCVTrS Xd, Dn`

Convert double-precision scalar in Dn to signed 64-bit integer in Xd .

FCVTrU *Wd*, *Sn*

Convert single-precision scalar in *Sn* to unsigned 32-bit integer in *Wd*.

FCVTrU *Xd*, *Sn*

Convert single-precision scalar in *Sn* to unsigned 64-bit integer in *Xd*.

FCVTrU *Wd*, *Dn*

Convert double-precision scalar in *Dn* to unsigned 32-bit integer in *Wd*.

FCVTrU *Xd*, *Dn*

Convert double-precision scalar in *Dn* to unsigned 64-bit integer in *Xd*.

SCVTF *Sd*, *Wn*

Convert signed 32-bit integer in *Wn* to single-precision scalar in *Sd*, using FPCR rounding mode.

SCVTF *Sd*, *Xn*

Convert signed 64-bit integer in *Xn* to single-precision scalar in *Sd*, using FPCR rounding mode.

SCVTF *Dd*, *Wn*

Convert signed 32-bit integer in *Wn* to double-precision scalar in *Dd*, using FPCR rounding mode.

SCVTF *Dd*, *Xn*

Convert signed 64-bit integer in *Xn* to double-precision scalar in *Dd*, using FPCR rounding mode.

UCVTF *Sd*, *Wn*

Convert unsigned 32-bit integer in *Wn* to single-precision scalar in *Sd*, using FPCR rounding mode.

UCVTF *Sd*, *Xn*

Convert unsigned 64-bit integer in *Xn* to single-precision scalar in *Sd*, using FPCR rounding mode.

UCVTF *Dd*, *Wn*

Convert unsigned 32-bit integer in *Wn* to double-precision scalar in *Dd*, using FPCR rounding mode.

UCVTF *Dd*, *Xn*

Convert unsigned 64-bit integer in *Xn* to double-precision scalar in *Dd*, using FPCR rounding mode.

5.7.4.3 Convert to/from Fixed-point

These instructions convert a floating-point scalar to or from a signed or unsigned fixed-point value in a general-purpose register. The `#fbits` operand indicates that the general register holds a fixed-point number with `fbits` bits after the binary point, where `fbits` is in the range 1 to 32 for a 32-bit general register, or 1 to 64 for a 64-bit general register.

The instructions raise the Invalid Operation exception (`FPSR.IOC`) in response to a floating point input of NaN, Infinity, or a numerical value that cannot be represented within the destination register. An out of range fixed-point result will also be saturated to the destination size. A numeric result which differs from the input will raise the Inexact exception (`FPSR.IXC`). When flush-to-zero mode is enabled a denormal input will be replaced by a zero and will raise the Input Denormal exception (`FPSR.IDC`).

FCVTZS *Wd*, *Sn*, `#fbits`

Convert single-precision scalar in *Sn* to signed 32-bit fixed-point in *Wd*, rounding towards zero.

FCVTZS *Xd*, *Sn*, `#fbits`

Convert single-precision scalar in *Sn* to signed 64-bit fixed-point in *Xd*, rounding towards zero.

FCVTZS *Wd*, *Dn*, `#fbits`

Convert double-precision scalar in *Dn* to signed 32-bit fixed-point in *Wd*, rounding towards zero.

FCVTZS $X_d, D_n, \#fbits$

Convert double-precision scalar in D_n to signed 64-bit fixed-point in X_d , rounding towards zero.

FCVTZU $W_d, S_n, \#fbits$

Convert single-precision scalar in S_n to unsigned 32-bit fixed-point in W_d , rounding towards zero.

FCVTZU $X_d, S_n, \#fbits$

Convert single-precision scalar in S_n to unsigned 64-bit fixed-point in X_d , rounding towards zero.

FCVTZU $W_d, D_n, \#fbits$

Convert double-precision scalar in D_n to unsigned 32-bit fixed-point in W_d , rounding towards zero.

FCVTZU $X_d, D_n, \#fbits$

Convert double-precision scalar in D_n to unsigned 64-bit fixed-point in X_d , rounding towards zero.

SCVTF $S_d, W_n, \#fbits$

Convert signed 32-bit fixed-point in W_n to single-precision scalar in S_d , using FPCR rounding mode.

SCVTF $S_d, X_n, \#fbits$

Convert signed 64-bit fixed-point in X_n to single-precision scalar in S_d , using FPCR rounding mode.

SCVTF $D_d, W_n, \#fbits$

Convert signed 32-bit fixed-point in W_n to double-precision scalar in D_d , using FPCR rounding mode.

SCVTF $D_d, X_n, \#fbits$

Convert signed 64-bit fixed-point in X_n to double-precision scalar in D_d , using FPCR rounding mode.

UCVTF $S_d, W_n, \#fbits$

Convert unsigned 32-bit fixed-point in W_n to single-precision scalar in S_d , using FPCR rounding mode.

UCVTF $S_d, X_n, \#fbits$

Convert unsigned 64-bit fixed-point in X_n to single-precision scalar in S_d , using FPCR rounding mode.

UCVTF $D_d, W_n, \#fbits$

Convert unsigned 32-bit fixed-point in W_n to double-precision scalar in D_d , using FPCR rounding mode.

UCVTF $D_d, X_n, \#fbits$

Convert unsigned 64-bit fixed-point in X_n to double-precision scalar in D_d , using FPCR rounding mode.

5.7.5 Floating-point Round to Integral

The round to integral instructions round a floating-point value to an integral floating-point value of the same size. The only FPCR exception flags that can be raised by these instructions are: FPCR.IOC (Invalid Operation) for a Signaling NaN input; FPCR.IDC (Input Denormal) for a denormal input when flush-to-zero mode is enabled; for FRINTX only the FPCR.IXC (Inexact) exception if the result is numeric and does not have the same numerical value as the source. A zero input gives a zero result with the same sign, an infinite input gives an infinite result with the same sign, and a NaN is propagated as in normal arithmetic.

The letter 'r' in these mnemonics selects the rounding mode as follows: N (to nearest, ties to even); A (to nearest, ties away from zero), P (towards +Inf); M (towards -Inf), Z (towards zero), I (using FPCR rounding mode) and X (using FPCR rounding mode, with exactness check).

FRINT_r S_d, S_n

Single-precision floating-point scalar round to integral from S_n to S_d .

FRINT_r D_d, D_n

Double-precision floating-point scalar round to integral from D_n to D_d .

5.7.6 Floating-point Arithmetic (1 source)

FABS Sd, Sn

Single-precision floating-point scalar absolute value: $Sd = \text{abs}(Sn)$.

FABS Dd, Dn

Double-precision floating-point scalar absolute value: $Dd = \text{abs}(Dn)$.

FNEG Sd, Sn

Single-precision floating-point scalar negation: $Sd = -Sn$.

FNEG Dd, Dn

Double-precision floating-point scalar negation: $Dd = -Dn$.

FSQRT Sd, Sn

Single-precision floating-point scalar square root: $Sd = \text{sqrt}(Sn)$.

FSQRT Dd, Dn

Double-precision floating-point scalar square root: $Dd = \text{sqrt}(Dn)$.

5.7.7 Floating-point Arithmetic (2 source)

FADD Sd, Sn, Sm

Single-precision floating-point scalar addition: $Sd = Sn + Sm$.

FADD Dd, Dn, Dm

Double-precision floating-point scalar addition: $Dd = Dn + Dm$.

FDIV Sd, Sn, Sm

Single-precision floating-point scalar division: $Sd = Sn / Sm$.

FDIV Dd, Dn, Dm

Double-precision floating-point scalar division: $Dd = Dn / Dm$.

FMUL Sd, Sn, Sm

Single-precision floating-point scalar multiply: $Sd = Sn * Sm$.

FMUL Dd, Dn, Dm

Double-precision floating-point scalar multiply: $Dd = Dn * Dm$.

FNMUL Sd, Sn, Sm

Single-precision floating-point scalar multiply-negate: $Sd = -(Sn * Sm)$.

FNMUL Dd, Dn, Dm

Double-precision floating-point scalar multiply-negate: $Dd = -(Dn * Dm)$.

FSUB Sd, Sn, Sm

Single-precision floating-point scalar subtraction: $Sd = Sn - Sm$.

FSUB Dd, Dn, Dm

Double-precision floating-point scalar subtraction: $Dd = Dn - Dm$.

5.7.8 Floating-point Min/Max

The $\text{min}(x, y)$ and $\text{max}(x, y)$ operations behave similarly to the ARM v7 VMIN.F and VMAX.F instructions and return a quiet NaN when either x or y is a NaN. In flush-to-zero mode subnormal operands are flushed to zero before comparison, and if a flushed value is then the appropriate result the zero value is returned. Where both x and y are zero (or subnormal values flushed to zero) with differing sign, then +0.0 is returned by $\text{max}()$ and -0.0 by $\text{min}()$.

The $\text{minNum}(x, y)$ and $\text{maxNum}(x, y)$ operations follow the IEEE 754-2008 standard and return the numerical operand when one operand is numerical and the other a quiet NaN. Apart from this additional handling of a single quiet NaN the result is then identical to $\text{min}(x, y)$ and $\text{max}(x, y)$.

FMAX Sd, Sn, Sm

Single-precision floating-point scalar maximum: $Sd = \text{max}(Sn, Sm)$.

FMAX Dd, Dn, Dm

Double-precision floating-point scalar maximum: $Dd = \text{max}(Dn, Dm)$.

FMAXNM Sd, Sn, Sm

Single-precision floating-point scalar maximum number: $Sd = \text{maxNum}(Sn, Sm)$.

FMAXNM Dd, Dn, Dm

Double-precision floating-point scalar maximum number: $Dd = \text{maxNum}(Dn, Dm)$.

FMIN Sd, Sn, Sm

Single-precision floating-point scalar minimum: $Sd = \text{min}(Sn, Sm)$.

FMIN Dd, Dn, Dm

Double-precision floating-point scalar minimum: $Dd = \text{min}(Dn, Dm)$.

FMINNM Sd, Sn, Sm

Single-precision floating-point scalar minimum number: $Sd = \text{minNum}(Sn, Sm)$.

FMINNM Dd, Dn, Dm

Double-precision floating-point scalar minimum number: $Dd = \text{minNum}(Dn, Dm)$.

5.7.9 Floating-point Multiply-Add

FMADD Sd, Sn, Sm, Sa

Single-precision floating-point scalar fused multiply-add: $Sd = Sa + Sn * Sm$.

FMADD Dd, Dn, Dm, Da

Double-precision floating-point scalar fused multiply-add: $Dd = Da + Dn * Dm$.

FMSUB Sd, Sn, Sm, Sa

Single-precision floating-point scalar fused multiply-subtract: $Sd = Sa + (-Sn) * Sm$.

FMSUB Dd, Dn, Dm, Da

Double-precision floating-point scalar fused multiply-subtract: $Dd = Da + (-Dn) * Dm$.

FNMADD Sd, Sn, Sm, Sa

Single-precision floating-point scalar negated fused multiply-add: $Sd = (-Sa) + (-Sn) * Sm$.

FNMADD Dd, Dn, Dm, Da

Double-precision floating-point scalar negated fused multiply-add: $Dd = (-Da) + (-Dn) * Dm$.

FNMSUB Sd, Sn, Sm, Sa

Single-precision floating-point scalar negated fused multiply-subtract: $Sd = (-Sa) + Sn * Sm$.

FNMSUB Dd, Dn, Dm, Da

Double-precision floating-point scalar negated fused multiply-subtract: $Dd = (-Da) + Dn * Dm$.

5.7.10 Floating-point Comparison

These instructions set the integer NZCV condition flags directly, and do not alter the condition flags in the FPSR. In the conditional compare instructions, the `#uimm4` operand is a bitmask used to set the NZCV flags when the input condition is false, with bit 3 setting the N flag, bit 2 the Z flag, bit 1 the C flag, and bit 0 the V flag. If floating-point comparisons are *unordered* the C and V flag bits are set and the N and Z bits cleared.

FCMP Sn, Sm|#0.0

Single-precision compare: set condition flags from floating point comparison of Sn with Sm or 0.0.
Invalid Operation exception only on signaling NaNs.

FCMP Dn, Dm|#0.0

Double-precision compare: set condition flags from floating point comparison of Dn with Dm or 0.0.
Invalid Operation exception only on signaling NaNs.

FCMPE Sn, Sm|#0.0

Single-precision compare, exceptional: set flags from floating point comparison of Sn with Sm or 0.0.
Invalid Operation exception on all NaNs.

FCMPE Dn, Dm|#0.0

Double-precision compare, exceptional: set flags from floating point comparison of Dn with Dm or 0.0.
Invalid Operation exception on all NaNs.

FCCMP Sn, Sm, #uimm4, cond

Single-precision conditional compare: NZCV = if cond then FPCompare(Sn, Sm) else uimm4.
Invalid Operation exception only on signaling NaNs when cond holds true.

FCCMP Dn, Dm, #uimm4, cond

Double-precision conditional compare: NZCV = if cond then FPcompare(Dn, Dm) else uimm4.
Invalid Operation exception only on signaling NaNs when cond holds true.

FCCMPE Sn, Sm, #uimm4, cond

Single-precision conditional compare, exceptional:
NZCV = if cond then FPCompare(Sn, Sm) else uimm4.
Invalid Operation exception on all NaNs when cond holds true.

FCCMPE Dn, Dm, #uimm4, cond

Double-precision conditional compare, exceptional:
NZCV = if cond then FPCompare(Dn, Dm) else uimm4.
Invalid Operation exception on all NaNs when cond holds true.

5.7.11 Floating-point Conditional Select

FCSEL Sd, Sn, Sm, cond

Single-precision conditional select: Sd = if cond then Sn else Sm.

FCSEL Dd, Dn, Dm, cond

Double-precision conditional select: Dd = if cond then Dn else Dm.

5.8 Advanced SIMD

5.8.1 Overview

AArch64 Advanced SIMD is based upon the existing AArch32 Advanced SIMD extension, with the following changes:

- In AArch64 Advanced SIMD, there are thirty two 128-bit wide vector registers, whereas AArch32 Advanced SIMD had sixteen 128-bit wide registers.
- There are thirty two 64-bit vectors and these are held in the lower 64 bits of each 128-bit register.
- Writes of 64 bits or less to a vector register result in the higher bits being zeroed (except for lane inserts).
- New lane insert and extract instructions have been added to support the new register packing scheme.
- Additional widening instructions are provided for generating the top 64 bits of a 128-bit vector register.
- Data-processing instructions which would generate more than one result register (e.g. widening to a 256-bit vector), or consume more than three sources (e.g. narrowing to a 128-bit vector), have been split into separate instructions.
- A set of scalar instructions have been added to implement loop heads and tails, but only where the instruction does not already exist in the main scalar floating-point instruction set, and only when “over-computing” using a vector form might have the side effect of setting the saturation or floating point exception flags if there was “garbage” in unused higher lanes. Scalar operations on 64-bit integers are also provided in this section, to avoid the cost of over-computing using a 128-bit vector.
- A new set of vector “reduction” operations provide across-lane sum, minimum and maximum.
- Some existing instructions have been extended to support 64-bit integer values: e.g. comparison, addition, absolute value and negate, including saturating versions.
- Advanced SIMD now supports both single-precision (32-bit) and double-precision (64-bit) floating-point vector data types and arithmetic as defined by the IEEE 754 floating-point standard, honoring the FPCR Rounding Mode field, the Default NaN control, the Flush-to-Zero control, and (where supported by the implementation) the Exception trap enable bits.
- The ARMv7 SIMD “chained” floating-point multiply-accumulate instructions have been replaced with IEEE754 “fused” multiply-add. This includes the reciprocal step and reciprocal square root step instructions.
- Convert float to integer (`FCVTTxU`, `FCVTTxS`) encode a directed rounding mode: towards zero, towards +Inf, towards -Inf, to nearest with ties to even, and to nearest with ties away from zero.
- Round float to nearest integer in floating-point format (`FRINTx`) has been added, with the same directed rounding modes, as well as rounding according to the ambient rounding mode.
- A new double to single precision down-convert instruction with inexact “rounding to odd”, suitable for ongoing down-conversion to half-precision with correct rounding (`FCVTTxN`).
- IEEE 754-2008 `minNum()` and `maxNum()` instructions have been added (`FMINNM`, `FMAXNM`).
- Instructions to accelerate floating point vector normalisation have been added (`FRECPX`, `FMULX`).
- Saturating instructions have been extended to include unsigned accumulate into signed, and vice-versa.

5.8.2 Advanced SIMD Mnemonics

Although derived from the AArch32 Advanced SIMD syntax, a number of changes have been made to harmonise with the AArch64 core integer and scalar floating point instruction set syntax, and to unify AArch32's divergent "architectural" and "programmers" notations:

- The 'v' mnemonic prefix has been removed, and *S/U/F/P* added to indicate signed/unsigned/floating-point/polynomial data type. The mnemonic always indicates the data type(s) of the operation.
- The vector organisation (element size and number of lanes) is described by the register qualifiers and never by a mnemonic qualifier. See the description of the vector register syntax in §4.4.2 above.
- The 'P' prefix for "pairwise" operations becomes a suffix.
- A 'v' suffix has been added for the new reduction (across-all-lanes) operations
- A '2' suffix has been added for the new widening/narrowing "second part" instructions, described below.
- Vector compares now use the integer condition code names to indicate whether an integer comparison is signed or unsigned (e.g. *CMLT*, *CMLO*, *CMGE*, *CMHI*, etc)
- Some mnemonics have been renamed where the removal of the *v* prefix caused clash with the core instruction set mnemonics.

With the exception of the above changes, the mnemonics are based closely on AArch32 Advanced SIMD. As such, the learning curve for existing Advanced SIMD programmers is reduced. A full list of the equivalent AArch32 mnemonics can be found in §5.8.23 below.

Widening instructions with a '2' suffix implement the "second" or "top" part of a widening operation that would otherwise need to write two 128-bit vectors: they get their input data from the high numbered lanes of the 128-bit source vectors, and write the expanded results to the 128-bit destination.

Narrowing instructions with a '2' suffix implement the "second" or "top" part of a narrowing operation that would otherwise need to read two 128-bit vectors for each source operand: they get their input data from the 128-bit source operands and insert their narrowed results into the high numbered lanes of the 128-bit destination, leaving the lower lanes unchanged.

5.8.3 Data Movement

Note that some of these instructions overlap functionality provided by the scalar floating-point *FMOV* instructions described in section 5.7.2. These Advanced SIMD instructions should be preferred unless the register is known to contain a value that will only be operated upon by scalar floating-point instructions.

DUP *Vd.<Td>*, *Vn.<Ts>*[*index*]

Duplicate element (vector). Replicate single vector element from *Vn* to all elements of *Vd*. Where *<Td>/<Ts>* may be 8B/B, 16B/B, 4H/H, 8H/H, 2S/S, 4S/S or 2D/D. The immediate index is a value in the range 0 to (16/sizeof(*<Ts>*))-1.

DUP *Vd.<T>*, *Wn*

Duplicate 32-bit general register (vector). Replicate low order bits from 32-bit general register *Wn* to all elements of vector *Vd*. Where *<T>* may be 8B, 16B, 4H, 8H, 2S or 4S.

DUP *Vd.2D*, *Xn*

Duplicate 64-bit general register (vector). Replicate 64-bit general register *Xn* to both elements of vector *Vd*.

DUP *<V>d*, *Vn.<T>*[*index*]

Duplicate element (scalar). Copy single vector element from *Vn* to scalar register *<V>d*. Where *<V>/<T>* may be B/B, H/H, S/S or D/D. The immediate index is a value in the range 0 to (16/sizeof(*<T>*))-1. Normally disassembled as *MOV*.

INS Vd.<T>[index], Vn.<T>[index2]

Insert element (vector). Inserts a single vector element from Vn into a single element of Vd. Where <T> may be B, H, S or D. Both immediates index and index2 are values in the range 0 to (16/sizeof(<T>))-1. Normally disassembled as MOV.

INS Vd.<T>[index], Wn

Insert 32-bit general register (vector). Inserts low order bits from 32-bit general register Wn into a single vector element of Vd. Where <T> may be B, H or S. The immediate index is a value in the range 0 to (16/sizeof(<T>))-1. Normally disassembled as MOV.

INS Vd.D[index], Xn

Insert 64-bit general register (vector). Inserts 64-bit general register Xn into a single vector element of Vd. The immediate index is a value in the range 0 to 1. Normally disassembled as MOV.

MOV Vd.<T>[index], Vn.<T>[index2]

Move element. Moves a vector element from Vn to a vector element in Vd: alias for INS Vd.<T>[index],Vn.<T>[index2].

MOV Vd.<T>[index], Wn

Move 32-bit general register to element. Moves a 32-bit general register Wn to vector element in Vd: alias for INS Vd.<T>[index],Wn.

MOV Vd.2D[index], Xn

Move 64-bit general register to element. Moves a 64-bit general register Xn to a vector element in Vd: alias for INS Vd.D[index],Xn.

MOV <V>d, Vn.<T>[index]

Move element (scalar). Moves a vector element from Vn to scalar register <V>d: alias for DUP <V>d,Vn.<T>[index].

MOV <V>d, <V>n

Move (scalar). Moves a scalar register <V>n to scalar register <V>d: alias for DUP <V>d,Vn.<V>[0].

UMOV Wd, Vn.<T>[index]

Unsigned integer move element to 32-bit general register. Zero-extends an integer vector element from Vn into 32-bit general register Wd. Where <T> may be B, H or S. The index is in the range 0 to (16/sizeof(<T>))-1. Disassembled as MOV when <T> is S,

UMOV Xd, Vn.D[index]

Unsigned integer move element to 64-bit general register. Moves an unsigned 64-bit integer vector element from Vn into 64-bit general register Xd. The immediate index is in the range 0 to 1. Normally disassembled as MOV.

MOV Wd, Vn.S[index]

Move element to 32-bit general register. Moves a 32-bit vector element from Vn to 32-bit general register Wd: alias for UMOV Wd,Vn.S[index],

MOV Xd, Vn.D[index]

Move element to 64-bit general register. Moves a 64-bit vector element from Vn to 64-bit general register Xd: alias for UMOV Xd,Vn.D[index].

SMOV Wd, Vn.<T>[index]

Signed integer move element to 32-bit general register. Sign-extends an integer vector element from Vn into 32-bit general register Wd. Where <T> may be B or H. The index is a value is in the range 0 to (16/sizeof(<T>))-1.

SMOV Xd, Vn.<T>[index]

Signed integer move element to 64-bit general register. Sign-extends an integer vector element from Vn into 64-bit general register Xd. Where <T> may be B, H or S. The index is in the range 0 to (16/sizeof(<T>))-1.

5.8.4 Vector Arithmetic

UABA Vd.<T>, Vn.<T>, Vm.<T>

Unsigned integer absolute difference and accumulate (vector). Subtracts the elements of Vm from the corresponding elements of Vn, and accumulates the absolute values of the results into the elements of Vd. Operand and result elements are all unsigned integers of the same length: <T> is 8B, 16B, 4H, 8H, 2S or 4S.

SABA Vd.<T>, Vn.<T>, Vm.<T>

Signed integer absolute difference and accumulate (vector). Subtracts the elements of Vm from the corresponding elements of Vn, and accumulates the absolute values of the results into the elements of Vd. Operand and result elements are all signed integers of the same length: <T> is 8B, 16B, 4H, 8H, 2S or 4S.

UABD Vd.<T>, Vn.<T>, Vm.<T>

Unsigned integer absolute difference (vector). Subtracts the elements of Vm from the corresponding elements of Vn, and places the absolute values of the results in the elements of Vd. Operand and result elements are all integers of the same length: <T> is 8B, 16B, 4H, 8H, 2S or 4S.

SABD Vd.<T>, Vn.<T>, Vm.<T>

Signed integer absolute difference (vector). Subtracts the elements of Vm from the corresponding elements of Vn, and places the absolute values of the results in the elements of Vd. Operand and result elements are all integers of the same length: <T> is 8B, 16B, 4H, 8H, 2S or 4S.

FABD Vd.<T>, Vn.<T>, Vm.<T>

Floating-point absolute difference (vector). Subtracts the elements of Vm from the corresponding elements of Vn, and places the absolute values of the results in the elements of Vd. Operand and result elements are all of the same length: <T> is 2S, 4S or 2D.

ADD Vd.<T>, Vn.<T>, Vm.<T>

Integer add (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

FADD Vd.<T>, Vn.<T>, Vm.<T>

Floating-point add (vector). Where <T> is 2S, 4S or 2D.

AND Vd.<T>, Vn.<T>, Vm.<T>

Bitwise AND (vector). Where <T> is 8B or 16B (though an assembler should accept any valid format).

BIC Vd.<T>, Vn.<T>, Vm.<T>

Bitwise bit clear (vector). Where <T> is 8B or 16B (though an assembler should accept any valid format).

BIF Vd.<T>, Vn.<T>, Vm.<T>

Bitwise insert if false (vector). Where <T> is 8B or 16B (though an assembler should accept any valid format).

BIT Vd.<T>, Vn.<T>, Vm.<T>

Bitwise insert if true (vector). Where <T> is 8B or 16B (though an assembler should accept any valid format).

BSL Vd.<T>, Vn.<T>, Vm.<T>

Bitwise select (vector). Where <T> is 8B or 16B (though an assembler should accept any valid format).

CMEQ Vd.<T>, Vn.<T>, Vm.<T>

Integer compare mask equal (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

CMEQ Vd.<T>, Vn.<T>, #0

Integer compare mask equal to zero (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

CMHS Vd.<T>, Vn.<T>, Vm.<T>

Unsigned integer compare mask higher or same (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

-
- CMGE** Vd.<T>, Vn.<T>, Vm.<T>
Signed integer compare mask greater than or equal (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
- CMGE** Vd.<T>, Vn.<T>, #0
Signed integer compare mask greater than or equal to zero (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
- CMHI** Vd.<T>, Vn.<T>, Vm.<T>
Unsigned integer compare mask higher (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
- CMGT** Vd.<T>, Vn.<T>, Vm.<T>
Signed integer compare mask greater than (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
- CMGT** Vd.<T>, Vn.<T>, #0
Signed integer compare mask greater than zero (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
- CMLS** Vd.<T>, Vn.<T>, Vm.<T>
Unsigned integer compare mask lower or same (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
Alias for CMHS with operands reversed.
- CMLE** Vd.<T>, Vn.<T>, Vm.<T>
Signed integer compare mask less than or equal (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
Alias for CMGE with operands reversed.
- CMLE** Vd.<T>, Vn.<T>, #0
Signed integer compare mask less than or equal to zero (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
- CMLO** Vd.<T>, Vn.<T>, Vm.<T>
Unsigned integer compare mask lower (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
Alias for CMHI with operands reversed.
- CMLT** Vd.<T>, Vn.<T>, Vm.<T>
Signed integer compare mask less than (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
Alias for CMGT with operands reversed.
- CMLT** Vd.<T>, Vn.<T>, #0
Signed integer compare mask less than zero (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
- CMTST** Vd.<T>, Vn.<T>, Vm.<T>
Integer compare mask bitwise test (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.
- FCMEQ** Vd.<T>, Vn.<T>, Vm.<T>
Floating-point compare mask equal (vector). Where <T> is 2S, 4S or 2D.
- FCMEQ** Vd.<T>, Vn.<T>, #0
Floating-point compare mask equal to zero (vector). Where <T> is 2S, 4S or 2D.
- FCMGE** Vd.<T>, Vn.<T>, Vm.<T>
Floating-point compare mask greater than or equal (vector). Where <T> is 2S, 4S or 2D.
- FCMGE** Vd.<T>, Vn.<T>, #0
Floating-point compare mask greater than or equal to zero (vector). Where <T> is 2S, 4S or 2D.
- FCMGT** Vd.<T>, Vn.<T>, Vm.<T>
Floating-point compare mask greater than (vector). Where <T> is 2S, 4S or 2D.
- FCMGT** Vd.<T>, Vn.<T>, #0
Floating-point compare mask greater than zero (vector). Where <T> is 2S, 4S or 2D.
-

| | | |
|--------|------------------------|---|
| FCMLE | Vd.<T>, Vn.<T>, Vm.<T> | Floating-point compare mask less than or equal (vector). Where <T> is 2S, 4S or 2D. Alias for FCMGE with operands reversed. |
| FCMLE | Vd.<T>, Vn.<T>, #0 | Floating-point compare mask less than or equal to zero (vector). Where <T> is 2S, 4S or 2D. |
| FCMLT | Vd.<T>, Vn.<T>, Vm.<T> | Floating-point compare mask less than (vector). Where <T> is 2S, 4S or 2D. Alias for FCMGT with operands reversed. |
| FCMLT | Vd.<T>, Vn.<T>, #0 | Floating-point compare mask less than zero (vector). Where <T> is 2S, 4S or 2D. |
| FACGE | Vd.<T>, Vn.<T>, Vm.<T> | Floating-point absolute compare mask greater than or equal (vector). Where <T> is 2S, 4S or 2D. |
| FACGT | Vd.<T>, Vn.<T>, Vm.<T> | Floating-point absolute compare mask greater than (vector). Where <T> is 2S, 4S or 2D. |
| FACLE | Vd.<T>, Vn.<T>, Vm.<T> | Floating-point absolute compare mask less than or equal (vector). Where <T> is 2S, 4S or 2D. Alias for FACGE with operands reversed. |
| FACLT | Vd.<T>, Vn.<T>, Vm.<T> | Floating-point absolute compare mask less than (vector). Where <T> is 2S, 4S or 2D. Alias for FACGT with operands reversed. |
| FDIV | Vd.<T>, Vn.<T>, Vm.<T> | Floating-point divide (vector). Where <T> is 2S, 4S or 2D. |
| EOR | Vd.<T>, Vn.<T>, Vm.<T> | Bitwise exclusive OR (vector). Where <T> is 8B or 16B (an assembler should accept any valid arrangement). |
| UHADD | Vd.<T>, Vn.<T>, Vm.<T> | Unsigned integer halving add (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| SHADD | Vd.<T>, Vn.<T>, Vm.<T> | Signed integer halving add (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| UHSUB | Vd.<T>, Vn.<T>, Vm.<T> | Unsigned integer halving subtract (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| SHSUB | Vd.<T>, Vn.<T>, Vm.<T> | Signed integer halving subtract (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| UMAX | Vd.<T>, Vn.<T>, Vm.<T> | Unsigned integer maximum (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| SMAX | Vd.<T>, Vn.<T>, Vm.<T> | Signed integer maximum (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| FMAX | Vd.<T>, Vn.<T>, Vm.<T> | Floating-point maximum (vector). Where <T> is 2S, 4S or 2D. |
| FMAXNM | Vd.<T>, Vn.<T>, Vm.<T> | Floating-point maxNum (vector). Where <T> is 2S, 4S or 2D. |
| UMIN | Vd.<T>, Vn.<T>, Vm.<T> | Unsigned integer minimum (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |

| | |
|---------------------------------|---|
| SMIN Vd.<T>, Vn.<T>, Vm.<T> | Signed integer minimum (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| FMIN Vd.<T>, Vn.<T>, Vm.<T> | Floating-point minimum (vector). Where <T> is 2S, 4S or 2D. |
| FMINNM Vd.<T>, Vn.<T>, Vm.<T> | Floating-point minNum (vector). Where <T> is 2S, 4S or 2D. |
| MLA Vd.<T>, Vn.<T>, Vm.<T> | Integer multiply-accumulate (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| FMLA Vd.<T>, Vn.<T>, Vm.<T> | Floating-point fused multiply-accumulate (vector). Where <T> is 2S, 4S or 2D. |
| MLS Vd.<T>, Vn.<T>, Vm.<T> | Integer multiply-subtract from accumulator (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| FMLS Vd.<T>, Vn.<T>, Vm.<T> | Floating-point fused multiply-subtract from accumulator (vector). Where <T> is 2S, 4S or 2D. |
| MUL Vd.<T>, Vn.<T>, Vm.<T> | Integer multiply (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S. |
| FMUL Vd.<T>, Vn.<T>, Vm.<T> | Floating-point multiply (vector). Where <T> is 2S, 4S or 2D. |
| FMULX Vd.<T>, Vn.<T>, Vm.<T> | Floating-point multiply extended, like FMUL but $0 \times \pm\infty \rightarrow \pm 2$ (vector). Where <T> is 2S, 4S or 2D. |
| PMUL Vd.<T>, Vn.<T>, Vm.<T> | Polynomial multiply (vector). Where <T> is 8B or 16B. |
| ORN Vd.<T>, Vn.<T>, Vm.<T> | Bitwise OR NOT (vector). Where <T> is 8B or 16B (an assembler should accept any valid arrangement). |
| ORR Vd.<T>, Vn.<T>, Vm.<T> | Bitwise OR (vector). Where <T> is 8B or 16B (an assembler should accept any valid arrangement). Will be disassembled as MOV if Vn and Vm specify the same register. |
| MOV Vd.<T>, Vn.<T> | Move (vector). An alias for ORR Vd.<T>, Vn.<T>, Vn.<T> where <T> is 8B or 16B (an assembler should accept any valid arrangement). |
| SQADD Vd.<T>, Vn.<T>, Vm.<T> | Signed integer saturating add (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D. |
| UQADD Vd.<T>, Vn.<T>, Vm.<T> | Unsigned integer saturating add (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D. |
| SQDMULH Vd.<T>, Vn.<T>, Vm.<T> | Signed integer saturating doubling multiply high half (vector). Where <T> is 4H, 8H, 2S or 4S. |
| SQRDMULH Vd.<T>, Vn.<T>, Vm.<T> | Signed integer saturating rounding doubling multiply high half (vector). Where <T> is 4H, 8H, 2S or 4S. |
| UQRSHL Vd.<T>, Vn.<T>, Vm.<T> | Unsigned integer saturating rounding shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D. |
| SQRSHL Vd.<T>, Vn.<T>, Vm.<T> | Signed integer saturating rounding shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D. |

UQSUB Vd.<T>, Vn.<T>, Vm.<T>
 Unsigned integer saturating subtract (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

SQSUB Vd.<T>, Vn.<T>, Vm.<T>
 Signed integer saturating subtract (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

URHADD Vd.<T>, Vn.<T>, Vm.<T>
 Unsigned integer rounding halving add (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S.

SRHADD Vd.<T>, Vn.<T>, Vm.<T>
 Signed integer rounding halving add (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S.

URSHL Vd.<T>, Vn.<T>, Vm.<T>
 Unsigned integer rounding shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

SRSHL Vd.<T>, Vn.<T>, Vm.<T>
 Signed integer rounding shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

UQSHL Vd.<T>, Vn.<T>, Vm.<T>
 Unsigned integer saturating shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

SQSHL Vd.<T>, Vn.<T>, Vm.<T>
 Signed integer saturating shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

USHL Vd.<T>, Vn.<T>, Vm.<T>
 Unsigned integer shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

SSHL Vd.<T>, Vn.<T>, Vm.<T>
 Signed integer shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

SUB Vd.<T>, Vn.<T>, Vm.<T>
 Integer subtract (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D

FSUB Vd.<T>, Vn.<T>, Vm.<T>
 Floating-point subtract (vector). Where <T> is 2S, 4S or 2D.

FRECPS Vd.<T>, Vn.<T>, Vm.<T>
 Floating-point reciprocal step (vector). Where <T> is 2S, 4S or 2D. The embedded multiply-accumulate is fused in AArch64 `FRECPS`, whilst in AArch32 `VRECPS` it remains chained.

FRSQRTS Vd.<T>, Vn.<T>, Vm.<T>
 Floating-point reciprocal square root step (vector). Where <T> is 2S, 4S or 2D. The embedded multiply-accumulate is fused in AArch64 `FRSQRTS`, whilst in AArch32 `VRSQRTS` it remains chained.

5.8.5 Scalar Arithmetic

FABD <V>d, <V>n, <V>m
 Floating-point absolute difference (scalar). Subtracts <V>m from <V>n, and places the absolute value of the result in <V>d. Where <V> is S or D.

ADD Dd, Dn, Dm
 Integer add (scalar).

CMEQ Dd, Dn, Dm
 Integer compare mask equal (scalar).

CMEQ Dd, Dn, #0
 Integer compare mask equal to zero (scalar).

| | | |
|-------|------------------|--|
| CMHS | Dd, Dn, Dm | Unsigned integer compare mask higher or same (scalar). |
| CMGE | Dd, Dn, Dm | Signed integer compare mask greater than or equal (scalar). |
| CMGE | Dd, Dn, #0 | Signed integer compare mask greater than or equal to zero (scalar). |
| CMHI | Dd, Dn, Dm | Unsigned integer compare mask higher (scalar). |
| CMGT | Dd, Dn, Dm | Signed integer compare mask greater than (scalar). |
| CMGT | Dd, Dn, #0 | Signed integer compare mask greater than zero (scalar). |
| CMLS | Dd, Dn, Dm | Unsigned integer compare mask lower or same (scalar). Alias for CMHS with operands reversed. |
| CMLE | Dd, Dn, Dm | Signed integer compare mask less than or equal (scalar). Alias for CMGE with operands reversed. |
| CMLE | Dd, Dn, #0 | Signed integer compare mask less than or equal to zero (scalar). |
| CMLO | Dd, Dn, Dm | Unsigned integer compare mask lower (scalar). Alias for CMHI with operands reversed. |
| CMLT | Dd, Dn, Dm | Signed integer compare mask less than (scalar). Alias for CMGT with operands reversed. |
| CMLT | Dd, Dn, #0 | Signed integer compare mask less than zero (scalar). |
| CMTST | Dd, Dn, Dm | Integer compare mask bitwise test (scalar). |
| FCMEQ | <V>d, <V>n, <V>m | Floating-point compare mask equal (scalar). Where <V>is S or D. |
| FCMEQ | <V>d, <V>n, #0 | Floating-point compare mask equal to zero (scalar). Where <V>is S or D. |
| FCMGE | <V>d, <V>n, <V>m | Floating-point compare mask greater than or equal (scalar). Where <V>is S or D. |
| FCMGE | <V>d, <V>n, #0 | Floating-point compare mask greater than or equal to zero (scalar). Where <V>is S or D. |
| FCMGT | <V>d, <V>n, <V>m | Floating-point compare mask greater than (scalar). Where <V>is S or D. |
| FCMGT | <V>d, <V>n, #0 | Floating-point compare mask greater than zero (scalar). Where <V>is S or D. |

| | | |
|----------|------------------|--|
| FCMLE | <V>d, <V>n, <V>m | Floating-point compare mask less than or equal (scalar). Where <V>is S or D. Alias for FCMGE with operands reversed. |
| FCMLE | <V>d, <V>n, #0 | Floating-point compare mask less than or equal to zero (scalar). Where <V>is S or D. |
| FCMLT | <V>d, <V>n, <V>m | Floating-point compare mask less than (scalar). Where <V>is S or D. Alias for FCMGT with operands reversed. |
| FCMLT | <V>d, <V>n, #0 | Floating-point compare mask less than zero (scalar). Where <V>is S or D. |
| FACGE | <V>d, <V>n, <V>m | Floating-point absolute compare mask greater than or equal (scalar). Where <V>is S or D. |
| FACGT | <V>d, <V>n, <V>m | Floating-point absolute compare mask greater than (scalar). Where <V>is S or D. |
| FACLE | <V>d, <V>n, <V>m | Floating-point absolute compare mask less than or equal (scalar). Where <V>is S or D. Alias for FACGE with operands reversed. |
| FACLT | <V>d, <V>n, <V>m | Floating-point absolute compare mask less than (scalar). Where <V>is S or D. Alias for FACGT with operands reversed. |
| SQADD | <V>d, <V>n, <V>m | Signed integer saturating add (scalar). Where <V> is B, H, S or D. |
| UQADD | <V>d, <V>n, <V>m | Unsigned integer saturating add (scalar). Where <V> is B, H, S or D. |
| SQDMULH | <V>d, <V>n, <V>m | Signed integer saturating doubling multiply high half (scalar). Where <V> is H or S. |
| SQRDMULH | <V>d, <V>n, <V>m | Signed integer saturating rounding doubling multiply high half (scalar). Where <V> is H or S. |
| UQRSHL | <V>d, <V>n, <V>m | Unsigned integer saturating rounding shift left (scalar). Where <V> is B, H, S or D. |
| SQRSHL | <V>d, <V>n, <V>m | Signed integer saturating rounding shift left (scalar). Where <V> is B, H, S or D. |
| UQSUB | <V>d, <V>n, <V>m | Unsigned integer saturating subtract (scalar). Where <V> is B, H, S or D. |
| SQSUB | <V>d, <V>n, <V>m | Signed integer saturating subtract (scalar). Where <V> is B, H, S or D. |
| UQSHL | <V>d, <V>n, <V>m | Unsigned integer saturating shift left (scalar). Where <V> is B, H, S or D. |
| SQSHL | <V>d, <V>n, <V>m | Signed integer saturating shift left (scalar). Where <V> is B, H, S or D. |
| URSHL | Dd, Dn, Dm | Unsigned integer rounding shift left (scalar). |

SRSHL Dd, Dn, Dm

Signed integer rounding shift left (scalar).

USHL Dd, Dn, Dm

Unsigned integer shift left (scalar).

SSHL Dd, Dn, Dm

Signed integer shift left (scalar).

SUB Dd, Dn, Dm

Integer subtract (scalar).

FMULX <V>d, <V>n, <V>m

Floating-point multiply extended, like FMUL but $0 \times \pm\infty \rightarrow \pm 2$ (scalar). Where <V> is S or D.

FRECPS <V>d, <V>n, <V>m

Floating-point reciprocal step (scalar). Where <V> is S or D. The embedded multiply-accumulate is fused in AArch64 FRECPS, whilst in AArch32 VRECPS it remains chained.

FRSQRTS <V>d, <V>n, <V>m

Floating-point reciprocal square root step (scalar). Where <V> is S or D. The embedded multiply-accumulate is fused in AArch64 FRSQRTS, whilst in AArch32 VRSQRTS it remains chained.

5.8.6 Vector Widening/Narrowing Arithmetic

UABAL Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Unsigned integer absolute difference and accumulate long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S.

UABAL2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Unsigned integer absolute difference and accumulate long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S.

SABAL Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer absolute difference and accumulate long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S.

SABAL2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer absolute difference and accumulate long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S.

UABDL Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Unsigned integer absolute difference long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S.

UABDL2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Unsigned integer absolute difference long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S.

SABDL Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer absolute difference long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S.

SABDL2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer absolute difference long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S.

UADDL Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Unsigned integer add long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S.

UADDL2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Unsigned integer add long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S.

| | | |
|--------|---------------------------|--|
| SADDL | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer add long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S. |
| SADDL2 | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer add long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S. |
| USUBL | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Unsigned integer subtract long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S. |
| USUBL2 | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Unsigned integer subtract long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S. |
| SSUBL | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer subtract long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S. |
| SSUBL2 | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer subtract long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S. |
| UMLAL | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Unsigned integer multiply-accumulate long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S. |
| UMLAL2 | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Unsigned integer multiply-accumulate long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S. |
| SMLAL | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer multiply-accumulate long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S. |
| SMLAL2 | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer multiply-accumulate long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S. |
| UMLSL | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Unsigned integer multiply-subtract from accumulator long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S. |
| UMLSL2 | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Unsigned integer multiply-subtract from accumulator long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S. |
| SMLSL | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer multiply-subtract from accumulator long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S. |
| SMLSL2 | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer multiply-subtract from accumulator long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S. |
| UMULL | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Unsigned integer multiply long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S. |
| UMULL2 | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Unsigned integer multiply long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S. |
| SMULL | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer multiply long (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S. |
| SMULL2 | Vd.<Td>, Vn.<Ts>, Vm.<Ts> | Signed integer multiply long (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S. |

PMULL Vd.8H, Vn.8B, Vm.8B

Polynomial multiply long (vector).

PMULL2 Vd.8H, Vn.16B, Vm.16B

Polynomial multiply long (vector, second part).

SQDMLAL Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer saturating doubling multiply accumulate long (vector). Where the <Td>/<Ts> is 4S/4H or 2D/2S.

SQDMLAL2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer saturating doubling multiply accumulate long (vector, second part). Where the <Td>/<Ts> is 4S/8H or 2D/4S.

SQDMLSL Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer saturating doubling multiply subtract from accumulator long (vector). Where the <Td>/<Ts> is 4S/4H or 2D/2S.

SQDMLSL2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer saturating doubling multiply subtract from accumulator long (vector, second part). Where the <Td>/<Ts> is 4S/8H or 2D/4S.

SQDMULL Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer saturating doubling multiply long (vector). Where the <Td>/<Ts> is 4S/4H or 2D/2S.

SQDMULL2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Signed integer saturating doubling multiply long (vector, second part). Where the <Td>/<Ts> is 4S/8H or 2D/4S.

UADDW Vd.<Td>, Vn.<Td>, Vm.<Ts>

Unsigned integer add wide (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S.

UADDW2 Vd.<Td>, Vn.<Td>, Vm.<Ts>

Unsigned integer add wide (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S.

SADDW Vd.<Td>, Vn.<Td>, Vm.<Ts>

Signed integer add wide (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S.

SADDW2 Vd.<Td>, Vn.<Td>, Vm.<Ts>

Signed integer add wide (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S.

USUBW Vd.<Td>, Vn.<Td>, Vm.<Ts>

Unsigned integer subtract wide (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S.

USUBW2 Vd.<Td>, Vn.<Td>, Vm.<Ts>

Unsigned integer subtract wide (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S.

SSUBW Vd.<Td>, Vn.<Td>, Vm.<Ts>

Signed integer subtract wide (vector). Where the <Td>/<Ts> is 8H/8B, 4S/4H or 2D/2S.

SSUBW2 Vd.<Td>, Vn.<Td>, Vm.<Ts>

Signed integer subtract wide (vector, second part). Where the <Td>/<Ts> is 8H/16B, 4S/8H or 2D/4S.

RADDHN Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Integer rounding add and narrow high half (vector). Where the <Td>/<Ts> is 8B/8H, 4H/4S or 2S/2D.

RADDHN2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Integer rounding add and narrow high half (vector, second part). Where the <Td>/<Ts> is 16B/8H, 8H/4S or 4S/2D.

RSUBHN Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Integer rounding subtract and narrow high half (vector). Where the <Td>/<Ts> is 8B/8H, 4H/4S or 2S/2D.

RSUBHN2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Integer rounding subtract and narrow high half (vector, second part). Where the <Td>/<Ts> is 16B/8H, 8H/4S or 4S/2D.

ADDHN Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Integer add and narrow high half (vector). Where the <Td>/<Ts> is 8B/8H, 4H/4S or 2S/2D.

ADDHN2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Integer add and narrow high half (vector, second part). Where the <Td>/<Ts> is 16B/8H, 8H/4S or 4S/2D.

SUBHN Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Integer subtract and narrow high half (vector). Where the <Td>/<Ts> is 8B/8H, 4H/4S or 2S/2D.

SUBHN2 Vd.<Td>, Vn.<Ts>, Vm.<Ts>

Integer subtract and narrow high half (vector, second part). Where the <Td>/<Ts> is 16B/8H, 8H/4S or 4S/2D.

5.8.7 Scalar Widening/Narrowing Arithmetic

SQDMLAL <Vd>d, <Vs>n, <Vs>m

Signed integer saturating doubling multiply accumulate long (scalar). Where the <Vd>/<Vs> is S/H or D/S.

SQDMLSL <Vd>d, <Vs>n, <Vs>m

Signed integer saturating doubling multiply subtract from accumulator long (scalar). Where the <Vd>/<Vs> is S/H or D/S.

SQDMLL <Vd>d, <Vs>n, <Vs>m

Signed integer saturating doubling multiply long (scalar). Where the <Vd>/<Vs> is S/H or D/S.

5.8.8 Vector Unary Arithmetic

ABS Vd.<T>, Vn.<T>

Integer absolute value (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

SQABS Vd.<T>, Vn.<T>

Signed integer saturating absolute (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

FABS Vd.<T>, Vn.<T>

Floating-point absolute value (vector). Where <T> is 2S, 4S or 2D.

NEG Vd.<T>, Vn.<T>

Integer negate (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

SQNEG Vd.<T>, Vn.<T>

Signed integer saturating negate (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

FNEG Vd.<T>, Vn.<T>

Floating-point negate (vector). Where <T> is 2S, 4S or 2D.

CLS Vd.<T>, Vn.<T>

Signed integer count leading sign bits (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S.

CLZ Vd.<T>, Vn.<T>

Integer count leading zero bits (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S.

CNT Vd.<T>, Vn.<T>

Count non-zero bits (vector). Where <T> is 8B or 16B.

NOT Vd.<T>, Vn.<T>

Bitwise invert (vector). Where <T> is 8B or 16B (an assembler should accept any valid arrangement).
Normally disassembled as MVN.

MVN Vd.<T>, Vn.<T>

Bitwise invert (vector). Where <T> is 8B or 16B (an assembler should accept any valid arrangement).
Alias for NOT Vd.<T>, Vn.<T>

SUQADD Vd.<T>, Vn.<T>

Signed integer saturating accumulate of unsigned value (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

USQADD Vd.<T>, Vn.<T>

Unsigned integer saturating accumulate of signed value (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

UADALP Vd.<Td>, Vn.<Ts>

Unsigned integer add and accumulate long pairwise (vector). Where <Td>/<Ts> is 4H/8B, 8H/16B, 2S/4H, 4S/8H, 1D/2S or 2D/4S.

SADALP Vd.<Td>, Vn.<Ts>

Signed integer add and accumulate long pairwise (vector). Where <Td>/<Ts> is 4H/8B, 8H/16B, 2S/4H, 4S/8H, 1D/2S or 2D/4S.

UADDLP Vd.<Td>, Vn.<Ts>

Unsigned integer add long pair (vector). Where <Td>/<Ts> is 4H/8B, 8H/16B, 2S/4H, 4S/8H, 1D/2S or 2D/4S.

SADDLP Vd.<Td>, Vn.<Ts>

Signed integer add long pair (vector). Where <Td>/<Ts> is 4H/8B, 8H/16B, 2S/4H, 4S/8H, 1D/2S or 2D/4S.

FCVTL Vd.<Td>, Vn.<Ts>

Floating-point convert long half-precision to single-precision, or single-precision to double-precision (vector). Where <Td>/<Ts> is 4S/4H or 2D/2S

FCVTL2 Vd.<Td>, Vn.<Ts>

Floating-point convert long half-precision to single-precision, or single-precision to double-precision (vector, second part). Where <Td>/<Ts> is 4S/8H or 2D/4S

XTN Vd.<Td>, Vn.<Ts>

Integer narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D.

XTN2 Vd.<Td>, Vn.<Ts>

Integer narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D.

SQXTUN Vd.<Td>, Vn.<Ts>

Signed integer saturating and unsigned narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D.

SQXTUN2 Vd.<Td>, Vn.<Ts>

Signed integer saturating and unsigned narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D.

UQXTN Vd.<Td>, Vn.<Ts>

Unsigned integer saturating narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D.

UQXTN2 Vd.<Td>, Vn.<Ts>

Unsigned integer saturating narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D.

SQXTN Vd.<Td>, Vn.<Ts>

Signed integer saturating narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D.

SQXTN2 Vd.<Td>, Vn.<Ts>

Signed integer saturating narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D.

FCVTN Vd.<Td>, Vn.<Ts>

Floating-point convert narrow single-precision to half-precision, or double-precision to single-precision using FPCR rounding mode (vector). Where <Td>/<Ts> is 4H/4S or 2S/2D.

FCVTN2 Vd.<Td>, Vn.<Ts>

Floating-point convert narrow single-precision to half-precision, or double-precision to single-precision using FPCR rounding mode (vector, second part). Where <Td>/<Ts> is 8H/4S or 4S/2D.

FCVTXN Vd.2S, Vn.2D

Floating-point convert narrow double-precision to single-precision with inexact result rounding to odd (vector). Rounding to odd, or *Von Neumann's* rounding, is only suitable for further narrowing to half-precision giving correct rounding of the half-precision result.

FCVTXN2 Vd.4S, Vn.2D

Floating-point convert narrow double-precision to single-precision with inexact result rounding to odd (vector, second part). Rounding to odd, or *Von Neumann's* rounding, is only suitable for further narrowing to half-precision giving correct rounding of the half-precision result.

FRINTx Vd.<T>, Vn.<T>

Floating-point round to integral (vector). Where <T> is 2S, 4S or 2D. The letter x selects the rounding mode: N (nearest, ties to even); A (nearest, ties away from zero), P (towards +Inf); M (towards -Inf), Z (towards zero), I (using FPCR rounding mode) and X (using FPCR rounding mode, with exactness test).

FSQRT Vd.<T>, Vn.<T>

Floating-point square root (vector). Where <T> is 2S, 4S or 2D.

URECPE Vd.<T>, Vn.<T>

Unsigned integer reciprocal estimate (vector). Where <T> is 2S or 4S.

FRECPE Vd.<T>, Vn.<T>

Floating-point reciprocal estimate (vector). Where <T> is 2S, 4S or 2D.

URSQRTE Vd.<T>, Vn.<T>

Unsigned integer reciprocal square root estimate (vector). Where <T> is 2S or 4S.

FRSQRTE Vd.<T>, Vn.<T>

Floating-point reciprocal square root estimate (vector). Where <T> is 2S, 4S or 2D.

RBIT Vd.<T>, Vn.<T>

Bit reverse (vector): reverses the bits within each byte vector element. Where <T> is 8B or 16B.

REV16 Vd.<T>, Vn.<T>

Element reverse in 16-bit halfwords (vector). Where <T> is 8B or 16B.

REV32 Vd.<T>, Vn.<T>

Element reverse in 32-bit words (vector). Where <T> is 8B, 16B, 4H, or 8H.

REV64 Vd.<T>, Vn.<T>

Element reverse in 64-bit doublewords (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S.

5.8.9 Scalar Unary Arithmetic

ABS Dd, Dn

Signed 64-bit integer absolute (scalar).

SQABS <V>d, <V>n

Signed integer saturating absolute (scalar). Where <V> is B, H, S or D.

NEG Dd, Dn

Signed 64-bit integer negate (scalar).

SQNEG <V>d, <V>n

Signed integer saturating negate (scalar). Where <V> is B, H, S or D.

SUQADD <V>d, <V>n

Signed integer saturating accumulate of unsigned value (scalar). Where <V> is B, H, S or D.

USQADD <V>d, <V>n

Unsigned integer saturating accumulate of signed value Where <V> is B, H, S or D.

SQXTUN <Vd>d, <Vs>n

Signed integer saturating and unsigned narrow (scalar). Where <Vd>/<Vs> is B/H, H/S or S/D.

UQXTN <Vd>d, <Vs>n

Unsigned integer saturating narrow (scalar). Where <Vd>/<Vs> is B/H, H/S or S/D.

SQXTN <Vd>d, <Vs>n

Signed integer saturating narrow (scalar). Where <Vd>/<Vs> is B/H, H/S or S/D.

FCVTXN Sd, Dn

Floating-point convert narrow double-precision to single-precision with inexact result rounding to odd (scalar). Rounding to odd, or *Von Neumann's* rounding, is only suitable for further narrowing to half-precision giving correct rounding of the half-precision result.

FRECPE <V>d, <V>n

Floating-point reciprocal estimate (scalar). Where <V> is S or D.

FRECPX <V>d, <V>n

Floating-point reciprocal exponent (scalar). Where <V> is S or D.

FRSQRTE <V>d, <V>n

Floating-point reciprocal square root estimate (scalar). Where <V> is S or D.

5.8.10 Vector-by-element Arithmetic

In all cases the immediate `index` is a constant in the range 0 to $(16/\text{sizeof}(\langle Ts \rangle)) - 1$.

FMLA Vd.<T>, Vn.<T>, Vm.<Ts>[`index`]

Floating-point fused multiply add (vector, by element). Where <T>/<Ts> is 2S/S, 4S/S or 2D/D.

FMLS Vd.<T>, Vn.<T>, Vm.<Ts>[`index`]

Floating-point fused multiply subtract (vector, by element). Where <T>/<Ts> is 2S/S, 4S/S or 2D/D.

FMUL Vd.<T>, Vn.<T>, Vm.<Ts>[`index`]

Floating-point multiply (vector, by element). Where <Td>/<Ts> is 2S/S 4S/S or 2D/D.

FMULX Vd.<T>, Vn.<T>, Vm.<Ts>[`index`]

Floating-point multiply extended (vector, by element): like FMUL but $0 \times \pm\infty \rightarrow \pm 2$. Where <Td>/<Ts> is 2S/S, 4S/S or 2D/D.

MLA Vd.<T>, Vn.<T>, Vm.<Ts>[`index`]

Integer multiply accumulate (vector, by element). Where <T>/<Ts> is 4H/H, 8H/H, 2S/S or 4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

MLS Vd.<T>, Vn.<T>, Vm.<Ts>[`index`]

Integer multiply subtract (vector, by element). Where <T>/<Ts> is 4H/H, 8H/H, 2S/S or 4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

MUL Vd.<T>, Vn.<T>, Vm.<Ts>[index]

Integer multiply (vector, by element). Where <T>/<Ts> is 4H/H, 8H/H, 2S/S or 4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SMLAL Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer multiply accumulate long (vector, by element). Where <Ta>/<Tb>/<Ts> is 4S/4H/H or 2D/2S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SMLAL2 Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer multiply accumulate long (vector, by element, second part). Where <Ta>/<Tb>/<Ts> is 4S/8H/H or 2D/4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SMLSL Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer multiply subtract long (vector, by element). Where <Ta>/<Tb>/<Ts> is 4S/4H/H or 2D/2S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SMLSL2 Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer multiply subtract long (vector, by element, second part). Where <Ta>/<Tb>/<Ts> is 4S/8H/H or 2D/4S/S. If <Ts> is H, then Vm must be in the range V0-V15. If <Ts> is H, then Vm must be in the range V0-V15.

SMULL Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer multiply long (vector, by element). Where <Ta>/<Tb>/<Ts> is 4S/4H/H or 2D/2S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SMULL2 Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer multiply long (vector, by element, second part). Where <Ta>/<Tb>/<Ts> is 4S/8H/H or 2D/4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

UMLAL Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Unsigned integer multiply accumulate long (vector, by element). Where <Ta>/<Tb>/<Ts> is 4S/4H/H or 2D/2S/S. If <Ts> is H, then Vm must be in the range V0-V15.

UMLAL2 Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Unsigned integer multiply accumulate long (vector, by element, second part). Where <Ta>/<Tb>/<Ts> is 4S/8H/H or 2D/4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

UMLSL Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Unsigned integer multiply subtract long (vector, by element). Where <Ta>/<Tb>/<Ts> is 4S/4H/H or 2D/2S/S. If <Ts> is H, then Vm must be in the range V0-V15.

UMLSL2 Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Unsigned integer multiply subtract long (vector, by element, second part). Where <Ta>/<Tb>/<Ts> is 4S/8H/H or 2D/4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

UMULL Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Unsigned integer multiply long (vector, by element). Where <Ta>/<Tb>/<Ts> is 4S/4H/H or 2D/2S/S. If <Ts> is H, then Vm must be in the range V0-V15.

UMULL2 Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Unsigned integer multiply long (vector, by element, second part). Where <Ta>/<Tb>/<Ts> is 4S/8H/H or 2D/4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMLAL Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer saturating doubling multiply accumulate long (vector, by element). Where <Ta>/<Tb>/<Ts> is 4S/4H/H or 2D/2S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMLAL2 Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer saturating doubling multiply accumulate long (vector, by element, second part). Where <Ta>/<Tb>/<Ts> is 4S/8H/H or 2D/4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMLSL Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer saturating doubling multiply subtract long (vector, by element). Where <Ta>/<Tb>/<Ts> is 4S/4H/H or 2D/2S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMLSL2 Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer saturating doubling multiply subtract long (vector, by element, second part). Where <Ta>/<Tb>/<Ts> is 4S/8H/H or 2D/4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMULL Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer saturating doubling multiply long (vector, by element). Where <Ta>/<Tb>/<Ts> is 4S/4H/H or 2D/2S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMULL2 Vd.<Ta>, Vn.<Tb>, Vm.<Ts>[index]

Signed integer saturating doubling multiply long (vector, by element, second part). Where <Ta>/<Tb>/<Ts> is 4S/8H/H or 2D/4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMULH Vd.<Td>, Vn.<Td>, Vm.<Ts>[index]

Signed integer saturating doubling multiply returning high half (vector, by element). Where <Td>/<Ts> is 4H/H, 8H/H, 2S/S or 4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQRDMULH Vd.<Td>, Vn.<Td>, Vm.<Ts>[index]

Signed integer saturating rounding doubling multiply returning high half (vector, by element). Where <Td>/<Ts> is 4H/H, 8H/H, 2S/S or 4S/S. If <Ts> is H, then Vm must be in the range V0-V15.

5.8.11 Scalar-by-element Arithmetic

In all cases the immediate `index` is a constant in the range 0 to $(16/\text{sizeof}(\langle Ts \rangle)) - 1$.

FMLA <V>d, <V>n, Vm.<Ts>[index]

Floating-point fused multiply add (scalar, by element). Where <V>/<Ts> is S/S or D/D.

FMLS <V>d, <V>n, Vm.<Ts>[index]

Floating-point fused multiply subtract (scalar, by element). Where <V>/<Ts> is S/S or D/D.

FMUL <V>d, <V>n, Vm.<Ts>[index]

Floating-point multiply (scalar, by element). Where <V>/<Ts> is S/S or D/D.

FMULX <V>d, <V>n, Vm.<Ts>[index]

Floating-point multiply extended (scalar, by element): like FMUL but $0 \times \pm\infty \rightarrow \pm 2$. Where <V>/<Ts> is S/S, or D/D.

SQDMLAL <Va>d, <Vb>n, Vm.<Ts>[index]

Signed integer saturating doubling multiply accumulate long (scalar, by element). Where <Va>/<Vb>/<Ts> is S/H/H or D/S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMLSL <Va>d, <Vb>n, Vm.<Ts>[index]

Signed integer saturating doubling multiply subtract long (scalar, by element). Where <Va>/<Vb>/<Ts> is S/H/H or D/S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMULL <Va>d, <Vb>n, Vm.<Ts>[index]

Signed integer saturating doubling multiply long (scalar, by element). Where <Va>/<Vb>/<Ts> is S/H/H or D/S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQDMULH <V>d, <V>n, Vm.<Ts>[index]

Signed integer saturating doubling multiply returning high half (scalar, by element). Where <V>/<Ts> is H/H or S/S. If <Ts> is H, then Vm must be in the range V0-V15.

SQRDMULH <V>d, <V>n, Vm.<Ts>[index]

Signed integer saturating rounding doubling multiply returning high half (scalar, by element). Where <V>/<Ts> is H/H or S/S. If <Ts> is H, then Vm must be in the range V0-V15.

5.8.12 Vector Permute

EXT Vd.<T>, Vn.<T>, Vm.<T>, #index

Bitwise extract (vector). Where <T> is either 8B or 16B. The index is an immediate value in the range 0 to nelem(<T>)-1.

The following are replacements for the ARMv7 VTRN, VUZP and VZIP instructions which had two destination registers. Semantically these are identical to the ARMv7 instruction except that UZP1/TRN1/ZIP1 produce what would have been the Dn/Qn output of the ARMv7 instruction, whilst UZP2/TRN2/ZIP2 produce what would have been the Dm/Qm output.

TRN1 Vd.<T>, Vn.<T>, Vm.<T>

Vector element transpose (first part). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

TRN2 Vd.<T>, Vn.<T>, Vm.<T>

Vector element transpose (second part). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

UZP1 Vd.<T>, Vn.<T>, Vm.<T>

Vector element unzip (first part). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

UZP2 Vd.<T>, Vn.<T>, Vm.<T>

Vector element unzip (second part). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

ZIP1 Vd.<T>, Vn.<T>, Vm.<T>

Vector element zip (first part). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

ZIP2 Vd.<T>, Vn.<T>, Vm.<T>

Vector element zip (second part). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

5.8.13 Vector Immediate

MOVI Vn.<T>, #uimm8{, LSL #shift}

Move immediate (vector, shifted): replicates LSL(uimm8,shift) into each 32-bit element. Where <T> is 2S or 4S, and shift is 0, 8, 16 or 24 (default 0).

MOVI Vn.<T>, #uimm8, MSL #shift

Move immediate (vector, masked): replicates MSL(uimm8,shift) into each 32-bit element. Where <T> is 2S or 4S, and shift is 8 or 16. The MSL operator is a left shift, but filling the low order bits with ones instead of zeros.

MOVI Vn.<T>, #uimm8{, LSL #shift}

Move immediate (vector, shifted): replicates LSL(uimm8,shift) into each 16-bit element. Where <T> is 4H or 8H, and shift is 0 or 8 (default 0).

MOVI Vn.<T>, #uimm8

Move immediate (vector) : replicates uimm8 into each 8-bit element. Where <T> is 8B or 16B.

MOVI Vn.2D, #uimm64

Move immediate (vector) : replicates a “byte mask immediate” consisting of 8 bytes, each byte having only the value 0x00 or 0xff, into each 64-bit element.

MOVI Dn, #uimm64

Move immediate (scalar) : moves a “byte mask” immediate consisting of 8 bytes, each byte having only the value 0x00 or 0xff, into a 64-bit vector register.

MVNI Vn.<T>, #uimm8{, LSL #shift}

Move inverted immediate (vector, shifted): replicates NOT(LSL(uimm8,shift)) into each 32-bit element. Where <T> is 2S or 4S, and shift is 0, 8, 16 or 24 (default 0).

MVNI Vn.<T>, #uimm8, MSL #shift

Move inverted immediate (vector, masked): replicates NOT(MSL(uimm8,shift)) into each 32-bit element. Where <T> is 2S or 4S, and shift is 8 or 16. The MSL operator is a left shift, but filling the low order bits with ones instead of zeros.

MVNI Vn.<T>, #uimm8{, LSL #shift}

Move inverted immediate (vector, shifted): replicates NOT(LSL(uimm8,shift)) into each 16-bit element. Where <T> is 4H or 8H, and shift is 0 or 8 (default 0).

FMOV Vn.<T>, #fpimm

Floating point move immediate (vector). Where <T> is 2S, 4S or 2D, and fpimm is a floating point constant replicated into each vector element. The constant may be specified either in decimal notation (e.g. “12.0” or “-1.2e1”), or as a string beginning “0x” followed by the hexadecimal representation of its IEEE754 encoding. A disassembler should prefer the decimal notation, so long as the value can be displayed precisely. The floating point value must be expressible as $\pm n \cdot 16 \times 2^r$, where n and r are integers such that $16 \leq n \leq 31$ and $-3 \leq r \leq 4$, i.e. a normalized binary floating point encoding with sign, 4 bits of fraction and a 3-bit exponent.

Note that this encoding does not include the constant 0.0 – it is recommended that software should load this value using a MOVI Vn.<T>, #0 instruction.

BIC Vn.<T>, #uimm8{, LSL #shift}

Bitwise bit clear immediate (vector): bitwise AND of NOT(LSL(uimm8,shift)) with each 32-bit element. Where <T> is 2S or 4S, and shift is 0, 8, 16 or 24 (default 0).

BIC Vn.<T>, #uimm8{, LSL #shift}

Bitwise bit clear immediate (vector): bitwise AND of NOT(LSL(uimm8,shift)) with each 16-bit element. Where <T> is 4H or 8H, and shift is 0 or 8 (default 0).

ORR Vn.<T>, #uimm8{, LSL #shift}

Bitwise OR immediate (vector): bitwise OR of LSL(uimm8,shift) with each 32-bit element. Where <T> is 2S or 4S, and shift is 0, 8, 16 or 24 (default 0).

ORR Vn.<T>, #uimm8{, LSL #shift}

Bitwise OR immediate (vector): bitwise OR of LSL(uimm8,shift) with each 16-bit element. Where <T> is 4H or 8H, and shift is 0 or 8 (default 0).

5.8.14 Vector Shift (immediate)

USHR Vd.<T>, Vn.<T>, #shift

Unsigned integer shift right (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 1 to elsize(<T>).

SSHR Vd.<T>, Vn.<T>, #shift

Signed integer shift right (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 1 to elsize(<T>).

URSHR Vd.<T>, Vn.<T>, #shift

Unsigned integer rounding shift right (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 1 to elsize(<T>).

SRSR Vd.<T>, Vn.<T>, #shift

Signed integer rounding shift right (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 1 to elsize(<T>).

USRA Vd.<T>, Vn.<T>, #shift

Unsigned integer shift right and accumulate (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 1 to elsize(<T>).

SSRA Vd.<T>, Vn.<T>, #shift

Signed integer shift right and accumulate (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 1 to elsize(<T>).

URSRA Vd.<T>, Vn.<T>, #shift

Unsigned integer rounding shift right and accumulate (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 1 to elsize(<T>).

SRSRA Vd.<T>, Vn.<T>, #shift

Signed integer rounding shift right and accumulate (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 1 to elsize(<T>).

SRI Vd.<T>, Vn.<T>, #shift

Integer shift right and insert (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 1 to elsize(<T>).

SHRN Vd.<Td>, Vn.<Ts>, #shift

Integer shift right narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D; and shift is in the range 1 to elsize(<Td>).

SHRN2 Vd.<Td>, Vn.<Ts>, #shift

Integer shift right narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D; and shift is in the range 1 to elsize(<Td>).

UQSHRN Vd.<Td>, Vn.<Ts>, #shift

Unsigned integer saturating shift right narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D; and shift is in the range 1 to elsize(<Td>).

UQSHRN2 Vd.<Td>, Vn.<Ts>, #shift

Unsigned integer saturating shift right narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D; and shift is in the range 1 to elsize(<Td>).

SQSHRN Vd.<Td>, Vn.<Ts>, #shift

Signed integer saturating shift right narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D; and shift is in the range 1 to elsize(<Td>).

SQSHRN2 Vd.<Td>, Vn.<Ts>, #shift

Signed integer saturating shift right narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D; and shift is in the range 1 to elsize(<Td>).

RSHRN Vd.<Td>, Vn.<Ts>, #shift

Integer rounding shift right narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D; and shift is in the range 1 to elsize(<Td>).

RSHRN2 Vd.<Td>, Vn.<Ts>, #shift

Integer rounding shift right narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D; and shift is in the range 1 to elsize(<Td>).

UQRSHRN Vd.<Td>, Vn.<Ts>, #shift

Unsigned integer saturating rounding shift right narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D; and shift is in the range 1 to elsize(<Td>).

UQRSHRN2 Vd.<Td>, Vn.<Ts>, #shift

Unsigned integer saturating rounding shift right narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D; and shift is in the range 1 to elsize(<Td>).

SQRSHRN Vd.<Td>, Vn.<Ts>, #shift

Signed integer saturating rounding shift right narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D; and shift is in the range 1 to elsize(<Td>).

SQRSHRN2 Vd.<Td>, Vn.<Ts>, #shift

Signed integer saturating rounding shift right narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D; and shift is in the range 1 to elsize(<Td>).

SQSHRUN Vd.<Td>, Vn.<Ts>, #shift

Signed integer saturating shift right unsigned narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D; and shift is in the range 1 to elsize(<Td>).

SQSHRUN2 Vd.<Td>, Vn.<Ts>, #shift

Signed integer saturating shift right unsigned narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D; and shift is in the range 1 to elsize(<Td>).

SQRSHRUN Vd.<Td>, Vn.<Ts>, #shift

Signed integer saturating rounding shift right unsigned narrow (vector). Where <Td>/<Ts> is 8B/8H, 4H/4S, or 2S/2D; and shift is in the range 1 to elsize(<Td>).

SQRSHRUN2 Vd.<Td>, Vn.<Ts>, #shift

Signed integer saturating rounding shift right unsigned narrow (vector, second part). Where <Td>/<Ts> is 16B/8H, 8H/4S, or 4S/2D; and shift is in the range 1 to elsize(<Td>).

SHL Vd.<T>, Vn.<T>, #shift

Unsigned integer shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 0 to elsize(<T>)-1.

UQSHL Vd.<T>, Vn.<T>, #shift

Unsigned integer saturating shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 0 to elsize(<T>)-1.

SQSHL Vd.<T>, Vn.<T>, #shift

Signed integer saturating shift left (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 0 to elsize(<T>)-1.

SQSHLU Vd.<T>, Vn.<T>, #shift

Signed integer saturating shift left unsigned (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 0 to elsize(<T>)-1.

SLI Vd.<T>, Vn.<T>, #shift

Integer shift left and insert (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D; and shift is in the range 0 to elsize(<T>)-1.

USHLL Vd.<Td>, Vn.<Ts>, #shift

Unsigned integer shift left long (vector). Where <Td>/<Ts> is 8H/8B, 4S/4H, or 2D/2S; and shift is in the range 0 to elsize(<Ts>)-1.

USHLL2 Vd.<Td>, Vn.<Ts>, #shift

Unsigned integer shift left long (vector, second part). Where <Td>/<Ts> is 8H/16B, 4S/8H, or 2D/4S; and shift is in the range 0 to elsize(<Ts>)-1.

UXTL Vd.<Td>, Vn.<Ts>

Unsigned integer lengthen (vector). Where <Td>/<Ts> is 8H/8B, 4S/4H, or 2D/2S.
Alias for USHLL Vd.<Td>,Vn.<Ts>,#0.

UXTL2 Vd.<Td>, Vn.<Ts>

Unsigned integer lengthen (vector, second part). Where <Td>/<Ts> is 8H/16B, 4S/8H, or 2D/4S.
Alias for USHLL2 Vd.<Td>,Vn.<Ts>,#0.

SSHLL Vd.<Td>, Vn.<Ts>, #shift

Signed integer shift left long (vector). Where <Td>/<Ts> is 8H/8B, 4S/4H, or 2D/2S; and shift is in the range 0 to elsize(<Ts>)-1.

SSHLL2 Vd.<Td>, Vn.<Ts>, #shift

Signed integer shift left long (vector, second part). Where <Td>/<Ts> is 8H/16B, 4S/8H, or 2D/4S; and shift is in the range 0 to elsize(<Ts>)-1.

SHLL Vd.<Td>, Vn.<Ts>, #shift

Integer shift left long by element size (vector). Where <Td>/<Ts> is 8H/8B, 4S/4H, or 2D/2S; and shift is elsize(<Ts>).

SHLL2 Vd.<Td>, Vn.<Ts>, #shift

Integer shift left long by element size (vector, second part). Where <Td>/<Ts> is 8H/16B, 4S/8H, or 2D/4S; and shift is elsize(<Ts>).

SXTL Vd.<Td>, Vn.<Ts>

Signed integer lengthen (vector). Where <Td>/<Ts> is 8H/8B, 4S/4H, or 2D/2S.
Alias for SSHLL Vd.<Td>,Vn.<Ts>,#0.

SXTL2 Vd.<Td>, Vn.<Ts>

Signed integer lengthen (vector, second part). Where <Td>/<Ts> is 8H/16B, 4S/8H, or 2D/4S.
Alias for SSHLL2 Vd.<Td>,Vn.<Ts>,#0.

5.8.15 Scalar Shift (immediate)

USHR Dd, Dn, #shift

Unsigned integer shift right (scalar). Where shift is in the range 1 to 64.

SSHR Dd, Dn, #shift

Signed integer shift right (scalar). Where shift is in the range 1 to 64.

URSHR Dd, Dn, #shift

Unsigned integer rounding shift right (scalar). Where shift is in the range 1 to 64.

SRSHR Dd, Dn, #shift

Signed integer rounding shift right (scalar). Where shift is in the range 1 to 64.

USRA Dd, Dn, #shift

Unsigned integer shift right and accumulate (scalar). Where shift is in the range 1 to 64.

SSRA Dd, Dn, #shift

Signed integer shift right and accumulate (scalar). Where shift is in the range 1 to 64.

URSRA Dd, Dn, #shift

Unsigned integer rounding shift right and accumulate (scalar). Where shift is in the range 1 to 64.

SRSRA Dd, Dn, #shift

Signed integer rounding shift right and accumulate (scalar). Where shift is in the range 1 to 64.

SRI Dd, Dn, #shift

Integer shift right and insert (scalar). Where shift is in the range 1 to 64.

UQSHRN <Vd>d, <Vs>n, #shift

Unsigned integer saturating shift right narrow (scalar). Where <Vd>/<Vs> is B/H, H/S, or S/D; and shift is in the range 1 to elsize(<Vd>).

SQSHRN <Vd>d, <Vs>n, #shift

Signed integer saturating shift right narrow (scalar). Where <Vd>/<Vs> is B/H, H/S, or S/D; and shift is in the range 1 to elsize(<Vd>).

UQRSHRN <Vd>d, <Vs>n, #shift

Unsigned integer saturating rounding shift right narrow (scalar). Where <Vd>/<Vs> is B/H, H/S, or S/D; and shift is in the range 1 to elsize(<Vd>).

SQRSHRN <Vd>d, <Vs>n, #shift

Signed integer saturating rounding shift right narrow (scalar). Where <Vd>/<Vs> is B/H, H/S, or S/D; and shift is in the range 1 to elsize(<Vd>).

SQSHRUN <Vd>d, <Vs>n, #shift

Signed integer saturating shift right unsigned narrow (scalar). Where <Vd>/<Vs> is B/H, H/S, or S/D; and shift is in the range 1 to elsize(<Vd>).

SQRSHRUN <Vd>d, <Vs>n, #shift

Signed integer saturating rounding shift right unsigned narrow (scalar). Where <Vd>/<Vs> is B/H, H/S, or S/D; and shift is in the range 1 to elsize(<Vd>).

SHL Dd, Dn, #shift

Unsigned integer shift left (scalar). Where shift is in the range 0 to 63.

UQSHL <V>d, <V>n, #shift

Unsigned integer saturating shift left (scalar). Where <V> is B, H, S, or D; and shift is in the range 0 to elsize(<V>)-1.

SQSHL <V>d, <V>n, #shift

Signed integer saturating shift left (scalar). Where <V> is B, H, S, or D; and shift is in the range 0 to elsize(<V>)-1.

SQSHLU <V>d, <V>n, #shift

Signed integer saturating shift left unsigned (scalar). Where <V> is B, H, S, or D; and shift is in the range 0 to elsize(<V>)-1.

SLI Dd, Dn, #shift

Integer shift left and insert (scalar). Where shift is in the range 0 to 63.

5.8.16 Vector Floating Point / Integer Convert

These instructions raise the Invalid Operation exception (FPSR.IOC) in response to a floating point input of NaN, Infinity, or a numerical value that cannot be represented within the destination register. An out of range integer or fixed-point result will also be saturated to the destination size. A numeric result which differs from the input will raise the Inexact exception (FPSR.IXC).

FCVTxS Vd.<T>, Vn.<T>

Floating-point convert to signed integer of same size (vector). Where <T> is 2S, 4S or 2D. The letter x selects the rounding mode: N (nearest, ties to even); A (nearest, ties away from zero), P (towards +Inf); M (towards -Inf), Z (towards zero).

FCVTZS Vd.<T>, Vn.<T>, #fbits

Floating-point convert to signed fixed-point of same size (vector) with rounding towards zero. Where <T> is 2S, 4S or 2D. The number of fractional bits is represented by fbits in the range 1 to elsize(<T>).

FCVTxU Vd.<T>, Vn.<T>

Floating-point convert to unsigned integer of same size (vector). Where <T> is 2S, 4S or 2D. The letter x selects the rounding mode: N (nearest, ties to even); A (nearest, ties away from zero), P (towards +Inf); M (towards -Inf), Z (towards zero).

FCVTZU Vd.<T>, Vn.<T>, #fbits

Floating-point convert to unsigned fixed-point of same size (vector) with rounding towards zero. Where <T> is 2S, 4S or 2D. The number of fractional bits is represented by fbits in the range 1 to elsize(<T>).

SCVTF Vd.<T>, Vn.<T>

Signed integer convert to floating-point of same size using FPCR rounding mode (vector). Where <T> is 2S, 4S or 2D.

SCVTF Vd.<T>, Vn.<T>, #fbits

Signed fixed-point convert to floating-point of same size using FPCR rounding mode (vector). Where <T> is 2S, 4S or 2D. The number of fractional bits is represented by fbits in the range 1 to elsize(<T>).

UCVTF Vd.<T>, Vn.<T>

Unsigned integer convert to floating-point of same size using FPCR rounding mode (vector). Where <T> is 2S, 4S or 2D.

UCVTF Vd.<T>, Vn.<T>, #fbits

Unsigned fixed-point convert to floating-point of same size using FPCR rounding mode (vector). Where <T> is 2S, 4S or 2D. The number of fractional bits is represented by fbits in the range 1 to elsize(<T>).

5.8.17 Scalar Floating Point / Integer Convert

These instructions raise the Invalid Operation exception (FPSR.IOC) in response to a floating point input of NaN, Infinity, or a numerical value that cannot be represented within the destination register. An out of range integer or fixed-point result will also be saturated to the destination size. A numeric result which differs from the input will raise the Inexact exception (FPSR.IXC).

FCVTxS <V>d, <V>n

Floating-point convert to signed integer of same size (scalar). Where <V> is S or D. The letter x selects the rounding mode: N (nearest, ties to even); A (nearest, ties away from zero), P (towards +Inf); M (towards -Inf), Z (towards zero).

FCVTZS <V>d, <V>n, #fbits

Floating-point convert to signed fixed-point of same size (scalar) with rounding towards zero. Where <V> is S or D. The number of fractional bits is represented by fbits in the range 1 to elsize(<V>).

FCVTxU <V>d, <V>n

Floating-point convert to unsigned integer of same size (scalar). Where <V> is S or D. The letter x selects the rounding mode: N (nearest, ties to even); A (nearest, ties away from zero), P (towards +Inf); M (towards -Inf), Z (towards zero).

FCVTZU <V>d, <V>n, #fbits

Floating-point convert to unsigned fixed-point of same size (scalar) with rounding towards zero. Where <V> is S or D. The number of fractional bits is represented by fbits in the range 1 to elsize(<V>).

SCVTF <V>d, <V>n

Signed integer convert to floating-point of same size using FPCR rounding mode (scalar). Where <V> is S or D.

SCVTF <V>d, <V>n, #fbits

Signed fixed-point convert to floating-point of same size using FPCR rounding mode (scalar). Where <V> is S or D. The number of fractional bits is represented by fbits in the range 1 to elsize(<V>).

UCVTF <V>d, <V>n

Unsigned integer convert to floating-point of same size using FPCR rounding mode (scalar). Where <V> is S or D.

UCVTF <V>d, <V>n, #fbits

Unsigned fixed-point convert to floating-point of same size using FPCR rounding mode (scalar). Where <V> is S or D. The number of fractional bits is represented by fbits in the range 1 to elsize(<V>).

5.8.18 Vector Reduce (across lanes)

ADDV <V>d, Vn.<T>

Integer sum elements to scalar (vector). Where <V>/<T> is B/8B, B/16B, H/4H, H/8H, S/2S, or S/4S.

SADDLV <V>d, Vn.<T>

Signed integer sum elements to scalar long (vector). Where <V>/<T> is H/8B, H/16B, S/4H, S/8H, D/2S, or D/4S.

UADDLV <V>d, Vn.<T>

Unsigned integer sum elements to scalar long (vector). Where <V>/<T> is H/8B, H/16B, S/4H, S/8H, D/2S, or D/4S.

SMAXV <V>d, Vn.<T>

Signed integer maximum element to scalar (vector). Where <V>/<T> is B/8B, B/16B, H/4H, H/8H, S/2S, or S/4S.

SMINV <V>d, Vn.<T>

Signed integer minimum element to scalar (vector). Where <V>/<T> is B/8B, B/16B, H/4H, H/8H, S/2S, or S/4S.

UMAXV <V>d, Vn.<T>

Unsigned integer maximum element to scalar (vector). Where <V>/<T> is B/8B, B/16B, H/4H, H/8H, S/2S, or S/4S.

UMINV <V>d, Vn.<T>

Unsigned integer minimum element to scalar (vector). Where <V>/<T> is B/8B, B/16B, H/4H, H/8H, S/2S, or S/4S.

FMAXV Sd, Vn.4S

Floating-point maximum element to scalar (vector), equivalent to a sequence of pairwise reductions.

FMAXNMV Sd, Vn.4S

Floating-point maxNum element to scalar (vector), equivalent to a sequence of pairwise reductions.

FMINV Sd, Vn.4S

Floating-point minimum element to scalar (vector), equivalent to a sequence of pairwise reductions.

FMINNMV Sd, Vn.4S

Floating-point minNum element to scalar (vector), equivalent to a sequence of pairwise reductions.

5.8.19 Vector Pairwise Arithmetic

ADDP Vd.<T>, Vn.<T>, Vm.<T>

Integer add pair (vector). Where <T> is 8B, 16B, 4H, 8H, 2S, 4S or 2D.

FADDP Vd.<T>, Vn.<T>, Vm.<T>

Floating-point add pair (vector). Where <T> is 2S, 4S or 2D.

SMAXP Vd.<T>, Vn.<T>, Vm.<T>

Signed integer maximum pair (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S.

UMAXP Vd.<T>, Vn.<T>, Vm.<T>

Unsigned integer maximum pair (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S.

FMAXP Vd.<T>, Vn.<T>, Vm.<T>

Floating-point maximum pair (vector). Where <T> is 2S, 4S or 2D.

FMAXNMP Vd.<T>, Vn.<T>, Vm.<T>

Floating-point maxNum pair (vector). Where <T> is 2S, 4S or 2D.

SMINP Vd.<T>, Vn.<T>, Vm.<T>

Signed integer minimum pair (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S.

UMINP Vd.<T>, Vn.<T>, Vm.<T>

Unsigned integer minimum pair (vector). Where <T> is 8B, 16B, 4H, 8H, 2S or 4S.

FMINP Vd.<T>, Vn.<T>, Vm.<T>

Floating-point minimum pair (vector). Where <T> is 2S, 4S or 2D.

FMINNMP Vd.<T>, Vn.<T>, Vm.<T>

Floating-point minNum pair (vector). Where <T> is 2S, 4S or 2D.

5.8.20 Scalar Reduce (pairwise)

ADDP Dd, Vn.2D

Integer pairwise sum (scalar).

FADDP <V>d, Vn.<T>

Floating-point pairwise sum (scalar). Where <V>/<T> is S/2S or D/2D.

FMAXP <V>d, Vn.<T>

Floating-point pairwise maximum (scalar). Where <V>/<T> is S/2S or D/2D.

FMAXNMP <V>d, Vn.<T>

Floating-point pairwise maxNum (scalar). Where <V>/<T> is S/2S or D/2D.

FMINP <V>d, Vn.<T>

Floating-point pairwise minimum (scalar). Where <V>/<T> is S/2S or D/2D.

FMINNMP <V>d, Vn.<T>

Floating-point pairwise minNum (scalar). Where <V>/<T> is S/2S or D/2D.

5.8.21 Vector Table Lookup

TBL Vd.<T>, {Vn*.16B}, Vm.<T>

Table lookup (vector). Where <T> may be 8B or 16B, and Vn* is a list of between one and four consecutively numbered vector registers each holding sixteen 8-bit table elements. The list braces “{ }” are concrete symbols, and do not indicate an optional field as elsewhere in this manual.

TBX Vd.<T>, {Vn*.16B}, Vm.<T>

Table lookup extension (vector). Where <T> may be 8B or 16B, and Vn* is a list of between one and four consecutively numbered vector registers each holding sixteen 8-bit table elements. The list braces “{ }” are concrete symbols, and do not indicate an optional field as elsewhere in this manual.

5.8.22 Vector Load-Store Structure

All SIMD load-store structure instructions use the syntax term `vaddr` as shorthand for the following addressing modes:

`[base]`

Memory addressed by base register X_n or SP .

`[base], Xm`

Memory addressed by base register X_n or SP , post-incremented by 64-bit index register X_m .

`[base], #imm`

Memory addressed by X_n or SP , post-incremented by an immediate value which must equal the total number of bytes transferred to/from memory.

Register notation of the form V_{t+n} in the register lists below indicates that the register number is required to be equal to $(t + n) \text{ MOD } 32$. Furthermore the list braces “{ }” are concrete symbols, and do not indicate an optional field as elsewhere in this manual.

Like other load-store instructions they permit arbitrary address alignment, unless strict alignment checking is enabled, in which case alignment to the size of the element is checked. However unlike the general-purpose load-store instructions, the vector load-store instructions make no guarantee of atomicity, even when the address is naturally aligned to the size of element.

5.8.22.1 Load-Store Multiple Structures

In all of these instructions $\langle T \rangle$ is one of $8B$, $16B$, $4H$, $8H$, $2S$, $4S$, $2D$ and additionally the $LD1$ and $ST1$ instructions support the $1D$ format. A post-increment immediate offset, if present, must be 8, 16, 24, 32, 48 or 64, depending on the number of elements transferred.

$LD1 \{V_t.\langle T \rangle\}, vaddr$

Load multiple 1-element structures (to one register)

$LD1 \{V_t.\langle T \rangle, V_{t+1}.\langle T \rangle\}, vaddr$

Load multiple 1-element structures (to two consecutive registers)

$LD1 \{V_t.\langle T \rangle, V_{t+1}.\langle T \rangle, V_{t+2}.\langle T \rangle\}, vaddr$

Load multiple 1-element structures (to three consecutive registers)

$LD1 \{V_t.\langle T \rangle, V_{t+1}.\langle T \rangle, V_{t+2}.\langle T \rangle, V_{t+3}.\langle T \rangle\}, vaddr$

Load multiple 1-element structures (to four consecutive registers)

$LD2 \{V_t.\langle T \rangle, V_{t+1}.\langle T \rangle\}, vaddr$

Load multiple 2-element structures (to two consecutive registers)

$LD3 \{V_t.\langle T \rangle, V_{t+1}.\langle T \rangle, V_{t+2}.\langle T \rangle\}, vaddr$

Load multiple 3-element structures (to three consecutive registers)

$LD4 \{V_t.\langle T \rangle, V_{t+1}.\langle T \rangle, V_{t+2}.\langle T \rangle, V_{t+3}.\langle T \rangle\}, vaddr$

Load multiple 4-element structures (to four consecutive registers)

$ST1 \{V_t.\langle T \rangle\}, vaddr$

Store multiple 1-element structures (from one register)

$ST1 \{V_t.\langle T \rangle, V_{t+1}.\langle T \rangle\}, vaddr$

Store multiple 1-element structures (from two consecutive registers)

$ST1 \{V_t.\langle T \rangle, V_{t+1}.\langle T \rangle, V_{t+2}.\langle T \rangle\}, vaddr$

Store multiple 1-element structures (from three consecutive registers)

-
- ST1 {Vt.<T>, Vt+1.<T>, Vt+2.<T>, Vt+3.<T>}, vaddr
Store multiple 1-element structures (from four consecutive registers)
- ST2 {Vt.<T>, Vt+1.<T>}, vaddr
Store multiple 2-element structures (from two consecutive registers)
- ST3 {Vt.<T>, Vt+1.<T>, Vt+2.<T>}, vaddr
Store multiple 3-element structures (from three consecutive registers)
- ST4 {Vt.<T>, Vt+1.<T>, Vt+2.<T>, Vt+3.<T>}, vaddr
Store multiple 4-element structures (from four consecutive registers)

5.8.22.2 Load-Store Single Structure

In all of these instructions <T> is one of B, H, S or D. A post-increment immediate offset, if present, must be 1, 2, 3, 4, 6, 8, 12, 16, 24 or 32, depending on the number of elements transferred. The index is in the range 0 to (16/sizeof(<T>)-1).

- LD1 {Vt.<T>} [index], vaddr
Load single 1-element structure to one lane (of one register)
- LD2 {Vt.<T>, Vt+1.<T>} [index], vaddr
Load single 2-element structure to one lane (of two consecutive registers)
- LD3 {Vt.<T>, Vt+1.<T>, Vt+2.<T>} [index], vaddr
Load single 3-element structure to one lane (of three consecutive registers)
- LD4 {Vt.<T>, Vt+1.<T>, Vt+2.<T>, Vt+3.<T>} [index], vaddr
Load single 4-element structure to one lane (of four consecutive registers)
- ST1 {Vt.<T>} [index], vaddr
Store single 1-element structure from one lane (of one register)
- ST2 {Vt.<T>, Vt+1.<T>} [index], vaddr
Store single 2-element structure from one lane (of two consecutive registers)
- ST3 {Vt.<T>, Vt+1.<T>, Vt+2.<T>} [index], vaddr
Store single 3-element structure from one lane (of three consecutive registers)
- ST4 {Vt.<T>, Vt+1.<T>, Vt+2.<T>, Vt+3.<T>} [index], vaddr
Store single 4-element structure from one lane (of four consecutive registers)

5.8.22.3 Load Single Structure and Replicate

In all of these instructions <T> is one of 8B, 16B, 4H, 8H, 2S, 4S, 1D or 2D. A post-increment immediate offset, if present, must be 1, 2, 3, 4, 6, 8, 12, 16, 24 or 32, depending on the number of elements transferred.

- LD1R {Vt.<T>}, vaddr
Load single 1-element structure to all lanes (of one register)
- LD2R {Vt.<T>, Vt+1.<T>}, vaddr
Load single 2-element structure to all lanes (of two consecutive registers)
- LD3R {Vt.<T>, Vt+1.<T>, Vt+2.<T>}, vaddr
Load single 3-element structure to all lanes (of three consecutive registers)
- LD4R {Vt.<T>, Vt+1.<T>, Vt+2.<T>, Vt+3.<T>}, vaddr
Load single 4-element structure to all lanes (of four consecutive registers)

5.8.23 AArch32 Equivalent Advanced SIMD Mnemonics

New or changed functionality is **highlighted**. Note that all Advanced SIMD floating point functionality changes implicitly to honor the FPCR rounding mode field, the Default NaN control, the Flush-to-Zero control, and (where supported by the implementation) the Exception trap enable bits.

| AArch32 | AArch64 | | | | | Description |
|---------|-----------------|-----------------|-----------------|----------------|------|--|
| | Integer | | | Floating point | Poly | |
| | Agnostic | Unsigned | Signed | | | |
| VABA | | UABA | SABA | | | Integer vector absolute difference and accumulate |
| VABAL | | UABAL UABAL2 | SABAL SABAL2 | | | Integer vector absolute difference and accumulate long |
| VABD | | UABD | SABD | FABD | | Vector absolute difference |
| VABDL | | UABDL UABDL2 | SABDL SABDL2 | | | Integer vector absolute difference long |
| VABS | | | ABS | FABS | | Vector absolute value |
| VACGE | | | | FACGE | | Floating-point vector absolute compare greater than or equal |
| VACGT | | | | FACGT | | Floating-point vector absolute compare greater than |
| VACLE | | | | FACLE | | Floating-point vector absolute compare less than or equal |
| VACLT | | | | FACLT | | Floating-point vector absolute compare less than |
| VADD | ADD | | | FADD | | Vector add |
| VADDHN | ADDHN ADDHN2 | | | | | Integer vector add and narrow high half |
| VADDL | | UADDL UADDL2 | SADDL SADDL2 | | | Integer vector add long |
| VADDW | | UADDW UADDW2 | SADDW SADDW2 | | | Integer vector add wide |
| VAND | AND | | | | | Bitwise vector AND |
| VBIC | BIC | | | | | Bitwise vector bit clear |
| VBIF | BIF | | | | | Bitwise vector insert if false |

| | | | | | | |
|---------------------|------|-------|-------|----------------|--|---|
| VBIT | BIT | | | | | Bitwise vector insert if true |
| VBSL | BSL | | | | | Bitwise vector select |
| VCEQ | CMEQ | | | FCMEQ | | Vector compare equal |
| VCGE | | CMHS | CMGE | FCMGE | | Vector compare greater than or equal |
| VCGT | | CMHI | CMGT | FCMGT | | Vector compare greater than |
| VCLE | | CMLS | CMLE | FCMLE | | Vector compare less than or equal |
| VCLS | CLS | | | | | Integer vector count leading sign bits |
| VCLT | | CMLO | CMLT | FCMLT | | Vector compare less than |
| VCLZ | CLZ | | | | | Integer vector count leading zero bits |
| VCMP | | | | FCMP | | Floating-point compare |
| VCMPPE | | | | FCMPPE | | Floating-point compare (exceptions on quiet NaNs) |
| VCNT | CNT | | | | | Vector count non-zero bits |
| VCVT.s32.f32 | | | | FCVTZS | | Vector floating-point convert to signed integer (round to zero) |
| new | | | | FCVTxS | | Vector floating-point convert to signed integer (round to x) |
| VCVT.u32.f32 | | | | FCVTZU | | Vector floating-point convert to unsigned integer (round to zero) |
| new | | | | FCVTxU | | Vector floating-point convert to unsigned integer (round to x) |
| VCVT.f32.i32 | | UCVTF | SCVTF | | | Vector integer convert to floating-point |
| VCVT.f*.f* | | | | FCVTN FCVTL | | Vector convert floating-point precision |
| new | | | | FCVTxN | | Vector convert double to single-precision (rounding to odd) |
| new | | | | FRINTx | | Vector floating-point round to integral f-p value (towards x) |
| new | | | | FDIV | | Vector floating-point divide |

| | | | | | | |
|------------------|------------|-----------------|-----------------|---------------|-----------------|--|
| VDUP | DUP | | | | | Duplicate single vector element to all elements |
| new | INS | | | | | Insert single element in another element |
| VEOR | EOR | | | | | Bitwise vector exclusive OR |
| VEXT | EXT | | | | | Bitwise vector extract |
| VHADD | | UHADD | SHADD | | | Integer vector halving add |
| VHSUB | | UHSUB | SHSUB | | | Integer vector halving subtract |
| VLD1..4 | LD1..4 | | | | | Vector structure /element load |
| VLD1..4 | LD1..4R | | | | | Vector replicated element load |
| VLDM/VLDR | LDP/LDR | | | | | Vector load pair/register |
| VMAX | | UMAX | SMAX | FMAX | | Vector maximum |
| new | | | | FMAXNM | | Floating-point vector maxNum |
| VMIN | | UMIN | SMIN | FMIN | | Vector minimum |
| new | | | | FMINNM | | Floating-point vector minNum |
| VMLA | MLA | | | n/a | | Vector chained multiply-accumulate |
| VFMA | | | | FMLA | | Vector fused multiply-accumulate |
| VMLAL | | UMLAL UMLAL2 | SMLAL SMLAL2 | | | Integer vector multiply-accumulate long |
| VMLS | MLS | | | n/a | | Vector chained multiply-subtract |
| VFMS | | | | FMLS | | Vector fused multiply-subtract |
| VMLSL | | UMLSL UMLSL2 | SMLSL SMLSL2 | | | Integer vector multiply-subtract long |
| VMOV | MOV | UMOV | SMOV | FMOV | | Vector move |
| VMOVL | | UXTL UXTL2 | SXTL SXTL2 | | | Integer vector lengthen (pseudo for USHLL/SSHL #0) |
| VMOVN | XTN | | | | | Integer vector narrow |
| VMUL | MUL | | | FMUL | PMUL | Vector multiply |
| new | | | | FMULX | | Floating-point vector multiply extended (0xINF→2) |
| VMULL | | UMULL UMULL2 | SMULL SMULL2 | | PMULL PMULL2 | Vector multiply long |
| VMVN | MVN | | | | | Bitwise vector NOT |

| | | | | | | |
|----------------|------|-----------------|---------------------|----------------|--|---|
| VNEG | | | NEG | FNEG | | Vector negate |
| VORN | ORN | | | | | Bitwise vector OR NOT |
| VORR | ORR | | | | | Bitwise vector OR |
| VPADAL | | UADALP | SADALP | | | Integer vector add and accumulate long pair |
| VPADD | ADDP | | | FADDP | | Vector add pair |
| VPADDL | | UADDLP | SADDLP | | | Integer vector add long pair |
| VPMAX | | UMAXP | SMAXP | FMAXP | | Vector max pair |
| new | | | | FMAXNMP | | Floating-point vector maxNum pair |
| VPMIN | | UMINP | SMINP | FMINP | | Vector min pair |
| new | | | | FMINNMP | | Floating-point vector minNum pair |
| VQABS | | | SQABS | | | Signed integer saturating vector absolute |
| VQADD | | UQADD | SQADD | | | Integer saturating vector add |
| new | | SUQADD | | | | Signed integer saturating vector accumulate of unsigned value |
| new | | | USQADD | | | Unsigned integer saturating vector accumulate of signed value |
| VQDMLAL | | | SQDMLAL SQDMLAL2 | | | Signed integer saturating vector doubling multiply accumulate long |
| VQDMLSL | | | SQDMLSL SQDMLSL2 | | | Signed integer saturating vector doubling multiply subtract from accumulator long |
| VQDMULH | | | SQDMULH | | | Signed integer saturating vector doubling multiply high half |
| VQDMULL | | | SQDMULL SQDMULL2 | | | Signed integer saturating vector doubling multiply long |
| VQMOVN | | UQXTN UQXTN2 | SQXTN SQXTN2 | | | Integer saturating vector narrow |

| | | | | | | |
|---|-------------------------|---------|-------------------|--------|--|---|
| VQMOVUN | | | SQXTUN SQXTUN2 | | | Signed integer saturating vector and unsigned narrow |
| VQNEG | | | SQNEG | | | Signed integer saturating vector negate |
| VQRDMULH | | | SQRDMULH | | | Signed integer vector saturating rounding doubling multiply high half |
| VQRSHL | | UQRSHL | SQRSHL | | | Integer saturating vector rounding shift left |
| VQRSHRN | | UQRSHRN | SQRSHRN | | | Integer saturating vector shift right rounded narrow |
| VQRSHRUN | | | SQRSHRUN | | | Signed integer saturating vector shift right rounded unsigned narrow |
| VQSHL | | UQSHL | SQSHL | | | Integer saturating vector shift left |
| VQSHLU | | | SQSHLU | | | Signed integer saturating vector shift left unsigned |
| VQSHRN | | UQSHRN | SQSHRN | | | Integer saturating vector shift right narrow |
| VQSHRUN | | | SQSHRUN | | | Signed integer saturating vector shift right unsigned narrow |
| VQSUB | | UQSUB | SQSUB | | | Integer saturating vector subtract |
| VRADDHN | RADDHN | | | | | Integer vector rounding add and narrow high half |
| VRECPE | | URECPE | | FRECPE | | Vector reciprocal estimate |
| VRECPS | | | | FRECPS | | Floating-point vector reciprocal step (FRECPS uses fused mac; VRECPS remains non-fused) |
| new | | | | FRECPS | | Floating-point reciprocal exponent |
| new | RBIT | | | | | Vector reverse bits in bytes |
| VREV16 VREV32 VREV64 | REV16 REV32 REV64 | | | | | Vector reverse elements |

| | | | | | | |
|------------------|-------------------|-----------------|-----------------|---------|--|--|
| VRHADD | | URHADD | SRHADD | | | Integer rounding vector halving add |
| VRSHL | | URSHL | SRSHL | | | Integer rounding vector shift left |
| VRSHR | | URSHR | SRSHR | | | Integer rounding vector shift right |
| VRSHRN | RSHRN RSHRN2 | | | | | Integer rounding vector shift right narrow |
| VRSQRTE | | URSQRTE | | FRSQRTE | | Vector reciprocal square root estimate |
| VRSQRTS | | | | FRSQRTS | | Floating-point reciprocal square root step (FRSQRTS uses fused mac; VRSQRTS remains non-fused) |
| VRSRA | | URSRA | SRSRA | | | Integer rounding vector shift right and accumulate |
| VRSUBHN | RSUBHN RSUBHN2 | | | | | Integer rounding vector subtract and narrow high half |
| VSHL | SHL | | | | | Integer vector shift left |
| VSHLL | | USHLL | SSHLL | | | Integer vector shift left long |
| VSHR | | USHR | SSHHR | | | Integer vector shift right |
| VSHRN | SHRN SHRN2 | | | | | Integer vector shift right narrow |
| VSLI | SLI | | | | | Integer vector shift left and insert |
| new | | | | FSQRT | | Floating-point vector square root |
| VSRA | | USRA | SSRA | | | Integer vector shift right and accumulate |
| VSRI | SRI | | | | | Integer vector shift right and insert |
| VST1..4 | ST1..4 | | | | | Vector structure store |
| VSTM/VSTR | STP/STR | | | | | Vector store pair/register |
| VSUB | SUB | | | FSUB | | Vector subtract |
| VSUBHN | SUBHN SUBHN2 | | | | | Integer vector subtract and narrow high half |
| VSUBL | | USUBL USUBL2 | SSUBL SSUBL2 | | | Integer vector subtract long |
| VSUBW | | USUBW USUBW2 | SSUBW SSUBW2 | | | Integer vector subtract wide |
| VSWP | n/a | | | | | Vector swap |

| | | | | | | |
|-------------|--------------|---------------|---------------|----------------|--|---|
| VTBL | TBL | | | | | Vector table lookup |
| VTBX | TBX | | | | | Vector table extension |
| VTRN | TRN1 TRN2 | | | | | Vector element transpose |
| VTST | CMTST | | | | | Vector test bits |
| VUZP | UZP1 UZP2 | | | | | Vector element unzip |
| VZIP | ZIP ZIP2 | | | | | Vector element zip |
| new | ADDV | | | | | Integer sum elements in vector |
| new | | SADDLV | UADDLV | | | Integer sum elements in vector long |
| new | | SMAXV | UMAXV | FMAXV | | Maximum element in vector |
| new | | | | FMAXNMV | | Floating-point maxNum element in vector |
| new | | SMINV | UMINV | FMINV | | Minimum element in vector |
| new | | | | FMINNMV | | Floating-point minNum element in vector |

5.8.24 Crypto Extension

The optional Crypto extension shares the FP/SIMD register file. For more information see [AES], [GCM] and [SHA].

PMULL Vd.1Q, Vn.1D, Vm.1D

Polynomial multiply long (vector): AES-GCM acceleration 64x64 to 128-bit.

PMULL2 Vd.1Q, Vn.2D, Vm.2D

Polynomial multiply long (vector, second part). Upper lanes AES-GCM acceleration 64x64 to 128-bit.

AESE Vd.16B, Vn.16B

AES single round encryption.

AESD Vd.16B, Vn.16B

AES single round decryption.

AESMC Vd.16B, Vn.16B

AES mix columns.

AESIMC Vd.16B, Vn.16B

AES inverse mix columns.

SHA256H Qd, Qn, Vm.4S

SHA256 hash update accelerator.

SHA256H2 Qd, Qn, Vm.4S

SHA256 hash update accelerator, upper part.

SHA256SU0 Vd.4S, Vn.4S

SHA256 schedule update accelerator, first part

SHA256SU1 Vd.4S, Vn.4S, Vm.4S

SHA256 schedule update accelerator, second part

SHA1C Qd, Sn, Vm.4S

SHA1 hash update accelerator (choose).

SHA1P Qd, Sn, Vm.4S

SHA1 hash update accelerator (parity).

SHA1M Qd, Sn, Vm.4S

SHA1 hash update accelerator (majority).

SHA1H Sd, Sn

SHA1 hash update accelerator (rotate left by 30).

SHA1SU0 Vd.4S, Vn.4S, Vm.4S

SHA1 schedule update accelerator, first part

SHA1SU1 Vd.4S, Vn.4S

SHA1 schedule update accelerator, second part

5.9 System Instructions

The following instruction groups are supported:

- Exception generating instructions
- System register access
- System management
- Architectural hints
- Barriers and CLREX

In several of the system instructions described in this section, the following terms are used to describe operands:

`op0`

A 2-bit opcode field with an immediate value 2 or 3.

`op1, op2`

A 3-bit opcode field with an immediate value in the range 0 to 7.

`Cn`

A 4-bit opcode field named for historical reasons `C0 – C15`.

`Cm`

A 4-bit opcode field named for historical reasons `C0 – C15`.

5.9.1 Exception Generation and Return

5.9.1.1 Non-debug exceptions

`SVC #uimm16`

Generate exception targeted at exception level 1 (system), with 16-bit payload in `uimm16`.

`HVC #uimm16`

Generate exception targeted at exception level 2 (hypervisor), with 16-bit payload in `uimm16`.

`SMC #uimm16`

Generate exception targeted at exception level 3 (secure monitor), with 16-bit payload in `uimm16`.

`ERET`

Exception return: reconstructs the processor state from the current exception level's `SPSR_ELn` register, and branches to the address in `ELR_ELn`.

5.9.1.2 Debug exceptions

`BRK #uimm16`

Monitor mode software breakpoint: exception routed to a debug monitor executing in EL1 or EL2, with 16-bit payload in `uimm16`.

`HLT #uimm16`

Halting mode software breakpoint: enters halting mode debug state if enabled, else treated as UNALLOCATED. With 16-bit payload in `uimm16`.

`DCPS1 {#uimm16}`

Debug Change Processor State to EL1 (valid in halting mode debug state only), the optional 16-bit immediate `uimm16` defaults to zero and is ignored by the hardware.

DCPS2 {#uimm16}

Debug Change Processor State to EL2 (valid in halting mode debug state only), the optional 16-bit immediate `uimm16` defaults to zero and is ignored by the hardware.

DCPS3 {#uimm16}

Debug Change Processor State to EL3 (valid in halting mode debug state only), the optional 16-bit immediate `uimm16` defaults to zero and is ignored by the hardware.

DRPS

Debug Restore Processor State: restores the processor to the exception level and mode recorded in the current exception level's `SPSR_ELn` register (valid in halting mode debug state only).

5.9.2 System Register Access

MRS `Xt`, <system_register>

Move <system_register> to `Xt`, where <system_register> is a system register name, or for registers encoded in the region reserved for implementations a synthetic name of the form "S<op0>_<op1>_<Cn>_<Cm>_<op2>", e.g. "S3_4_c11_c9_7". Non-architectural register encodings outside of the implementation defined region do not have a name.

MSR <system_register>, `Xt`

Move `Xt` to <system_register>, where <system_register> is a system register name, or for implementation defined registers a synthetic name, as described for MRS.

MSR DAIFFClr, #uimm4

Uses `uimm4` as a bitmask to select the clearing of one or more of the DAIF exception mask bits: bit 3 selects the D mask, bit 2 the A mask, bit 1 the I mask and bit 0 the F mask.

MSR DAIFSet, #uimm4

Uses `uimm4` as a bitmask to select the setting of one or more of the DAIF exception mask bits: bit 3 selects the D mask, bit 2 the A mask, bit 1 the I mask and bit 0 the F mask.

MSR SPSel, #uimm4

Uses `uimm4` as a control value to select the stack pointer: if bit 0 is set it selects the current exception level's stack pointer, if bit 0 is clear it selects shared EL0 stack pointer. Bits 1 to 3 of `uimm4` are reserved and should be zero.

5.9.3 System Management

Where the operands of a `SYS` instruction match an entry in the <xx_op> tables below, then the associated alias is the preferred disassembly. Otherwise the `SYS` or `SYSL` mnemonics shall be used, permitting generation and disassembly of arbitrary implementation-defined system instructions.

SYS #op1, Cn, Cm, #op2{, Xt}

Perform system maintenance instruction with optional source register `Xt` (defaulting to `XZR`), with the operation selected by `op1`, `Cn`, `Cm`, and `op2`.

SYSL `Xt`, #op1, Cn, Cm, #op2

Perform system maintenance instruction returning a result in destination register `Xt`, with the operation selected by `op1`, `Cn`, `Cm`, and `op2`.

IC <ic_op>{, Xt}

Instruction cache maintenance instruction, where `Xt` is the address argument as required (defaulting to `XZR`) and <ic_op> is defined as:

```
<ic_op> ::= <function><type><point>{<domain>}
<function> ::= "I" (invalidate)
<type> ::= "ALL" (entire cache) | "VA" (by virtual address)
```

<point> ::= "U" (to point of unification)
 <domain> ::= "IS" (inner sharable)

This is the preferred alias for the SYS instruction with the following operand values:

| <ic_op> | op1 | Cn | Cm | op2 | {Xt} |
|---------|-----|----|----|-----|------|
| IALLUIS | 0 | C7 | C1 | 0 | |
| IALLU | 0 | C7 | C5 | 0 | |
| IVAU | 3 | C7 | C5 | 1 | ✓ |

DC <dc_op>, Xt

Data cache maintenance instruction, where Xt is the address argument and <dc_op> is defined as:

<dc_op> ::= <function><type>{<point>}
 <function> ::= "I" (invalidate) | "C" (clean) | "CI" (clean & invalidate)
 | "Z" (zero)
 <type> ::= "VA" (by virtual address) | "SW" (by set/way)
 <point> ::= "C" (to point of coherency) | "U" (to point of unification)

This is the preferred alias for the SYS instruction with the following operand values:

| <dc_op> | op1 | Cn | Cm | op2 |
|---------|-----|----|-----|-----|
| ZVA | 3 | C7 | C4 | 1 |
| IVAC | 0 | C7 | C6 | 1 |
| ISW | 0 | C7 | C6 | 2 |
| CVAC | 3 | C7 | C10 | 1 |
| CSW | 0 | C7 | C10 | 2 |
| CVAU | 3 | C7 | C11 | 1 |
| CIVAC | 3 | C7 | C14 | 1 |
| CISW | 0 | C7 | C14 | 2 |

AT <at_op>, Xt

Address Translation instruction, where Xt is the address argument and <at_op> is defined as:

<at_op> ::= <type><level><readwrite>
 <type> ::= "S1" (stage 1 translation) | "S12" (stage 1 and 2 translation)
 <level> ::= "E0" (exception level 0) | "E1" (exception level 1)
 | "E2" (exception level 2) | "E3" (exception level 3)
 <readwrite> ::= "R" (read) | "W" (write)

This is the preferred alias for the SYS instruction with the following operand values:

| <at_op> | op1 | Cn | Cm | op2 |
|---------|-----|----|----|-----|
| S1E1R | 0 | C7 | C8 | 0 |
| S1E2R | 4 | C7 | C8 | 0 |
| S1E3R | 6 | C7 | C8 | 0 |
| S1E1W | 0 | C7 | C8 | 1 |
| S1E2W | 4 | C7 | C8 | 1 |
| S1E3W | 6 | C7 | C8 | 1 |
| S1E0R | 0 | C7 | C8 | 2 |
| S1E0W | 0 | C7 | C8 | 3 |
| S12E1R | 4 | C7 | C8 | 4 |
| S12E1W | 4 | C7 | C8 | 5 |
| S12E0R | 4 | C7 | C8 | 6 |
| S12E0W | 4 | C7 | C8 | 7 |

TLBI <tlbi_op>{, Xt}

TLB invalidation instruction, where Xt is the address argument if required (defaulting to XZR).

```

<tlbi_op> ::= <type><level>{<domain>}
<type>    ::= "ALL" (all translations at level)
           | "VMALL" (all stage 1 translations, current VMID)
           | "VMALLS12" (all stage 1 & 2 translations, current VMID)
           | "ASID" (translations matching ASID)
           | "VA" (translations matching VA and ASID)
           | "VAL" (last-level translations matching VA and ASID)
           | "VAA" (translations matching VA, all ASIDs)
           | "VAAL" (last-level translations matching VA, all ASIDs)
           | "IPAS2" (stage 2 translations matching IPA, current VMID)
           | "IPAS2L" (last-level stage 2 translations matching IPA, current VMID)
<level>   ::= "E0" (exception level 0) | "E1" (exception level 1)
           | "E2" (exception level 2) | "E3" (exception level 3)
<domain>  ::= "IS" (inner sharable)

```

This is the preferred alias for the SYS instruction with the following operand values:

| <tlbi_op> | op1 | Cn | Cm | op2 | {Xt} |
|--------------|-----|----|----|-----|------|
| IPAS2E1IS | 4 | C8 | C0 | 1 | ✓ |
| IPAS2LE1IS | 4 | C8 | C0 | 5 | ✓ |
| VMALLE1IS | 0 | C8 | C3 | 0 | |
| ALLE2IS | 4 | C8 | C3 | 0 | |
| ALLE3IS | 6 | C8 | C3 | 0 | |
| VAE1IS | 0 | C8 | C3 | 1 | ✓ |
| VAE2IS | 4 | C8 | C3 | 1 | ✓ |
| VAE3IS | 6 | C8 | C3 | 1 | ✓ |
| ASIDE1IS | 0 | C8 | C3 | 2 | ✓ |
| VAAE1IS | 0 | C8 | C3 | 3 | ✓ |
| ALLE1IS | 4 | C8 | C3 | 4 | |
| VALE1IS | 0 | C8 | C3 | 5 | ✓ |
| VAALE1IS | 0 | C8 | C3 | 7 | ✓ |
| VMALLE1 | 0 | C8 | C7 | 0 | |
| ALLE2 | 4 | C8 | C7 | 0 | |
| VALE2IS | 4 | C8 | C3 | 5 | ✓ |
| VALE3IS | 6 | C8 | C3 | 5 | ✓ |
| VMALLS12E1IS | 4 | C8 | C3 | 6 | |
| ALLE3 | 6 | C8 | C7 | 0 | |
| IPAS2E1 | 4 | C8 | C4 | 1 | ✓ |
| IPAS2LE1 | 4 | C8 | C4 | 5 | ✓ |
| VAE1 | 0 | C8 | C7 | 1 | ✓ |
| VAE2 | 4 | C8 | C7 | 1 | ✓ |
| VAE3 | 6 | C8 | C7 | 1 | ✓ |
| ASIDE1 | 0 | C8 | C7 | 2 | ✓ |
| VAAE1 | 0 | C8 | C7 | 3 | ✓ |
| ALLE1 | 4 | C8 | C7 | 4 | |
| VALE1 | 0 | C8 | C7 | 5 | ✓ |
| VALE2 | 4 | C8 | C7 | 5 | ✓ |
| VALE3 | 6 | C8 | C7 | 5 | ✓ |
| VMALLS12E1 | 4 | C8 | C7 | 6 | |
| VAALE1 | 0 | C8 | C7 | 7 | ✓ |

5.9.4 Architectural Hints

NOP

No Operation. May be used to enforce instruction alignment, but has no execution timing constraints and so may be safely deleted from the instruction stream.

YIELD

Yield hint.

WFE

Wait For Event.

WFI

Wait For Interrupt.

SEV

Send Event: send event globally. Note that in ARMv8 a *DSB* and *SEV* instruction are in most cases not required following a synchronization operation such as unlocking a spin-lock or releasing a semaphore. A memory transaction which clears a processor's global exclusive monitor also implicitly generates an event for that processor, as held in the Event register and used by the *WFE* instruction.

SEVL

Send Event Local: send event locally, without being required to affect other processors, for example to prime a wait-loop which starts with a *WFE* instruction.

HINT #uimm7

Unallocated hint, where *uimm7* is in the range 6-127. The unallocated hint instructions behave as a *NOP* but might be allocated to other hint functionality in future revisions of the architecture.

5.9.5 Barriers and CLREX

CLREX {#uimm4}

Clear Exclusive: clears the local record of the executing processor that an address has had a request for an exclusive access. The 4-bit immediate *uimm4* defaults to *0xf* if omitted, with all other values unallocated.

DSB <option>|#uimm4

Data Synchronization Barrier, where *<option>* is any barrier option, as below, or a 4-bit immediate *uimm4* for unallocated values of option:

DMB <option>|#uimm4

Data Memory Barrier, where *<option>* is any barrier option, as below, or a 4-bit immediate *uimm4* for unallocated values of option.

ISB {SY|#uimm4}

Instruction Synchronization Barrier, where *SY* encoded as value *0xf* is the default, or a 4-bit immediate *uimm4* for other unallocated values of option.

The following table defines the allocated values of data barrier option. Unallocated values behave as *SY* but might be allocated to other barrier functionality in future revisions of the architecture.

| <option> | Value | Shareability Domain | Ordered Accesses (before-after) |
|-----------------------|--------------|----------------------------|--|
| OSHLd | 0x1 | Outer shareable | Load-Load, Load-Store |
| OSHST | 0x2 | | Store-Store |
| OSH | 0x3 | | Any-Any |
| NSHLd | 0x5 | Non-shareable | Load-Load, Load-Store |
| NSHST | 0x6 | | Store-Store |
| NSH | 0x7 | | Any-Any |
| ISHLd | 0x9 | Inner shareable | Load-Load, Load-Store |
| ISHST | 0xa | | Store-Store |
| ISH | 0xb | | Any-Any |
| LD | 0xd | Full system | Load-Load, Load-Store |
| ST | 0xe | | Store-Store |
| SY | 0xf | | Any-Any |

6 A32 & T32 INSTRUCTION SETS

In ARMv8 AArch32 the A32, T32 and T32EE instruction sets are broadly equivalent to the instructions sets named ARM, Thumb and ThumbEE respectively in [v7A].

In addition ARMv8 AArch32 includes A32 and T32 instructions and features introduced by the following ARMv7 architectural extensions:

- *Multiprocessing (MP) Extensions*.
- *Large Physical Address Extension (LPAE)*.
- *Virtualization Extension (ARMv7VE)*, regardless of whether exception level EL2 is implemented, including the SDIV, UDIV, ERET, MRS/MSR (Banked register) and HVC instructions.
- *Security Extensions (ARMv6K)*, regardless of whether exception level EL3 is implemented, including the SMC instruction.
- *VFPv4-D32 or VFPv4U-D32*, including half-precision floating point, and the VFMA and VFMS instructions.
- *Advanced SIMDv2*, including half-precision floating point, and the VFMA and VFMS instructions.

The following ARMv7 architectural extensions are substantially altered as part of ARMv8.

- *Debug v8* – is backwards compatible in AArch32 state with self-hosted (*aka* monitor-mode) debug software written for *Debug v7.1*.
- *Optional Performance Monitors Extension (PMUv3)* – is backwards compatible in AArch32 state with self-hosted software written for *PMUv2*.
- *Optional Embedded Trace Macrocell (ETMv4)* – is not backwards compatible with *ETMv3.5* or *PFTv1.1*.

The following are obsoleted in ARMv8:

- A32 SWP and SWPB instructions.
- Jazelle (only trivial implementations are supported).
- VFP short vectors and asynchronous bounces.
- *Fast Context Switch Extension (FCSE)*.

The following are deprecated in ARMv8 and may be disabled by privileged software:

- A32 and T32 CP15 barriers CP15DSB, CP15ISB and CP15DMB.
- A32 and T32 SETEND instruction.
- A subset of T32 IT instruction functionality, as described in §6.1 below.
- T32EE instructions and coprocessor registers are both deprecated and optional.

In addition some of the new functionality provided by the A64 instruction set is independent of the general purpose register width and therefore equally applicable to AArch32 state, namely: enhanced barrier types; hints; load-acquire and store-release; new IEEE 754-2008 operations; and cryptography extensions. Accordingly these new instructions are added to the A32 and T32 instruction sets by ARMv8 as described below.

Note that the existing A32 and T32 assembler syntax remains unchanged from ARMv7 UAL. The syntax term `<c>` where used below represents a standard ARM condition code – mnemonics which do not include `<c>` may not be conditionally executed.

6.1 Partial Deprecation of IT

In conjunction with the reduction of conditionality in the A64 instruction set, and to facilitate higher performance implementations of the architecture in the future, ARMv8 deprecates some uses of the T32 IT instruction. All uses of IT that apply to other than a single subsequent 16-bit instruction from a restricted set are deprecated, as are explicit references to R15 (i.e. PC) within that single 16-bit instruction. This permits the non-deprecated forms of IT and subsequent instruction to be treated by the processor as a single 32-bit conditional instruction. The restricted set of 16-bit instructions which are *not* deprecated when used in conjunction with IT are as follows:

| Permitted 16-Bit Instructions | Class | But deprecated... |
|-------------------------------|--------------------|--|
| MOV, MVN | Move | when Rm or Rd is PC |
| LDR, LDRB, LDRH, LDRSB, LDRSH | Load | for PC-relative "load literal" forms |
| STR, STRB, STRH | Store | |
| ADD, ADC, RSB, SBC, SUB | Add/Subtract | ADD/SUB SP, SP, #imm or when Rm, Rdn or Rdm is PC |
| CMP, CMN | Compare | when Rm or Rn is PC |
| MUL | Multiply | |
| ASR, LSL, LSR, ROR | Shift | |
| AND, BIC, EOR, ORR, TST | Logical | |
| BX, BLX | Branch to register | when Rm is PC |

The IT instruction remains fully available in order to execute ARMv7 T32 code, but to verify conformance with the deprecation a new control bit permits privileged software to disable the deprecated forms of the IT instruction, causing them to generate an Undefined Instruction exception.

6.2 Load-Acquire / Store-Release

These new instructions provide similar functionality to the A64 instructions described in section 5.3.7 above. Natural alignment is required in all cases, and to 8 bytes in the case of LDRAEXD and STRLEXD: an unaligned address will cause an alignment fault.

6.2.1 Non-Exclusive

LDRA<c> Rt, [Rn{,#0}]

Load-Acquire Word: loads a word from memory addressed by Rn into Rt.

LDRAB<c> Rt, [Rn{,#0}]

Load-Acquire Byte: loads a byte from memory addressed by Rn and zero-extends it into Rt.

LDRAH<c> Rt, [Rn{,#0}]

Load-Acquire Halfword: loads a halfword from memory addressed by Rn and zero-extends it into Rt.

STRL<c> Rt, [Rn{,#0}]

Store-Release Word: stores a word from Rt to memory addressed by Rn.

STRLB<c> Rt, [Rn{,#0}]

Store-Release Byte: stores a byte from Rt to memory addressed by Rn.

STRLH<c> Rt, [Rn{,#0}]

Store-Release Halfword: stores a halfword from Rt to memory addressed by Rn.

6.2.2 Exclusive

LDRAEX<c> Rt, [Rn{,#0}]

Load-Acquire Exclusive Word: loads a word from memory addressed by Rn into Rt. Records the physical address as an exclusive access.

LDRAEXB<c> Rt, [Rn{,#0}]

Load-Acquire Exclusive Byte: loads a byte from memory addressed by Rn and zero-extends it into Rt. Records the physical address as an exclusive access.

LDRAEXH<c> Rt, [Rn{,#0}]

Load-Acquire Exclusive Halfword: loads a halfword from memory addressed by Rn and zero-extends it into Rt. Records the physical address as an exclusive access.

LDRAEXD<c> Rt1, Rt2, [Rn{,#0}]

Load-Acquire Exclusive Double: loads two words from memory addressed by base to Rt1 and Rt2. Records the physical address as an exclusive access. The register Rt1 must be an even-numbered register less than 14 and Rt2 must be R_(t1+1).

STRLEX<c> Rd, Rt, [Rn{,#0}]

Store-Release Exclusive: stores a word from Rt to memory addressed by Rn, and sets Rd to the returned exclusive access status.

STRLEXB<c> Rd, Rt, [Rn{,#0}]

Store-Release Exclusive Byte: stores a byte from Rt to memory addressed by Rn, and sets Rd to the returned exclusive access status.

STRLEXH<c> Rd, Rt, [Rn{,#0}]

Store-Release Exclusive Halfword: stores a halfword from Rt to memory addressed by Rn, and sets Rd to the returned exclusive access status.

STRLEXD<c> Rd, Rt1, Rt2, [Rn{,#0}]

Store-Release Exclusive Double: stores two words from Rt1 and Rt2 to memory addressed by Rn, and sets Rd to the returned exclusive access status. The register Rt1 must be an even-numbered register less than 14 and Rt2 must be R_(t1+1).

6.3 VFP Scalar Floating-point

6.3.1 Floating-point Conditional Select

The new `VSEL` instruction is equivalent of the A64 `FCSEL` instruction in section 5.7.11, For A32 it provides an alternative to a pair of conditional `VMOV` instructions, while for T32 it compensates for the partial deprecation of `IT` described in §6.1 above, since it does not require an `IT` prefix. The condition code `<fc>` may be one of `GE`, `GT`, `EQ` and `VS` only; the effect of the inverted conditions `LT`, `LE`, `NE` and `VC` may be achieved by reversing the order of the source operands.

```
VSEL<fc>.F32 Sd, Sn, Sm
```

Single-precision conditional select: `Sd = if <fc> then Sn else Sm.`

```
VSEL<fc>.F64 Dd, Dn, Dm
```

Double-precision conditional select: `Dd = if <fc> then Dn else Dm.`

6.3.2 Floating-point minNum/maxNum

The new `VMAXNM` and `VMINNM` instructions implement the `minNum(x, y)` and `maxNum(x, y)` operations defined by the IEEE 754-2008 standard, and are equivalent to A64's `FMAXNM` and `FMINNM` instructions. They return the numerical operand when one operand is numerical and the other is a quiet NaN, but otherwise the result is identical to VFP `VMAX` and `VMIN`. These instructions may not be conditional.

```
VMAXNM.F32 Sd, Sn, Sm
```

Single-precision maxNum (scalar).

```
VMAXNM.F64 Dd, Dn, Dm
```

Double-precision maxNum (scalar).

```
VMINNM.F32 Sd, Sn, Sm
```

Single-precision minNum (scalar).

```
VMINNM.F64 Dd, Dn, Dm
```

Double-precision minNum (scalar).

6.3.3 Floating-point Convert (floating-point to integer)

These new instructions extend the existing ARMv7 VFP `VCVT` instructions by providing four additional explicit rounding modes, where ARMv7 `VCVT` rounds towards zero, giving an equivalent set of options to the A64 `FCVTS` and `FCVTU` instructions described in section 5.7.4.2. The syntax term `<r>` selects the rounding direction as follows: `N` (nearest, ties to even), `A` (nearest, ties away from zero), `P` (towards `+Inf`) or `M` (towards `-Inf`). These instructions may not be conditional.

```
VCVT<r>.S32.F64 Sd, Dm
```

Convert double-precision floating-point to signed 32-bit integer with explicit rounding direction (scalar).

```
VCVT<r>.S32.F32 Sd, Sm
```

Convert single-precision floating-point to signed 32-bit integer with explicit rounding direction (scalar).

```
VCVT<r>.U32.F64 Sd, Dm
```

Convert double-precision floating-point to unsigned 32-bit integer with explicit rounding direction (scalar).

```
VCVT<r>.U32.F32 Sd, Sm
```

Convert single-precision floating-point to unsigned 32-bit integer with explicit rounding direction (scalar).

6.3.4 Floating-point Convert (half-precision to/from double-precision)

The VFP `VCVTT` and `VCVTB` instructions are extended to permit direct conversion between half-precision and double-precision floating-point as a single operation, preventing double rounding errors. The syntax term `<y>` below is either `T` (top half) or `B` (bottom half).

`VCVT<y><c>.F64.F16` `Dd, Sm`

Convert from half-precision value in top or bottom of `Sm` to double-precision in `Dd` (scalar).

`VCVT<y><c>.F16.F64` `Sd, Dm`

Convert from double-precision value in `Dm` to in half-precision value in top or bottom of `Sd` (scalar).

6.3.5 Floating-point Round to Integral

The new “round to integral” instructions round a floating-point value to the nearest integral floating-point value of the same size, equivalent to the A64 `FRINT*` instructions in section 5.7.5. The only floating-point exceptions that can be raised by these instructions are `FPSCR.IOC` (Invalid Operation) for a Signaling NaN input, or `FPSCR.IDC` (Input Denormal) for a denormal input when flush-to-zero mode is enabled. For `VRINTX` only the `FPSCR.IXC` (Inexact) exception may be raised if the result is numeric and does not have the same numerical value as the source. A zero input gives a zero result with the same sign, an infinite input gives an infinite result with the same sign, and a NaN is propagated as for normal arithmetic.

A subset of the rounding instructions may be conditional when the syntax term `<x>` selects the rounding direction as follows: `Z` (towards zero), `R` (`FPSCR` rounding mode), or `X` (`FPSCR` rounding mode and signal inexactness).

`VRINT<x><c>.F64.F64` `Dd, Dm`

Round a double-precision value to nearest integral double-precision value (scalar), with half-way cases rounding according to `<x>`.

`VRINT<x><c>.F32.F32` `Sd, Sm`

Round a single-precision value to nearest integral single-precision value (scalar), with half-way cases rounding according to `<x>`.

The remaining rounding instructions are not conditional when syntax term `<r>` selects the rounding direction as follows: `N` (nearest, ties to even), `A` (nearest, ties away from zero), `P` (towards `+Inf`) or `M` (towards `-Inf`).

`VRINT<r>.F64.F64` `Dd, Dm`

Round a double-precision value to nearest integral double-precision value (scalar), with half-way cases rounding according to `<r>`.

`VRINT<r>.F32.F32` `Sd, Sm`

Round a single-precision value to nearest integral single-precision value (scalar), with half-way cases rounding according to `<r>`.

6.4 Advanced SIMD Floating-Point

The AArch32 Advanced SIMD extension continues to support only single-precision (32-bit) floating-point data types, with fixed operating modes of Round to Nearest, Default NaN and Flush-to-Zero. However it is extended with the addition of the following new instructions.

6.4.1 Floating-point minNum/maxNum

Vector forms of the new `VMAXNM` and `VMINNM` instructions described in section 6.3.2 above.

`VMAXNM.F32 Dd, Dn, Dm`

`VMAXNM.F32 Qd, Qn, Qm`

Single-precision maxNum (vector).

`VMINNM.F32 Dd, Dn, Dm`

`VMINNM.F32 Qd, Qn, Qm`

Single-precision minNum (vector).

6.4.2 Floating-point Convert

Vector forms of the floating-point to integer convert instructions described in section 6.3.3 above. The syntax term `<r>` selects the rounding direction: `N` (nearest, ties to even), `A` (nearest, ties away from zero), `P` (towards +Inf) or `M` (towards -Inf).

`VCVT<r>.S32.F32 Dd, Dm`

`VCVT<r>.S32.F32 Qd, Qm`

Convert single-precision floating-point to signed 32-bit integer with explicit rounding direction (vector).

`VCVT<r>.U32.F32 Dd, Dm`

`VCVT<r>.U32.F32 Qd, Qm`

Convert single-precision floating-point to unsigned 32-bit integer with explicit rounding direction (vector).

6.4.3 Floating-point Round to Integral

Vector forms of the floating-point rounding instructions described in section 6.3.5 above. The syntax term `<rx>` selects the rounding direction as follows: `N` (nearest, ties to even), `A` (nearest, ties away from zero), `P` (towards +Inf) or `M` (towards -Inf), `Z` (towards zero), or `X` (nearest, ties to even, signal inexactness)

`VRINT<rx>.F32.F32 Qd, Qm`

`VRINT<rx>.F32.F32 Dd, Dm`

Round a single-precision value to nearest integral single-precision value (vector), with half-way cases rounding according to `<rx>`.

6.5 Crypto Extension

Equivalent to the A64 cryptographic instructions listed in section 5.8.24.

| | | |
|--------------|------------|--|
| AESD.8 | Qd, Qm | AES single round decryption. |
| AESE.8 | Qd, Qm | AES single round encryption. |
| AESIMC.8 | Qd, Qm | AES inverse mix columns. |
| AESMC.8 | Qd, Qm | AES mix columns. |
| SHA1C.32 | Qd, Qn, Qm | SHA1 hash update accelerator (choose). |
| SHA1M.32 | Qd, Qn, Qm | SHA1 hash update accelerator (majority). |
| SHA1P.32 | Qd, Qn, Qm | SHA1 hash update accelerator (parity). |
| SHA1H.32 | Qd, Qm | SHA1 hash update accelerator (rotate left by 30). |
| SHA1SU0.32 | Qd, Qn, Qm | SHA1 schedule update accelerator, first part |
| SHA1SU1.32 | Qd, Qm | SHA1 schedule update accelerator, second part |
| SHA256H.32 | Qd, Qn, Qm | SHA256 hash update accelerator. |
| SHA256H2.32 | Qd, Qn, Qm | SHA256 hash update accelerator upper part. |
| SHA256SU0.32 | Qd, Qm | SHA256 schedule update accelerator, first part |
| SHA256SU1.32 | Qd, Qn, Qm | SHA256 schedule update accelerator, second part |
| VMULL.P64 | Qd, Dn, Dm | Polynomial multiply long, AES-GCM acceleration 64x64 to 128-bit. |

6.6 System Instructions

6.6.1 Halting Debug

New halting mode debug support instructions.

DCPS1

Debug switch to EL1 (valid in halting mode debug state only).

DCPS2

Debug switch to EL2 (valid in halting mode debug state only).

DCPS3

Debug switch to EL3 (valid in halting mode debug state only).

HLT #uimm6

Halting mode software breakpoint: enters halting mode debug state if enabled, else treated as UNALLOCATED. With 6-bit payload in uimm6.

6.6.2 Barriers and Hints

New barrier options and hint instructions to match those in A64, as described in section 5.9.5.

DMB {ISHLD, OSHLD, NSHLD, LD}

Data Memory Barrier is extended to support the new A64 Load-Load/Store options.

DSB {ISHLD, OSHLD, NSHLD, LD}

Data Synchronization Barrier is extended to support the new A64 Load-Load/Store options.

SEVL

Send Event Locally without being required to affect other processors, for example to prime a wait-loop which starts with a WFE instruction.

6.6.3 TLB Maintenance

TLB maintenance operations that are only required to apply to the last level of translation table walk of the first stage of translation (consistent with the A64 TLBI operations described in section System Management5.9.3 above) are added to A32 and T32 as follows.

TLBIMVALIS

Related to the existing A32/T32 TLBIMVAIS operation.

TLBIMVAALIS

Related to the existing A32/T32 TLBIMVAAIS operation.

TLBIMVALHIS

Related to the existing A32/T32 TLBIMVAHIS operation.

TLBIMVAL

Related to the existing A32/T32 TLBIMVA operation.

TLBIMVAAL

Related to the existing A32/T32 TLBIMVAA operation.

TLBIMVALH

Related to the existing A32/T32 TLBIMVAH operation.

TLB maintenance operations that are required to apply to individual entries from Stage 2 TLB structures, holding IPA to PA translations (consistent with the A64 TLBI system instructions described in section System Management 5.9.3 above) are added to the A32 and T32 instruction sets as follows:

TLBIIPAS2IS

Equivalent to the A64 IPAS2E1IS operation.

TLBIIPAS2LIS

Equivalent to the A64 IPAS2LE1IS operation.

Related to the existing A32/T32 TLBIIPAS2IS operation.

TLBIIPAS2

Equivalent to the A64 IPAS2E1 operation.

TLBIIPAS2L

Equivalent to the A64 IPAS2LE1 operation.

Related to the existing A32/T32 TLBIIPAS2 operation.

Note that these new system operations are accessed via the MCR instruction or, if implemented by an assembler, using a SYS mnemonic followed by the TLBI* operation name.