

HP Surestore Optical 330fx



Protecting data is critical to the competitive life of any business. Retrieving that data with speed and efficiency is equally critical. Hewlett-Packard SureStore optical jukeboxes provide immediate, reliable access to mass amounts of archived information from a central location. The HP 330fx has a 330GB capacity and holds up to 128 optical discs for quick, simultaneous retrieval by multiple users. Its improved design and advanced robotics deliver discs to the drive in 10 seconds, eliminating unnecessary waiting. It's the perfect solution for large networks, CAD/CAM, document management, and data archiving. It's a reliable and cost-efficient solution to all your data archiving demands, no matter how intense.

www.dooyoo.co.uk :: Computer :: Removable Disk Drives :: HP Surestore Optical 330fx

General	
Device Type	MO disk library
Enclosure Type	Internal
Interface	SCSI
Total Storage Capacity	333 GB
Installed Devices / Modules Qty (Max)	6 (12)
Removable Media Capacity	128
Max Supported Drives	12
Width	87.6 cm
Depth	74.2 cm
Height	180.7 cm
Weight	222.7 kg
Enclosure Colour	White
Localisation	English / Europe
Compatibility	PC



Storage Removable	
Type	6 x Magneto-Optical disk
Capacity	2.6 GB
Data Transfer Rate	5 MBps (external) / 3.4 MBps (internal)
Media Type	Magneto-Optical disk, WORM disk - 5.25"
Average Seek / Access Time	25 ms
Removable Media Capacity	128
Buffer Size	1 MB
Media Type	Magneto-Optical disk, WORM disk 5.25"
Media Included Qty	1

Storage Controller	
Type	SCSI - integrated
Controller Interface Type	Fast SCSI
Supported Devices	Removable media drive

Expansion / Connectivity	
Interfaces	1 x storage - Fast SCSI - 50 pin HD D-Sub (HD-50) 1 x storage - Fast Wide SCSI - 68 pin HD D-Sub (HD-68)

Miscellaneous	
Media Included Qty	1

Expansion / Connectivity	
Connections	1 x storage - Fast SCSI - 50 pin HD D-Sub (HD-50) 1 x storage - Fast Wide SCSI - 68 pin HD D-Sub (HD-68)

Miscellaneous	
Rack Mounting Kit	Not available
MTBF	10 [^] 5 hour(s)

Power	
Voltage Required	AC 110/220 V (50/60 Hz)

Miscellaneous	
Package Type	Retail



Power	
Voltage Required	AC 110/220 V \pm 10% (50/60 Hz)
Power Consumption Operational	560 Watt

Manufacturer Warranty	
Service & Support	1 year warranty
Service & Support Details	Limited warranty - parts and labour - 1 year - on-site

Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90%
Vibration Tolerance	0.21 g @ 5-500 Hz (operating)